

1

2

3

4

A

A

B

B

C

C

D

D


REVISIONS

REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.06.23	阿树

SPEAFICATIONS

1.ELECTRICAL

Con tact rating	0.1A,30VDC
Con tact resistance	50mΩ Max
Insulation resistance	100MΩ Min .at 250VDC
Dielectric strength	250VAC Min .for 60sec



CIRCUIT DIAGRAM

2.MECHANICAL AND ENVIRONMENTAL

●Temperature ratong	Operating -15℃ to +55℃ storage.-25℃to +65℃
● Operation	250±50gf
● Stroke	Lock Stroke .15±0.2mm Full stroke,2.0±0.2mm
● Operating life	Full load:1x10 ⁴ cycles N0 load:1x10 ⁵ cycles
● Con tact form	DPDT

PAPT NO	XKB5858-Z-F-75
OPERATION	W:NO LOCK Z:LOCK

7	Contact	2	Phosphor Bronze	Plating silvering
6	Terminal	6	Brass	Plating silvering
5	Spring	1	Sus	Natural
4	Base	1	PPA	
3	Crochet Needle	1	Sus	Natural
2	Cover	1	PPA	
1	Keystake	1	PPA	
ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN

阿树

VIEW:

MODEL TYPE:
KEY SWITCH

CHECKED

UNIT: mm/in

PART NO.:
XKB5858-Z-F-75

APPROVED

SIZE: A4

DWG NO.:

X-XKB5858-Z-F-75

SCALE

PAGE

REVISION

1/1

A1

www.helloxkb.com

www.helloxkb.cn

www.xk-dg.cn

XKB INDUSTRIAL PRECISION CO.,LIMITED

1

2

3

4