



CONNECTOR HOUSINGS



✓ Active

TE CONNECTIVITY (TE)
POWER DBL LOCK PLUG HSG 3P(GWT)
[Power-Signal Double Lock](#) | [Power Double Lock](#)

5-177899-1
TE Internal Number: 5-177899-1

- [Always EU RoHS/ELV Compliant](#)
- Connector System **Wire-to-Board, Wire-to-Panel, Wire-to-Wire**
- Centerline **3.96 mm [.156 in]**
- Number of Positions **3**
- Number of Rows **1**
- Housing Material **Nylon 6/6**



No documentation available.

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features	Connector System	Wire-to-Board, Wire-to-Panel, Wire-to-Wire
	Connector Style	Plug
	Sealed	No
	Applies To	Panel, Printed Circuit Board, Wire/Cable
	Product Type	Connector
	Connector Type	Housing
Configuration Features	Number of Positions	3
	Number of Rows	1

	Selectively Loaded	No
	Preloaded	No
Electrical Characteristics	Operating Voltage (VAC)	300
Body Features	Sealable	No
Contact Features	Contact Type	Socket
	Shunts/Shorting Bars	Without
	Multiple Contact Types	Without
Mechanical Attachment	Contact Retention	Without
Housing Features	Centerline	3.96 mm [.156 in]
	Housing Material	Nylon 6/6
	Housing Color	Natural
Dimensions	Length (mm)	13.9
	Height	20.6 mm [.811 in]
	Width (mm)	6.9
Usage Conditions	Operating Temperature Range	-30 – 105 °C [-22 – 221 °F]
Operation/Application	Assembly Integration Feature	Without
	For Use With	Cap: 177907 or 179464, Contacts: 177914 or 177915, Double Lock Plate 177919-1, Header: 179839, Header: 179844 (3 pos./ 2 circuit)
Identification Marking	Circuit Identification Feature	Without
Industry Standards	CSA Rating	Certified
	CSA File Number	LR7189
	UL Rating	Recognized
	CSA Certified	Yes
	VDE Tested	Yes
	UL File Number	E28476

Agency/Standard		CSA, UL
Packaging Features	Packaging Quantity	400
	Packaging Method	Bag
Other	Comment	Part 179844 is a 3 position header, no pin in position 2.
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

