32.768 kHz LOW FREQUENCY SMD CRYSTAL

ABS25

Pb in High Temperature Solder
(exempt 7(a) per 2015/863/EU Annex)

RoHS Compliant



8.0 x 3.8 x 2.5 mm

FEATURES:

- Plastic molded SMD
- 2.5mm height ideal for high density circuit boards
- Suitable for RoHS compliant reflow
- Extended temperature -40°C to +85°C for industrial applications

APPLICATIONS:

- Wide range in communication & measuring equipment
- Commercial & Industrial applications
- Computer clock

STANDARD SPECIFICATIONS:

Parameters	Minimum	Typical	Maximum	Units	Notes
Nominal Frequency	-----	32.768	-----	kHz	
Frequency Range	30	-----	100	kHz	Other frequencies
Operating Temperature	-40	-----	+85	ºC	
Turnover Temperature	+20	+25	+30	ºC	
Storage Temperature	-55	-----	+125	ºC	
Frequency Tolerance @+25ºC	-20	-----	+20	ppm	32.768kHz
	-30	-----	+30		Other frequencies
Capacitance Ratio (C0/C1)	-----	450	-----		32.768kHz
	-----	425 to 800	-----		Other frequencies
Frequency Coefficient (ß)		-0.035±0.01		ppm/ºC^2	
Equivalent series resistance (R1)	-----	-----	50	kΩ	
Shunt capacitance (C0)	-----	1.35	-----	pF	32.768kHz
		0.8 to 1.7		pF	Other frequencies
Load capacitance (CL)		12.5		pF	See options
Drive Level	-----	-----	1	µW	
Aging @ 25°C±3°C (First year)	-3	-----	+3	ppm	32.768kHz
	-5	-----	+5		Other frequencies
Insulation Resistance	500	-----	-----	MΩ	@ 100Vdc ± 15V

OPTIONS AND PART IDENTIFICATION:

(Left blank if standard)

ABS25 - [ ] - [ ] - [ ] - [ ]

Frequency in kHz	Load Capacitance (pF)	Freq. Tolerance	Packaging
Please specify the frequency in kHz. e.g. 32.768kHz	Blank: 12.5pF	1: ± 10 ppm	Blank: Bulk
	Please specify load cap. in pF (ex. 6pF) if not standard	5: ± 15 ppm	T: Tape and Reel
		2*: ± 20 ppm	
		3: ± 25 ppm	
		4**: ± 30 ppm	

**STD for 32.768kHz. Please leave this blank if F is 32.768kHz.*

***STD for other frequencies. Please leave this blank if F is not 32.768kHz.*

ABRACON LLC

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-30-19

ABRACON IS
ISO9001-2015
CERTIFIED

32.768 kHz LOW FREQUENCY SMD CRYSTAL

ABS25


Pb in High Temperature Solder
(exempt 7(a) per 2015/863/EU Annex)


RoHS Compliant



8.0 x 3.8 x 2.5 mm


OUTLINE DRAWING:







Electrode Arrangement
Pin 2 and 3 are not connected
to the GND (Floating)

Recommended Land Pattern






Dimension Table	
A	3.8 ± 0.2 MAX
B	8.4 MAX
C	5.5 ± 0.1
D	2.5 ± 0.1 MAX
E	0.5
F	0.5
G	0.9 Ref.



Dimensions: (inches) mm


TAPE & REEL:

T = Tape and reel 3,000pcs/reel



Dimensions: mm

REFLOW PROFILE



ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.

ABRACON LLC

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09-30-19

ABRACON IS
ISO9001-2015
CERTIFIED