

Pitch:2.00x2.00mm(0.079 " x0.079 ")
 Female Header Side Entry S.M.T Type

ELETE
 Professional Connecting Solution
HFLDM51 Series


Specifications

Current Rating:2.0 Ampere
 Insulation Resistance:1000MΩ Min
 Dielectric Withstanding:500V AC
 Contact Resistance:20mΩ Max
 Operating Temperature:-40℃ to +105℃





Materials

Contact Material: Phosphor Bronze
 Insulation Material: Polyester,UL 94V-0
 LCP/NL6T

All material RoHS&Reach Compliant
 Halogen-free is available



Mating with



PS:Suggested Mating Pin Length:3.0~4.1 mm

No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information	
	A	C		A	C		A	C		A	C
03	4.00	6.00	09	16.00	18.00	15	28.00	30.00	21	40.00	42.00
04	6.00	8.00	10	18.00	20.00	16	30.00	32.00	22	42.00	44.00
05	8.00	10.00	11	20.00	22.00	17	32.00	34.00	23	44.00	46.00
06	10.00	12.00	12	22.00	24.00	18	34.00	36.00	24	46.00	48.00
07	12.00	14.00	13	24.00	26.00	19	36.00	38.00	25	48.00	50.00
08	14.00	16.00	14	26.00	28.00	20	38.00	40.00			