

- Cleaners & Compounds
- 3Mâ„¢ Breadboards & Test Clips
- 3Mâ„¢ Cable & Assemblies
- 3Mâ„¢ Copper Interconnects
- 3Mâ„¢ Fiber Optics
- 3Mâ„¢ Fire Protection
- 3Mâ„¢ Heat Shrink
- 3Mâ„¢ Identification Systems
- 3Mâ„¢ Occupational Health & Safety Products
- 3Mâ„¢ Protective Bumpers
- 3Mâ„¢ Reclosable Fasteners
- 3Mâ„¢ Splicing, Terminating & Ducting
- 3Mâ„¢ Static Control
- 3Mâ„¢ Tapes
- 3Mâ„¢ Terminals, Kits & Tools
- 3Mâ„¢ Vacuums & Accessories
- 3Mâ„¢ Warehousing & Packaging Supplies
- 3Mâ„¢ Wire Connectors



[\[click to enlarge\]](#)

GTIN(UPC/EAN) : 0 00 54007 21742 8  
 3M Id : 80 - 6100 - 0141 - 6

### Additional Information

A ring is the standard style of tongue. The safest and most reliable; it cannot be removed unless mounting screw is removed.

### Learn More . . .

[Packaging Data](#)


[Ring Tongues - Vinyl Insulated Brazed Seam 22 AWG - Product Selection Guide \(PDF 28.6 K\)](#)

[Scotchlok Terminals MV18 - 2R/S THRU MV10 - 12 Sheet \(PDF 24.2 K\)](#)

[Terminal Stud Size Chart - Product Selection Guide 5.2 K\)](#)

#### Please Note:

Adobe® Acrobat® Reader is required to view PDF documents.



### Other Tools

- What's New
- Sales Contacts
- U.S. Distributors

### Search This Product Catalog

By Keyword

### Characteristics

Agency Approvals	UL and CSA
Barrel Style	Brazed
China RoHS - Below MCV	No
CSA File Number	LR22190
EPC Can View	Public
EU RoHS Compliant	No
Insulation Material	Vinyl
Stud Size	1/4 Inch
Terminal Style	Standard
Terminal Type	Ring
UL File Number	E23438
Wire Gauge Range	18 to 22 American Wire Gauge (AWG)