

GRM21B1X1A823JA01#

" # " indicates a package specification code.

Recommended

Flow OK

Reflow OK

Complies with RoHS

< List of part numbers with package codes >
GRM21B1X1A823JA01L , GRM21B1X1A823JA01K , GRM21B1X1A823JA01C , GRM21B1X1A823JA01B

Shape



L size	2.0 ± 0.1mm
W size	1.25 ± 0.1mm
T size	1.25 ± 0.1mm
External terminal width e	0.2 to 0.7mm
Distance between external terminals g (Min.)	0.7mm
Size code in mm(inch)	2012 (0805)

References

Packaging	Specifications	Minimum quantity
L	Embossed tape (φ 180mm)	3000
K	Embossed tape (φ 330mm)	10000
C	Bulk case	5000
B	Packing in bulk	1000

Mass (typ.)	
1 piece	16mg
Reel (φ 180mm)	91g

Specifications

Capacitance	82000pF ± 5%
Rated voltage	10Vdc
Temperature characteristics (complied standard)	SL(JIS)
Temperature coefficient	+350 to -1000ppm/
Temperature range of temperature characteristics	20 to 85
Operating temperature range	-55 to 125

 Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.