

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A1	N/A		尺寸修正, 图面升级整理图面	2024.8.30	阿树
A2	N/A		独立各PIN数图纸, 增加开孔定位尺寸	2024.12.10	阿树

PART NO.:





X06 44 W T Z B 2
① ② ③ ④ ⑤ ⑥ ⑦

- ①Series N0.
②Row No.Pin No:15PIN
③Welding Board Angle :W-Male
④T:Tradutlional
⑤Planting Categoty:
1:1U' ;2:2U' ;3:3U' ;4:5U' ;5:15U' 6:30U'
;7:AuSn
⑥B:Black W:White BL:Blue Y:Yellow G:Green R:Red
⑦1:TYPE-1; 2:TYPE-2; 3:TYPE-3; 6:TYPE-6

Specifications:

规格:

- 1.Voltage rating:250VAC/DC
额定电压: 250V AC/DC
2.Current rating:3A AC/DC
额定电流: 3A AC/DC
3.Withstanding voltage:500V AC/minute
耐受电压: $\geq 500V$ AC/分钟
4.Temperature range: $-55^{\circ}C$ $-+105^{\circ}C$
温度范围: $-55^{\circ}C$ $-+105^{\circ}C$
5.Insulation resistance:1000M Ω MIN
绝缘电阻: $\geq 1000M\Omega$
6.Contact resistance:30m Ω Max
接触电阻: $\geq 30m\Omega$
7.Material:
材料和成本:
8.INSULATOR:PBT UL 94V-0
绝缘体: PBT UL 94V-0
9.SHELL:SPCC-SD Plated Ni /Au/Sn
外壳: 铁合金 镀镍、金、锡
10.CONTACT MATERIAL:Copper Alloy
触点材料: 铜合金

铆合方式	TYPE-1: 铆合	TYPE-6: 直铆锁	TYPE-3: 叉锁	TYPE-2: 铆合锁螺丝
图式				
DESIGN	阿树	VIEW: 	MODEL TYPE: D-SUB	
CHECKED		UNIT: mm/in	PART NO.: X0644WT7B2	
APPROVED		SIZE: A4	DWG NO.: X-X0644WT7B2	
SCALE			PAGE	REVISION
N/A			1/1	A2

AuGLAR	$\pm 5^{\circ}$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERANCES	

XKB 星树
Connection

XKB INDUSTRIAL PRECISION CO.,LIMITED