



EN 60603 [DIN 41612] Connector, Type G

SCHROFF



View of rear of plug

Other Views



Catalog Number: 69001-723

Back To Product

- Requirement class 2 as per EN 60603 (DIN 41642)

Description:

Connector

Product family:

PCB Accessories



Select product specifications before modifying or adding to project list or requesting a quote.

Configuration-defining

Female Connector ▾

[Clear Selection](#)

Quantity

Add Item to Project List +

Documents



Main Catalog - Connectors, busbars




User Information

Technical Data

Qty	1 piece	Connector pitch [mm]	5.08
Number of contacts	64	Creepage distances contact-contact [mm]	> 3.0
Row assignment	z, b, d, f	Current load max. at 20 °C [A]	6
Other	Female connector	Test voltage Ueff contact-contact [kV]	1.55
Connector	Wire-wrap pins, length 22 mm, 1 mm x 1 mm; straight	Test voltage Ueff contact-earth [kV]	2.5
		Contact resistance [mΩ]	≤ 20
		Separate coding	yes
		Contact surface	solidly gold-plated
		Insertion and withdrawal forces [N]	< 100 N
		Air gap contact-contact [mm]	> 1.6

Accessories



Panhead screw, Torx (M2.5x7), steel nickel plated, PU 100 pcs

24560-147

Add Item to Project List +

EXPLORE

- About Us
- Services & Capabilities
- News & Events
- Newsletter Subscriptions
- Strategic Partnerships
- Investor Relations

CONTACT

- Customer Service
- Find a Sales Office or Distributor
- Global Locations
- Product Compliance & Certifications
- Partner Login

DOWNLOAD

- Download Center
- Reference Projects
- Videos
- Product Configurators
- Warranties and Terms of Sale & Procurement

© 2018 nVent. All rights reserved | Privacy Policy | Terms of Use | Cookie Policy | Imprint | Site Map

Connect With Us

