

深圳市金航标电子有限公司

VH条形连接器

TECHNICAL PARAMETER (3.96 mm)

技术参数

间距 (PITCH): 3.96mm

极数 (Poles): 2—16

适用基板厚度 (Applicable PC board thickness): 1.6mm

额定电流 (Current rating): 5A, AC, DC

额定电压 (Voltage rating): 250V, AC, DC

工作温度 (Working Temperature): -25 °C ~ +85 °C

耐压值 (Withstand voltage): 1500V, AC/min

接触电阻 (Contact resistance) $\leq 0.01 \Omega$

绝缘电阻 (Insulation resistance) $\geq 1000M \Omega$


材料 MATERIAL

基座 (HOUSING): 尼龙66UL94V-0 (NYLON66 UL94V-0)

插针 (PIN) 黄铜 (BRASS) 表面镀纯锡 (PURE TIN-PLATED)


端子 (TERMINAL)

VH-nT




阳连接器 (直式) (WAFER-180°)

VH-nA




阳连接器 (弯式) (WAFER-90°)

VH-nAW






阳连接器 (长弯式) (LONG WAFER-90°)

VH-nAWT



阴连接器 (HOUSING)

VH-nY



极数	编号		尺寸	
			A	B
2	VH-2Y	VH-2A(W/T)	3.96	7.92
3	VH-3Y	VH-3A(W/T)	7.92	11.88
4	VH-4Y	VH-4A(W/T)	11.88	15.84
5	VH-5Y	VH-5A(W/T)	15.84	19.80
6	VH-6Y	VH-6A(W/T)	19.80	23.76
7	VH-7Y	VH-7A(W/T)	23.76	27.72
8	VH-8Y	VH-8A(W/T)	27.72	31.68
9	VH-9Y	VH-9A(W/T)	31.68	35.64
10	VH-10Y	VH-10A(W/T)	35.64	39.60
11	VH-11Y	VH-11A(W/T)	39.60	43.56
12	VH-12Y	VH-12A(W/T)	43.56	47.52
13	VH-13Y	VH-13A(W/T)	47.52	51.48
14	VH-14Y	VH-14A(W/T)	51.48	55.44
15	VH-15Y	VH-15A(W/T)	55.44	59.40
16	VH-16Y	VH-16A(W/T)	59.40	63.36