

S1SS-20-28-GF-03.00-D-NUS

S1SS-10-28-GF-03.00-L1

S1SS, S1SST SERIES

(1.00 mm) .03937"

MICRO CABLE ASSEMBLY

SPECIFICATIONS

For complete specifications see www.samtec.com?S1SS or www.samtec.com?S1SST

Insulator Material:

Nylon, White (with latch)
Black, LCP (without latch)

Contact Material:

Phosphor Bronze

Plating:

Au or Sn over
50 μm (1.27 μm) Ni

Operating Temp Range (S1SS(T)/T1M):

-10 °C to +85 °C (PVC)
-40 °C to +125 °C (Teflon® cable with -GF plated contact)

Current Rating (28 AWG):

3.3 A per pin
(1 pin powered)

Voltage Rating:


250 VAC/353 VDC

Wire: 28 or 30 AWG

RoHS Compliant: Yes

*DuPont™ Teflon® is a registered trademark of the E.I. du Pont de Nemours and Company or its affiliates.

Mates with:
T1M



ALSO AVAILABLE (MOQ Required)

- Other sizes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



COMPONENTS

- For body, see www.samtec.com?ISS1
- For contacts, see www.samtec.com?CC09R or www.samtec.com?CC09M

APPLICATION

S1SS CABLE COLOR CODING	
PIN	COLOR
1	BROWN
2	RED
3	ORANGE
4	YELLOW
5	GREEN
6	BLUE
7	VIOLET
8	GRAY
9	WHITE
10	BLACK
ETC	REPEAT

Notes:
Teflon® cable is intended for crimp only. Contact Samtec for solderable cable applications.

Some lengths, styles and options are non-standard, non-returnable.

TYPE	NO. OF POSITIONS	WIRE GAUGE	PLATING OPTION	ASSEMBLED LENGTH	OPTION
S1SS = Single Row PVC Cable	-02, -03, -05, -07, -10 -15, -20 (Standard sizes)	-28 = 28 AWG -28C = 28 AWG Color Coded Cable (S1SS only)	-GF = 3 μm (0.07 μm) Gold on contact and tail -T = Tin	-“XX.XX” = Assembled Length in Inches (45.72 mm) 01.80" min.	(Required Callout) -L = Single Ended With Latch -L1 = Double Ended Latch down, straight (Pin 1 to Pin 1) -L3 = Double Ended Latch up, straight (Pin 1 to Pin N) -S = Single Ended No Latch -D-NUS = Double Ended No Latch, “N” up, straight -D-NDS = Double Ended No Latch, “N” down, straight
S1SST = Single Row *Teflon® Cable (28 AWG only)		-30 = 30 AWG -30C = 30 AWG Color Coded Cable (S1SS only)			

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Components must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.