

FOC-FR19:1U-OS12-LCD6-OM1 - Patch panel



1419974

<https://www.phoenixcontact.com/pc/products/1419974>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Fiber optic distribution box, type: 19"-rack mount fiber optic distribution box, degree of protection: IP20, number of positions: 1*12, marking material: aluminum, color: gray



Your advantages

- Compact design with MT ferrule
- Plug-and-play
- Fast and reliable cabling, thanks to clear connections on the front

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1419974 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Product key | ABNHAC |
| GTIN | 4055626198927 |
| Weight per piece (including packing) | 1,677 g |
| Weight per piece (excluding packing) | 1,677 g |
| Customs tariff number | 85367000 |
| Country of origin | CN |

1419974

<https://www.phoenixcontact.com/pc/products/1419974>

Technical data

Product properties

| | |
|------------------------|-------------------------|
| Product type | Network distributor box |
| Housing type | Component housing |
| Type | 19" rack patch module |
| Sensor type | Ethernet |
| Number of positions | 12 |
| No. of cable outlets | 0 |
| Number of module slots | 6 |
| Number of slots | 12 |
| Protective cover | yes |

Data management status

| | |
|------------------|----|
| Article revision | 01 |
|------------------|----|

Electrical properties

| | |
|---------------------|-----------------------|
| Attenuation | typ. 0.35 dB |
| | max. 0.6 dB |
| Transmission medium | Multi-mode fiberglass |

Dimensions

| | |
|--------|----------|
| Width | 482.6 mm |
| Height | 132 mm |
| Depth | 220 mm |

Material specifications

| | |
|--|---------------------|
| Color | gray |
| Flammability rating according to UL 94 | V0 |
| Ferrule material | Zirconia ceramics |
| Housing material | Aluminum alloy |
| Housing surface material | Powder-coated, gray |
| Outer sheath, material | LSFH |

Cable/line

| | |
|------------------------|------------------------------|
| Cable type | Multimode fiberglass |
| Cable type | Fan out |
| Outer sheath, material | LSFH |
| Halogen-free | complying with IEC 60754-1/2 |

FO cable

| | |
|------------------|----------------------------------|
| Number of fibers | 12 |
| Fiber | 62.5/125 µm OM1 |
| Fiber type | Multimode fiberglass 62.5/125 µm |
| Attenuation | typ. 0.15 dB |

FOC-FR19:1U-OS12-LCD6-OM1 - Patch panel



1419974

<https://www.phoenixcontact.com/pc/products/1419974>

| | |
|---------------------|-----------------------|
| Transmission medium | Multi-mode fiberglass |
|---------------------|-----------------------|

Mechanical properties

Mechanical data

| | |
|-----------------------------|---|
| Insertion/withdrawal cycles | ≥ 500 (In the event of repeated cleaning) |
|-----------------------------|---|

Characteristics

| | |
|-------------|--------------|
| Attenuation | typ. 0.35 dB |
|-------------|--------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-----------------------------------|
| Degree of protection | IP20 |
| | IP20 |
| | IP67 |
| Ambient temperature (operation) | -40 °C ... 85 °C (IEC 61300-2-22) |

Mounting

| | |
|---------------|----------------|
| Mounting type | Screw mounting |
| Thread type | () |

1419974

<https://www.phoenixcontact.com/pc/products/1419974>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440219 |
| ECLASS-12.0 | 27440219 |
| ECLASS-13.0 | 19170113 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001130 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 43223300 |
|-------------|----------|

1419974

<https://www.phoenixcontact.com/pc/products/1419974>

Environmental product compliance

EU RoHS

| | |
|---|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|

China RoHS

| | |
|--|--|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

FOC-FR19:1U-OS12-LCD6-OM1 - Patch panel



1419974

<https://www.phoenixcontact.com/pc/products/1419974>

Accessories

FOC-OP12-OP12-GL02/10 - Connecting cable

1415353

<https://www.phoenixcontact.com/pc/products/1415353>



Double-end preassembled cable, type: circular connector, degree of protection: IP68, number of positions: 12

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com