

NOTES:

1. MATERIAL: SEE "TABLE 1";

2. FINISH: SEE "TABLE 1";

3. ELECTRICAL :

3-1.CONTACT CURRENT RATING :

5A(VBUS PIN 1.5A/PIN),

5A(GND PIN 1.25A/PIN MAX),0.25A/PIN(OTHER PIN).

3-2.INSULATION RESISTANCE :

100 MEGAOHMS MIN. AT 250VDC.

3-3.DIELECTRIC WITHSTANDING VOLTAGE :

100VAC MIN.

3-4.LOW LEVEL CONTACT RESISTANCE :

INITIAL 40mΩ MAX.

AFTER 50mΩ MAX.

4.MECHANICAL CHARACTERISTICS :

4-1. MATING FORCE: 5~20N.;

4-2. UNMATING FORCE: 8~20N(INITIAL),6~20N(AFTER 5000 CYCLES);

4-3.DURABILITY : 5,000 MATING CYCLES.

4-4.OPERATING TEMPERATURE :-40°C TO +80°C

INTERFACE(FRONT VIEW)

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	DP1	DN1	SBU1	VBUS			GND
GND			VBUS	SBU2	DN2	DP2	CC2	VBUS			GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1

PIN ASSIGNMENT

PIN NO.	A1&B12	A4&B9	B8	A5	B7	A6	A7	B6	A8	B5	A9&B4	A12&B1
SIGNAL NAME	GND	VBUS	SBU2	CC1	DN2	DP1	DN1	DP2	SBU1	CC2	VBUS	GND
PCB PAD NO.	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12

TABLE 1:

NO.	PART NAME	QTY	MATERIAL	DESCRIPTION	REMARK
⑤	Shell-1	1	Stainless steel	NI PLATING;	T=0.25mm
④	MID PLATE	1	Stainless steel		T=0.15mm
③	Terminal-B	8	铜镍硅合金	Au:3u" PLATING;	T=0.15mm
②	Terminal-A	8		Au:3u" PLATING;	T=0.15mm
①	Housing	1	HIGH TEMP	Black	



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ±0.30

X.XX ±0.25

X.XXX ±0.15

X' ±2" X.X' ±0.5'

UNIT: mm [inch]

SCALE:1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

USB TYPE C 防水母座16P 带耳SMT

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYCW339-USBC16-151B

APPROVED BY:

邱敏

DATE :




2014-02-23

DRAW NO:




HYC-2206091135

SHEET NO.


1 OF 1



RECOMMENDED PCB LAYOUT(TOP VIEW)

THICKNESS T=1.0mm
DEFAULT TOLERANCE+/-0.05

组装示意图



开孔建议尺寸

组装时, 加润滑油后
更容易组装