






芯数	2P	3P	4P	5P	6P	7P	8P	10P	12P	2P B	3P B	4P B	2P C	3P C	4P C
额定电压	60V	60V	60V	60V	60V	60V	60V	30V	30V	300V	300V	300V	125V	125V	125V
额定电流	5A	5A	5A	5A	5A	5A	5A	2A	2A	10A	10A	10A	10A	10A	10A
防水等级	IP67/IP68														
使用温度	-45°C~105°C														



6	E10 紧锁螺帽	尼龙	/	pc	1
5	E10 组装式防水硅胶塞	硅胶	/	pc	1
4	E10 插头主体	尼龙	/	pc	1
3	防水O型圈 φ13Xφ10X1.5	橡胶	/	pc	1
2	E系列 焊线式公针长针	黄铜	镀金	pc	2~12
1	E10 卡扣式针型对接插头外壳	尼龙	/	pc	1
No.	Specification	Material	Treat	Unit	Q'ty

(UNLESS SPECIFIED)
≤10 ±0.1
<10~≤20 ±0.2
<20~≤50 ±0.5
Angle ±1°


THIRD ANGLE

CHK

APVD

UNIT
MM

SIZE
A4

REV
A

SHEET
1 OF 1



TITLE
E10 卡扣式针型组装式对接插头

PART NO

DRAWING NO
E10P—BK1—Px

D