

CRM089P1 - Header

Number of poles: 16, 16A, 2.5mm², 300V, Pitch 5 mm,
Polarized, Green (RAL 6032), Soldering technology Wave,
UL, VDE, IMQ, CSA



Number of poles:	16
Number of levels:	2
Sides configuration:	Polarized
Pitch:	5 mm
Voltage:	300 V
Current :	16 A
Wire section:	0.05 ÷ 2.5 mm ²
Available approvals:	UL, VDE, IMQ, CSA

General Data

Features

Screw dimension	na
Insertion force	3 N
Withdrawal force	1.5 N
Operating temperature range	0 ÷ 0
Contact resistance	<15 mOhm
Insulation resistance	>1 GOhm

Certifications

CSA (n.LR 102896)

Rated voltage	300 V
Nominal current	15 A
Wire section	0

IMQ (n.EM672)

Rated voltage	300 V		
Nominal current	12 A		
Wire section	2.5 mm ²		
Insulating category	I		
Overvoltage category/Pollution degree	III/3	III/2	II/2
Impulse voltage	4kV	4kV	4kV
Rated voltage	250V	300V	600V
Insulation voltage	250V	320V	630V

UL (n.E167473)

Rated voltage	300 V
Nominal current	15 A
Wire section	0

