





REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		端子焊脚长度变更, 更新图框	2024.10.18	桑葚



PCB_LAYOUT

规格 Specifications:

1.电气特性:Electyical:

额定电压 Voltage rating:30V DC
额定电流 Current rating:1.5A Max
绝缘电阻 Insulation resistance:1000MΩ Min
接触电阻 Contact resistance:30mΩ Max
耐电压 Withstanding voltage:500V AC/minute

2.机械特性:Mechanical:

寿命 Durability: 3000 cycles Min
插入力 Connector Insertion forces: 3.75Kgf Max
拔出力 Connector unmating forces: 1.02Kgf Min
端子保持力 PIN RETENTION FORCE:1.2Kgf Min
工作温度 Temperature range:-40℃to+85℃

物理性能:Mechanical:

- 1.插拔力: Connector Mate and Unmate Force
Mate force:3.75kgf(MAX)
Unmate force:1.02kgf(MIN)
- 2.端子保持力: Terminal Retention
1.2kgf(MIN)

???Material:

- 1.塑胶:Housing:
Hing Temperature Thermoplastics,
UI 94V-0 PBT/LCP White/Black
- 2.端子:Contact:Copper Alloy C2680
- 3.外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

- 1.端子:Contact: Plated Gold in Mating Area;
Tin On Solder Tails
- 2.外壳:Shell:
Nickel Plating

3	SHELL	C2680 T=0.30mm	Ni Plated	1PCS
2	CONTACT	C2680 T=0.20mm	Au PLATING ON CONTACT AREA; Tin PLATING ON SOLDER TAIL;NICKEL UNDERPLATING OVERALL	1SET
1	HOUSING	PBT/LCP UL94V-0	BLACK/WHITE	1PCS
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	桑葚	VIEW:	MODEL TYPE: USB2.0 PLUG
CHECKED		UNIT: mm/in	PART NO.: U217-041N-1WV81
APPROVED		SIZE: A4	DWG NO.: X-U217-041N-1WV81
SCALE			PAGE
N/A			1/1
REVISION			A1