





Code-x	H	Code-x	H
A	4.30	O	11.00
B	4.50	P	11.50
C	5.00	Q	12.00
D	5.50	R	12.50
E	6.00	S	13.00
F	6.50	T	13.50
G	7.00	U	14.00
H	7.50	V	15.00
I	8.00	W	15.50
J	8.50	X	16.00
K	9.00	Y	16.50
L	9.50	Z	17.00
M	10.00	18	18.00
N	10.50	19	19.00



Technical drawing of a vertical assembly. The drawing shows two vertical rectangular components. The top component has a width of 21.00 and a height of 0.827. The bottom component has a width of 17.00 and a height of 0.669. The components are separated by a gap. The drawing includes dimension lines and arrows indicating the measurements.

Contact Rating:	50mA, 12V DC
Contact Resistance:	100mΩ max
Insulation Resistance:	100MΩ min. 500V DC
Dielectric Strength:	250V AC/1minute
Travel:	0.25mm
Operating Temp:	-40°C ~ +80°C
Storage Temp:	-40°C ~ +80°C

PAPT NO	TS-1102SD-A-Q-R
Operating Force	A:100gf B:160gf C:260gf
Height	Code-x
Color	B:Black BR:Brown R:Red O:Orange Y:Yellow BL:Blue W:White



P.C.B MOUNTING HOLES

AuGLAR	$\pm 5^\circ$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树	VIEW:		MODEL TYPE:	TACT SWITCH
CHECKED		UNIT: mm/in		PART NO.:	TS-1102SD-A-Q-R
APPROVED		SIZE: A4		DWG NO.:	TS-1102SD-A-Q-R
PRECISION CO., LIMITED			SCALE	PAGE	REVISION
			N/A	1/1	A1