

## Features

- Analog Switch Voltage: 3.3 V, 5 V, 10 V,  $\pm 5$  V
- Low On-State Resistance:
  - Typical 50  $\Omega$  at  $V_S = \pm 4.5$  V or 9 V
  - Typical 60  $\Omega$  at  $V_S = 4.5$  V
  - Typical 300  $\Omega$  at  $V_S = 3$  V
- Bandwidth: 200 MHz
- Fast Switching Time:  $t_{ON} = 60$  ns,  $t_{OFF} = 50$  ns
- Break-Before-Make Switching
- Operating Temperature Range:  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$

## Applications

- Industry Control Systems
- Battery-Powered Systems
- Audio Signal Routing
- Instrumentation

## Description

The TPW4051 is a single-pole octal-throw (SP8T) analog switch, suitable for use in analog or digital 8:1 multiplexer/demultiplexer applications. The switch features three digital select inputs (S0, S1, and S2), eight independent inputs/outputs (An), a common input/output (A), and a digital enable input ( $\bar{E}$ ). When  $\bar{E}$  is high, the switch is turned off.

The device is designed on an enhanced process that provides lower power dissipation and high switching speed. The device operates equally well as either multiplexers or demultiplexers, and has an input range that extends to the supplies. All channels exhibit break-before-make switching action, preventing momentary shorting when switching channels.

## Table of Contents

<b>Features</b> .....	<b>1</b>
<b>Applications</b> .....	<b>1</b>
<b>Description</b> .....	<b>1</b>
<b>Switch Selection Guide</b> .....	<b>3</b>
<b>Revision History</b> .....	<b>3</b>
<b>Pin Configuration and Functions</b> .....	<b>4</b>
<b>Specifications</b> .....	<b>6</b>
Absolute Maximum Ratings <sup>(1)</sup> .....	6
ESD, Electrostatic Discharge Protection.....	6
Thermal Information.....	6
Recommended Operating Conditions <sup>(1)</sup> .....	7
Electrical Characteristics.....	8
Electrical Characteristics (Continued).....	10
Electrical Characteristics (Continued).....	12
Electrical Characteristics (Continued).....	14
Typical Performance Characteristics.....	16
Test Circuit and Waveforms.....	17
<b>Application and Implementation</b> .....	<b>18</b>
Application Information .....	18
<b>Tape and Reel Information</b> .....	<b>19</b>
<b>Package Outline Dimensions</b> .....	<b>20</b>
SOP16.....	20
TSSOP16.....	21
QFN3X3-16.....	22
WSOP16.....	23
<b>Order Information</b> .....	<b>24</b>
<b>IMPORTANT NOTICE AND DISCLAIMER</b> .....	<b>25</b>

## Switch Selection Guide


Product	Switch Configuration	Supply Voltage (V)	R <sub>ON</sub> (Ω)	Bandwidth (MHz)	Package
TPW4051	8:1	12	50	200	SOP16, TSSOP16, QFN3X3-16
TPW4052	(4:1) × 2	12	50	200	SOP16, TSSOP16
TPW4053	(2:1) × 3	12	50	200	SOP16, TSSOP16
TPW3111	1:1	5.5	1	100	SOT353 (SC70-5)
TPW3115	1:1	5.5	5	250	SOT353 (SC70-5), SOT23-5
TPW4157	2:1	5.5	1	100	SOT363 (SC70-6)
TPW3157A	2:1	5.5	2	100	SOT363 (SC70-6)
TPW3221	(2:1) × 2	5.5	1	100	MSOP10
TPW3223	(2:1) × 2	5.5	1	100	QFN1.4X1.8-10

## Revision History


Date	Revision	Notes
2018-08-08	Rev.Pre.0	Pre-released version.
2019-03-04	Rev.A.0	Initial version.
2019-10-02	Rev.A.1	Changed the value of HBM: from 2 kV to 1 kV.
2019-12-25	Rev.A.2	Corrected the test conditions of ΔR <sub>ON</sub> (On Resistance Match between Channels) and switch leakage to follow the product test (Product test is not changed): <ul style="list-style-type: none"> <li>Corrected all "0 V" to "V<sub>EE</sub>";</li> <li>Removed the ΔR<sub>ON</sub> at 3 to 3.6 V V<sub>CC</sub>;</li> <li>Changed the ΔR<sub>ON</sub> at 9 to 11 V V<sub>CC</sub>: from V<sub>IS</sub> = 3.5 V to V<sub>IS</sub> = 1 V;</li> <li>Changed the ΔR<sub>ON</sub> at 4.5 to 5.5 V V<sub>CC</sub>, V<sub>EE</sub> = -4.5 V to 5.5 V: from V<sub>IS</sub> = 3.5 V to V<sub>IS</sub> = -3.5 V.</li> </ul>
2020-01-14	Rev.A.3	Corrected the "P0" information of TR in Tape and Reel Information.
2020-11-26	Rev.A.4	Corrected the Quantity of TPW4051-QF4R in Order Information: from 3000 to 4000.
2022-04-21	Rev.A.5	Added the Thermal Information. Updated the high POD of the QFN3x3-16 package.
2024-12-04	Rev.A.6	Added a new part number: TPW4051-SOBR. The following updates are all about the new datasheet formats or typos, and the actual product remains unchanged. Updated to a new datasheet format. Updated the Tape and Reel Information. Updated the Package Outline Dimensions.
2025-11-27	Rev.A.7	Added the thermal pad description in the Pin Configuration and Functions. The actual product remains unchanged.

## Pin Configuration and Functions

TPW4051  
SOP16/TSSOP16/WSOP16  
Top View



TPW4051  
QFN3X3-16  
Top View



**Table 1. Pin Functions: TPW4051**

Pin No.			Name	I/O	Description
SOP16	TSSOP16	QFN3X3-16			
1	1	15	A4	I/O	Channel 4 input or output
2	2	16	A6	I/O	Channel 6 input or output
3	3	1	A	I/O	Common input or output
4	4	2	A7	I/O	Channel 7 input or output
5	5	3	A5	I/O	Channel 5 input or output
6	6	4	$\bar{E}$	I	Enable switch, active low
7	7	5	V <sub>EE</sub>		Negative power input
8	8	6	GND		Ground
9	9	7	S2	I	Control input
10	10	8	S1	I	Control input
11	11	9	S0	I	Control input
12	12	10	A3	I/O	Channel 3 input or output
13	13	11	A0	I/O	Channel 0 input or output
14	14	12	A1	I/O	Channel 1 input or output
15	15	13	A2	I/O	Channel 2 input or output
16	16	14	V <sub>CC</sub>		Positive power input
-	-	-	Thermal Pad		Thermal pad. The thermal pad is recommended to be left float or connected to V <sub>EE</sub> .

---

**12-V General Purpose Analog Switch**

Table 2. Functional Table

$\bar{E}$ , Enable	S2	S1	S0	ON Channel
L	L	L	L	A0
L	L	L	H	A1
L	L	H	L	A2
L	L	H	H	A3
L	H	L	L	A4
L	H	L	H	A5
L	H	H	L	A6
L	H	H	H	A7
H	X	X	X	None

(1) X = Don't care.

## Specifications

### Absolute Maximum Ratings <sup>(1)</sup>

Parameter		Min	Max	Unit
	Supply Voltage, $V_{CC} - V_{EE}$	-0.5	13	V
	Supply Voltage, $V_{CC} - GND$	-0.5	13	V
	Supply Voltage, $V_{EE} - GND$	-6.5	0.5	V
	Analog Switch Voltage	$V_{EE} - 0.5$	$V_{CC} + 0.5$	V
	Analog Switch Current	-25	25	mA
	Analog Switch Diode Current	-20	20	mA
	Digital Input Voltage, $\bar{E}$ , S2, S1, S0	GND	$V_{CC} + 0.5$	V
	Digital Input Diode Current	-20	20	mA
$T_J$	Maximum Junction Temperature		150	°C
$T_{STG}$	Storage Temperature Range	-65	150	°C
$T_L$	Lead Temperature (Soldering, 10 sec)		260	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

### ESD, Electrostatic Discharge Protection

Symbol	Parameter	Condition	Minimum Level	Unit
HBM	Human Body Model ESD	ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>	1	kV
CDM	Charged Device Model ESD	ANSI/ESDA/JEDEC JS-002 <sup>(2)</sup>	1	kV

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### Thermal Information

Package Type	$\theta_{JA}$	$\theta_{JC}$	Unit
SOP16	100	50	°C/W
TSSOP16	150	60	°C/W
QFN3X3-16	65	41	°C/W

**Recommended Operating Conditions (1)**

All test conditions: over operating temperature range, unless otherwise noted.

Parameter		Min	Max	Unit
	Supply Voltage, $V_{CC} - V_{EE}$	3	12	V
	Supply Voltage, $V_{CC} - GND$ (2)	3	12	V
	Supply Voltage, $V_{EE} - GND$ (2)	-6	0	V
	Select Input Voltage	0	$V_{CC}$	V
	Input Transition Rise-and-Fall Rate		100	ns/V
	Switch I/O Port Voltage	$V_{EE}$	$V_{CC}$	V
$T_A$	Operating Temperature Range	-40	125	°C

(1) The select input must be held high or low, and it must not float.

(2) The voltage of  $V_{CC}$ ,  $V_{EE}$  needs to be within the range of  $V_{CC} - V_{EE}$ .

**12-V General Purpose Analog Switch**
**Electrical Characteristics**

 All test conditions: single supply,  $V_{CC} = 4.5\text{ V to }5.5\text{ V}$ ,  $V_{EE} = 0\text{ V}$ ,  $GND = 0\text{ V}$ , unless otherwise noted.

Symbol	Parameter	Conditions	$V_{CC}$ (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
<b>Power Supply</b>								
$I_{CC}$	Quiescent Supply Current	$V_{IN} = V_{EE}$ or $V_{CC}$	5.5	4	6	8	Max	$\mu\text{A}$
<b>Digital Input</b>								
$V_{IH}$	Input Voltage High				2.0	2.0	Min	V
$V_{IL}$	Input Voltage Low				0.8	0.8	Max	V
$I_{IN}$	Control Input Leakage	$V_{IN} = 0\text{ V}$ or $V_{CC}$	5.5	$\pm 0.4$	$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
<b>Analog Switch</b>								
$R_{ON}$	(1)	$I_{OUT} = 1\text{ mA}$ , $V_{IS} = V_{EE}$ or $V_{CC}$	4.5	60			Typ	$\Omega$
$R_{ON}$		$I_{OUT} = 1\text{ mA}$ , $V_{IS} = V_{EE}$ or $V_{CC}$	4.5	100	130	150	Max	$\Omega$
$\Delta R_{ON}$	On Resistance Match between Channels	$I_{OUT} = 1\text{ mA}$ , $V_{IS} = 2.5\text{ V}$	4.5	20	30	35	Max	$\Omega$
$R_{FLAT(ON)}$	On Resistance Flatness	$I_{OUT} = 1\text{ mA}$	4.5	60	80	80	Max	$\Omega$
$I_{CH(OFF)}$	Switch OFF Leakage Current on Channel	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	5.5	$\pm 0.4$	$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
$I_{COM(OFF)}$	Switch OFF Leakage Current on Common	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	5.5	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
$I_{(ON)}$	Switch ON Leakage Current	$V_{IS} = V_{EE}$ or $V_{CC}$	5.5	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
<b>Dynamic Characteristics</b>								
$t_{PHL}$ , $t_{PLH}$	Switch IN to OUT Time (1)	$C_L = 50\text{ pF}$	4.5	5			Typ	ns
$t_{ON}$	Switch Turn-on Time	$C_L = 50\text{ pF}$	4.5	60			Max	ns
$t_{OFF}$	Switch Turn-off Time	$C_L = 50\text{ pF}$	4.5	50			Max	ns
	Off Isolation (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ , $C_L = 10\text{ pF}$	5	-70			Typ	dB
	Crosstalk in Channel (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ , $C_L = 10\text{ pF}$	5	-70			Typ	dB
	Crosstalk in Control (1)	Between control and any switch; $R_L = 600\ \Omega$ ; $f = 1\text{ MHz}$ ; E or Sn square wave between $V_{CC}$ and GND	5	110			Typ	mV
BW	Bandwidth (1)	$R_L = 50\ \Omega$	5	200			Typ	MHz

**12-V General Purpose Analog Switch**

Symbol	Parameter	Conditions	V <sub>CC</sub> (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
THD	Total Harmonic Distortion <sup>(1)</sup>	R <sub>L</sub> = 10 kΩ, f = 1 kHz	5	0.05			Typ	%
<b>Capacitance</b>								
C <sub>IN</sub>	Switch Input Capacitance <sup>(1)</sup>		5	5			Typ	pF
C <sub>COM</sub>	Common Output Capacitance <sup>(1)</sup>		5	25			Typ	pF
C <sub>PD</sub>	Power Dissipation Capacitance <sup>(1)</sup>		5	50			Typ	pF

(1) The test data is based on bench tests and design simulation.

**12-V General Purpose Analog Switch**
**Electrical Characteristics (Continued)**

 All test conditions: single supply,  $V_{CC} = 3\text{ V to }3.6\text{ V}$ ,  $V_{EE} = 0\text{ V}$ ,  $GND = 0\text{ V}$ , unless otherwise noted.

Symbol	Parameter	Conditions	$V_{CC}$ (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
<b>Power Supply</b>								
$I_{CC}$	Quiescent Supply Current	$V_{IN} = V_{EE}$ or $V_{CC}$	3.6	4	6	8	Max	$\mu\text{A}$
<b>Digital Input</b>								
$V_{IH}$	Input Voltage High				2.0	2.0	Min	V
$V_{IL}$	Input Voltage Low				0.8	0.8	Max	V
$I_{IN}$	Control Input Leakage	$V_{IN} = 0\text{ V}$ or $V_{CC}$	3.6		$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
<b>Analog Switch</b>								
$R_{ON}$	(1)	$I_{OUT} = 1\text{ mA}$ , $V_{IS} = V_{EE}$ or $V_{CC}$	3	300			Typ	$\Omega$
$R_{FLAT(ON)}$	On Resistance Flatness (1)	$I_{OUT} = 1\text{ mA}$	3	100			Typ	$\Omega$
$I_{CH(OFF)}$	Switch OFF Leakage Current on Channel	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	3.6	$\pm 0.4$	$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
$I_{COM(OFF)}$	Switch OFF Leakage Current on Common	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	3.6	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
$I_{(ON)}$	Switch ON Leakage Current	$V_{IS} = V_{EE}$ or $V_{CC}$	3.6	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
<b>Dynamic Characteristics</b>								
$t_{PHL}$ , $t_{PLH}$	Switch IN to OUT Time (1)	$C_L = 50\text{ pF}$	3	5			Typ	ns
$t_{ON}$	Switch Turn-on Time (1)	$C_L = 50\text{ pF}$	3	70			Typ	ns
$t_{OFF}$	Switch Turn-off Time (1)	$C_L = 50\text{ pF}$	3	60			Typ	ns
	Off Isolation (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ , $C_L = 10\text{ pF}$	3.3	-70			Typ	dB
	Crosstalk (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ , $C_L = 10\text{ pF}$	3.3	-70			Typ	dB
	Crosstalk in Control (1)	Between control and any switch; $R_L = 600\ \Omega$ ; $f = 1\text{ MHz}$ ; E or Sn square wave between $V_{CC}$ and GND	3.3	110			Typ	mV
BW	Bandwidth (1)	$R_L = 50\ \Omega$	3.3	100			Typ	MHz
THD	Total Harmonic Distortion (1)	$R_L = 10\text{ k}\Omega$ , $f = 1\text{ kHz}$	3.3	0.2			Typ	%
<b>Capacitance</b>								
$C_{IN}$	Switch Input Capacitance (1)		3.3	5			Typ	pF
$C_{COM}$	Common Output Capacitance (1)		3.3	25			Typ	pF

**12-V General Purpose Analog Switch**

Symbol	Parameter	Conditions	V <sub>CC</sub> (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
C <sub>PD</sub>	Power Dissipation Capacitance (1)		3.3	50			Typ	pF

(1) The test data is based on bench tests and design simulation.

**12-V General Purpose Analog Switch**
**Electrical Characteristics (Continued)**

 All test conditions: single supply,  $V_{CC} = 9\text{ V to }11\text{ V}$ ,  $V_{EE} = 0\text{ V}$ ,  $GND = 0\text{ V}$ , unless otherwise noted.

Symbol	Parameter	Conditions	$V_{CC}$ (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
<b>Power Supply</b>								
$I_{CC}$	Quiescent Supply Current	$V_{IN} = V_{EE}$ or $V_{CC}$	9	8	12	16	Max	$\mu\text{A}$
<b>Digital Input</b>								
$V_{IH}$	Input Voltage High				2.4	2.4	Min	V
$V_{IL}$	Input Voltage Low				0.8	0.8	Max	V
$I_{IN}$	Control Input Leakage	$V_{IN} = 0\text{ V}$ or $V_{CC}$	11	$\pm 0.4$	$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
<b>Analog Switch</b>								
$R_{ON}$	(1)	$I_{OUT} = 1\text{ mA}$ , $V_{IS} = V_{EE}$ or $V_{CC}$	9	50			Typ	$\Omega$
$R_{ON}$		$I_{OUT} = 1\text{ mA}$ , $V_{IS} = V_{EE}$ or $V_{CC}$	9	80	95	105	Max	$\Omega$
$\Delta R_{ON}$	On Resistance Match between Channels	$I_{OUT} = 1\text{ mA}$ , $V_{IS} = 1\text{ V}$	9	15	25	30	Max	$\Omega$
$R_{FLAT(ON)}$	On Resistance Flatness	$I_{OUT} = 1\text{ mA}$	9	30	40	40	Max	$\Omega$
$I_{CH(OFF)}$	Switch OFF Leakage Current on Channel	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	11	$\pm 0.4$	$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
$I_{COM(OFF)}$	Switch OFF Leakage Current on Common	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	11	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
$I_{(ON)}$	Switch ON Leakage Current	$V_{IS} = V_{EE}$ or $V_{CC}$	11	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
<b>Dynamic Characteristics</b>								
$t_{PHL}$ , $t_{PLH}$	Switch IN to OUT Time (1)	$C_L = 50\text{ pF}$	9	5			Typ	ns
$t_{ON}$	Switch Turn-on Time	$C_L = 50\text{ pF}$	9	60			Max	ns
$t_{OFF}$	Switch Turn-off Time	$C_L = 50\text{ pF}$	9	50			Max	ns
	Off Isolation (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ , $C_L = 10\text{ pF}$	10	-70			Typ	dB
	Crosstalk (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ , $C_L = 10\text{ pF}$	10	-70			Typ	dB
	Crosstalk in Control (1)	Between control and any switch; $R_L = 600\ \Omega$ ; $f = 1\text{ MHz}$ ; E or Sn square wave between $V_{CC}$ and GND	10	220			Typ	mV
BW	Bandwidth (1)	$R_L = 50\ \Omega$	10	200			Typ	MHz

**12-V General Purpose Analog Switch**

Symbol	Parameter	Conditions	V <sub>CC</sub> (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
THD	Total Harmonic Distortion <sup>(1)</sup>	R <sub>L</sub> = 10 kΩ, f = 1 kHz	10	0.03			Typ	%
<b>Capacitance</b>								
C <sub>IN</sub>	Switch Input Capacitance <sup>(1)</sup>		10	5			Typ	pF
C <sub>COM</sub>	Common Output Capacitance <sup>(1)</sup>		10	25			Typ	pF
C <sub>PD</sub>	Power Dissipation Capacitance <sup>(1)</sup>		10	50			Typ	pF

(1) The test data is based on bench tests and design simulation.

**Electrical Characteristics (Continued)**

 All test conditions: dual supply,  $V_{CC} = 4.5\text{ V to }5.5\text{ V}$ ,  $V_{EE} = -4.5\text{ V to }5.5\text{ V}$ ,  $GND = 0\text{ V}$ , unless otherwise noted.



Symbol	Parameter	Conditions	$V_{CC}/V_{EE}$ (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
<b>Power Supply</b>								
$I_{CC}$	Quiescent Supply Current	$V_{IN} = V_{EE}$ or $V_{CC}$	5.5/ -5.5	8	12	16	Max	$\mu\text{A}$
<b>Digital Input</b>								
$V_{IH}$	Input Voltage High				$70\% \times V_{CC}$	$70\% \times V_{CC}$	Min	V
$V_{IL}$	Input Voltage Low				$30\% \times V_{CC}$	$30\% \times V_{CC}$	Max	V
$I_{IN}$	Control Input Leakage	$V_{IN} = 0\text{ V}$ or $V_{CC}$	5.5/ -5.5	$\pm 0.4$	$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
<b>Analog Switch</b>								
$R_{ON}$	(1)	$I_{OUT} = 1\text{ mA}$ , $V_{IS} = V_{EE}$ or $V_{CC}$	4.5/ -4.5	50			Typ	$\Omega$
$R_{ON}$		$I_{OUT} = 1\text{ mA}$ , $V_{IS} = V_{EE}$ or $V_{CC}$	4.5/ -4.5	80	95	105	Max	$\Omega$
$\Delta R_{ON}$	On Resistance Match between Channels	$I_{OUT} = 1\text{ mA}$ , $V_{IS} = -3.5\text{ V}$	4.5/ -4.5	15	25	30	Max	$\Omega$
$R_{FLAT(ON)}$	On Resistance Flatness	$I_{OUT} = 1\text{ mA}$	4.5/ -4.5	30	40	40	Max	$\Omega$
$I_{CH(OFF)}$	Switch OFF Leakage Current on Channel	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	5.5/ -5.5	$\pm 0.4$	$\pm 1$	$\pm 1$	Max	$\mu\text{A}$
$I_{COM(OFF)}$	Switch OFF Leakage Current on Common	$V_{IS} = V_{EE}$ , $V_{OS} = V_{CC}$ ; or $V_{IS} = V_{CC}$ , $V_{OS} = V_{EE}$	5.5/ -5.5	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
$I_{(ON)}$	Switch ON Leakage Current	$V_{IS} = V_{EE}$ or $V_{CC}$	5.5/ -5.5	$\pm 0.4$	$\pm 4$	$\pm 4$	Max	$\mu\text{A}$
<b>Dynamic Characteristics</b>								
$t_{PHL}$ , $t_{PLH}$	Switch IN to OUT Time (1)	$C_L = 50\text{ pF}$	4.5/ -4.5	5			Typ	ns
$t_{ON}$	Switch Turn-on Time	$C_L = 50\text{ pF}$	4.5/ -4.5	60			Max	ns
$t_{OFF}$	Switch Turn-off Time	$C_L = 50\text{ pF}$	4.5/ -4.5	50			Max	ns
	Off Isolation (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ , $C_L = 10\text{ pF}$	5/-5	-70			Typ	dB
	Crosstalk (1)	$f = 1\text{ MHz}$ , $R_L = 50\ \Omega$ ,	5/-5	-70			Typ	dB

**12-V General Purpose Analog Switch**

Symbol	Parameter	Conditions	V <sub>CC</sub> / V <sub>EE</sub> (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
		C <sub>L</sub> = 10 pF						
	Crosstalk in Control <sup>(1)</sup>	Between control and any switch; R <sub>L</sub> = 600 Ω; f = 1 MHz; E or Sn square wave between V <sub>CC</sub> and GND	5/-5	220			Typ	mV
BW	Bandwidth <sup>(1)</sup>	R <sub>L</sub> = 50 Ω	5/-5	200			Typ	MHz
THD	Total Harmonic Distortion <sup>(1)</sup>	R <sub>L</sub> = 10 kΩ, f = 1 kHz	5/-5	0.03			Typ	%
<b>Capacitance</b>								
C <sub>IN</sub>	Switch Input Capacitance <sup>(1)</sup>		5/-5	5			Typ	pF
C <sub>COM</sub>	Common Output Capacitance <sup>(1)</sup>		5/-5	25			Typ	pF
C <sub>PD</sub>	Power Dissipation Capacitance <sup>(1)</sup>		5/-5	50			Typ	pF


(1) The test data is based on bench tests and design simulation.

Typical Performance Characteristics



12-V General Purpose Analog Switch

Test Circuit and Waveforms



Parameter	Vis	S1 Position
$t_{PHL}, t_{PLH}$	Pulse	Open
$t_{PZH}, t_{PHZ}$	$V_{CC}$	$V_{EE}$
$t_{PZL}, t_{PLZ}$	$V_{EE}$	$V_{CC}$

$t_{ON}: t_{PZH}$  or  $t_{PZL}$

$t_{OFF}: t_{PHZ}$  or  $t_{PLZ}$




Figure 3. AC Test Circuit and Test Waveforms




Figure 4. Off Isolation




Figure 5. Crosstalk

## Application and Implementation



Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

## Application Information

A 0.1- $\mu$ F bypass capacitor on  $V_{CC}$  and GND is recommended to prevent power disturbance. Another 0.1- $\mu$ F bypass capacitor on  $V_{EE}$  and GND is also recommended if  $V_{EE}$  is not connected to GND.

Tape and Reel Information




Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm) <sup>(1)</sup>	B0 (mm) <sup>(1)</sup>	K0 (mm) <sup>(1)</sup>	P0 (mm)	W0 (mm)	Pin1 Quadrant
TPW4051-SR	SOP16	330	21.6	6.6	10.4	2.1	8	16	Q1
TPW4051-TR	TSSOP16	330	17.6	6.8	5.5	1.5	8	12	Q1
TPW4051-QF4R	QFN3X3-16	330	17.6	3.3	3.3	1.1	8	12	Q1
TPW4051-SOBR	WSOP16	330	21.6	10.9	10.8	3.1	12	16	Q1


(1) The value is for reference only. Contact the 3PEAK factory for more information.

Package Outline Dimensions


SOP16



TSSOP16




QFN3X3-16



WSOP16

Package Outline Dimensions

SOB(WSOP-16-A)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	2.350	2.650	0.093	0.104
A1	0.100	0.300	0.004	0.012
A2	2.250	2.350	0.089	0.093
b	0.350	0.450	0.014	0.018
c	0.200	0.290	0.008	0.011
D	10.100	10.500	0.398	0.413
E	10.100	10.600	0.398	0.417
E1	7.300	7.700	0.287	0.303
e	1.270 BSC		0.050 BSC	
L	0.500	0.850	0.020	0.033
θ	0	8°	0	8°

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

## Order Information

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPW4051-SR	-40 to 125°C	SOP16	W4051	3	Tape and Reel, 2500	Green
TPW4051-TR	-40 to 125°C	TSSOP16	W4051	3	Tape and Reel, 3000	Green
TPW4051-QF4R	-40 to 125°C	QFN3X3-16	W4051	3	Tape and Reel, 4000	Green
TPW4051-SOBR	-40 to 125°C	WSOP16	W4051	3	Tape and Reel, 1500	Green

**Green:** 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

## **IMPORTANT NOTICE AND DISCLAIMER**

**Copyright**© 3PEAK 2012-2025. All rights reserved.

**Trademarks.** Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

**Performance Information.** Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

**Disclaimer.** 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.

This page intentionally left blank