



Fxx*1)POG0-1424

e.g. F15POG0-1424

*1) xx No. of contacts 09, 15, 25 or 37

xx	A (mm)	B (mm)	C (mm)
09	30,8	16,9	25
15	39,1	25,2	33,3
25	53	38,9	47,04
37	69,3	55,3	63,5

Permeability is tested for the whole connector. Permeability less than 1,0025.

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	xx	Signal contact	P0 / Brass (nonmagnetic)	1,3µm Au / AWG 20
2	1	Shell	Brass (nonmagnetic)	blank
1	1	Insulator	PBT (-55°C - +125°C)	white

REV.	DATE	CH.-NO.	ORIGINAL: DIN A3-DRAWING AS A FILE	REPLACEMENT FOR:	PAGES
1					1

Measurement without tolerance acc. to ISO 2768-m

SCALE 2:1

TITLE

NONMAGNETIC
D-Sub Miniature Connector

DRAWN sschref 15-07-2003

CHECKED aschiekofer 15-07-2003

FCT group
fctgroup.com

DWG.NO. FxxPOG0-1424

REV. 1

COMMENT:
ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT,
THIS DRAWING IS NOT TO BE REPRODUCED, COPIED, TRANSMITTED OR OTHERWISE
AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

[F15P0G0-1424](#) [173114-0242](#)