



SitemapMasthead

english

Search

HOMEPRODUCTSCATALOGUECOMPANYLATEST NEWSERVICECONTACT0 ARTICLES

You are here: Products » Heatsinks f.cool » Profile heatsinks and fluid coolers » Standard extruded heatsinks » SK 69 ... » **SK 69**

Heatsinks f.cool

Profile heatsinks and fluid coolers

- Standard extruded heatsinks
- Extruded heatsinks for lock-in retaining spring
- Extruded heatsinks for PCB mounting
- Extruded heatsinks for DC/DC converter
- Retaining springs for transistors
- U-Extruded heatsinks
- Die-cast heatsinks
- Fin coolers
- Fluid coolers
- Aluminium flat-, quadrangular-, angled-, U- & T-profiles

Heatsinks and active heatsinks for processors

Board Level heatsinks

Cooling aggregates

Accessories for electronic components

Cases f.case

Connectors f.con

Standard extruded heatsinks

SK 69 ...

SK 69 100 SA

120.5 x 11.7 mm, mounting parts IS 1. IS 2. IS 3

add to request



Features

Technical Drawing

Service

Accessories / related products

width

height

plate thickness

length

thermal resistance R_{θ}

drilling pattern

surface

120.5 mm

11.7 mm

3 mm

100 mm

4.5 - 2.4 KW

TO 3

CB

black anodised

Fischer Elektronik GmbH & Co. KG

Nottebohmstraße 28, D - 58511 Lüdenscheid

☎: +49 (0) 23 51 / 4 35 - 0, info@fischer elektronik.de



SitemapMasthead

http://www.fischer elektronik.de/fisch_electronic_CB/heatsinks/VA/1/Standard%20extruded%20heatsinks/VA/SK69100SA/index.xhtml

1 / 1