


(RoHS 2.0)


REV	ECN	NO.	DESCRIPTION	DATE	DESIGN



- NOTES:
- MATERIAL:
 - HOUSING: LCP ,COLOR IS ORANGE ,HIGH TEMPERATURE PLASTIC;
 - CONTACT: BRASS (H65 T=0.20mm);
 - SHELL: COLD ROLLED IRON (SPCC T=0.30mm);
 - ELECTRICAL:
 - VOLTAGE RATING: 30V DC ;
 - CURRENT RATING: 1.5A ;
 - CONTACT RESISTANCE: 30MILLIOHMS MAX.;
 - WITHSTAND VOLTAGE: 100V AC RMS 50(60)Hz, 1MIN. ;
 - INSULATION RESISTANCE: 100MEGOHMS MIN @500V DC;
 - MECHANICAL:
 - MATING FORCE: 35N MAX. ;
 - UNMATING FORCE: 5~35N ;
 - OPERATING LIFE: 1500 CYCLES MIN. ;
 - PLATING:
 - TERMINAL:
NI PLATING OVER ALL,
Tin PLATING ON SOLDER AREA,
Au G/Fu" ON CONTACT AREA;
 - SHELL: NI PLATING OVER ALL;
 - ENVIRONMENTAL:
 - STORAGE TEMPERATURE RANGE: -40° C~+85° C;
 - OPERATION TEMPERATURE RANGE: -25° C~+70° C;
 - SALT SPRAY TEST:24H(EXCLUDING RIVETED BENDS)

C	外壳	SPCC	镀镍	
B	端子	黄铜+65	焊料区镀锡 接触区镀金	
A	基座	LCP	橙色	
序号	品 名	材 质	电镀 / 颜色	备 注

深圳市富港科技有限公司

UNLESS OTHERWISE, GENERAL TOLERANCE: X. xxx ±0.10 X. xx ±0.20 X. x ±0.30 ANGULAR: X. xx° ±1° X. x° ±3° X. ° ±5°	NAME: 3.0AF10GB沉板3.5L平口 LCP橙色				P/N:		
					DWG NO: FG-ST-003-3.5CB-Z		
	THIRD ANGLE PROJECTION 	UNIT:	SCALE	SIZE:	SHEET:	REV.	
		MM	1:1	A4	1/1	A1	
DRAWN: Q S X		CHECKED:			APPROVED:		