

PPv4 Power 250V/16A 3G1.5qmm PUR 1.0m



Image is for illustration purposes only. Please refer to product description.

Part number	33 59 222 0100 001
Specification	PPv4 Power 250V/16A 3G1.5qmm PUR 1.0m
HARTING eCatalogue	https://b2b.harting.com/33592220100001

Identification

Category	System cabling
Series	HARTING PushPull (V4)
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING PushPull (V4) Power 3-pin
Connector 2	HARTING PushPull (V4) Power 3-pin
Type of cable	Copper cable (round)
Description of the cable	Wiring 1:1

Version

Cable length	1 m
Termination method	Crimp termination
Locking type	PushPull
Shielding	Unshielded
Number of cores	3
Core structure	3G 1.5 mm ²
Number of contacts	2
PE contact	Yes

Technical characteristics

Conductor cross-section	1.5 mm ²
Rated current	16 A



Pushing Performance

Technical characteristics

Rated voltage	250 V
Limiting temperature	-40 ... +80 °C
Degree of protection acc. to IEC 60529	IP65 IP67
Vibration resistance	10-500 Hz, 5 g, 0.35 mm, 2h/axis 5.72 m/s ² acc. to IEC 61373 Category 1 Class B
Shock resistance	25 g / 11 ms, 3 shocks / axis and direction 5 g / 30 ms, 5 shocks / axis and direction acc. to IEC 61373 Category 1 Class B

Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Grey

Specifications and approvals

Specifications	IEC 61076-3-106 Variant 4 (V4)
----------------	--------------------------------

Commercial data

Packaging size	1
Country of origin	Latvia
European customs tariff number	85444290
eCl@ss	27060390 Ready-made data cable (unspecified)