



钜地半导体  
Tudi Semiconductor

## Product Specification

CAT24C04YI-GT3A-TUDI

I<sup>2</sup>C-Compatible(2-wire)Serial EEPROM  
1-Kbit(512\*8)or 2-Kbit(1024\*8)

网址 [www.sztdbdt.com](http://www.sztdbdt.com) 🔍

**用芯智造 · 卓越品质**

**semiconductor device  
manufacturer**

- Design
- research and development
- production
- and sales



## Standard Features


- Low-voltage and standard-voltage operation
  - $V_{CC} = 1.7V$  to  $5.5V$
- Internally organized as 512 x 8 (4K), or 1024 x 8 (8K)
- I<sup>2</sup>C-compatible (2-wire) serial interface
- Schmitt Trigger, filtered inputs for noise suppression
- Bidirectional data transfer protocol
- 1MHz (2.5V, 2.7V, 5V), 400kHz (1.7V) compatibility
- Write Protect pin for hardware data protection
- 16-byte Page Write mode
  - Partial Page Writes allowed
- High-reliability
  - Endurance: 1,000,000 write cycles
  - Data retention: 100 years
- Green package options (Pb/Halide-free/RoHS compliant)
  - 8-lead PDIP, 8-lead SOIC, 8-lead TSSOP, 8-pad UDFN, 5-lead SOT23, and 8-ball VFBGA
- Die options: wafer form and tape and reel

## Description

The AT24C04 and AT24C08 provides 4096/8192 bits of Serial Electrically Erasable and Programmable Read-Only Memory (EEPROM) organized as 512/1024 words of eight bits each. The device is optimized for use in many industrial and commercial applications where low-power and low-voltage operation are essential. 24C04C/08C is available in space-saving 8-lead PDIP, 8-lead JEDEC SOIC, 8-lead TSSOP, 8-pad UDFN, 5-lead SOT23, and 8-ball VFBGA packages and is accessed via a 2-wire serial interface.



## Pin Configuration




## Pin Descriptions

| Pin Name | Type | Functions          |
|----------|------|--------------------|
| A0-A2    | I    | Address Inputs     |
| SDA      | I/O  | Serial Data        |
| SCL      | I    | Serial Clock Input |
| WP       | I    | Write Protect      |
| GND      | P    | Ground             |
| Vcc      | P    | Power Supply       |

### Table 1

## Block Diagram



### Figure 1

DEVICE/PAGE ADDRESSES (A2, A1 and A0): The A2, A1 and A0 pins are device address inputs that are hard wire for the 24C02/04/08/16 Eight 2K/4K/8K/16K devices may be addressed on a single bus system (device addressing is discussed in detail under the Device Addressing section).

**SERIAL DATA (SDA):** The SDA pin is bi-directional for serial data transfer. This pin is open-drain driven and may be wire-ORed with any number of other open-drain or open-collector devices.

**SERIAL CLOCK (SCL):** The SCL input is used to positive edge clock data into each EEPROM device and negative edge clock data out of each device.



**WRITE PROTECT (WP):** The 24C02/04/08/16 has a Write Protect pin that provides hardware data protection. The Write Protect pin allows normal read/write operations when connected to ground (GND). When the Write Protection pin is connected to Vcc, the write protection feature is enabled and operates as shown in the following **Table 2**.

| WP Pin Status | AT24C04/24C08                |
|---------------|------------------------------|
| At VCC        | Full Array                   |
| At GND        | Normal Read/Write Operations |

Table 2

## Functional Description

### 1. Memory Organization

**24C02, 2K SERIAL EEPROM:** Internally organized with 16 pages of 16 bytes each, the 2K requires an 8-bit data word address for random word addressing.

**24C04, 4K SERIAL EEPROM:** Internally organized with 32 pages of 16 bytes each, the 4K requires a 9-bit data word address for random word addressing.

**24C08, 8K SERIAL EEPROM:** Internally organized with 64 pages of 16 bytes each, the 8K requires a 10-bit data word address for random word addressing.

**24C16, 16K SERIAL EEPROM:** Internally organized with 128 pages of 16 bytes each, the 16K requires an 11-bit data word address for random word addressing.

### 2. Device Operation

**CLOCK and DATA TRANSITIONS:** The SDA pin is normally pulled high with an external device. Data on the SDA pin may change only during SCL low time periods (see **Figure 2**). Data changes during SCL high periods will indicate a start or stop condition as defined below.

**START CONDITION:** A high-to-low transition of SDA with SCL high is a start condition which must precede any other command (see **Figure 3**).

**STOP CONDITION:** A low-to-high transition of SDA with SCL high is a stop condition. After a read sequence, the stop command will place the EEPROM in a standby power mode (see **Figure 3**).

**ACKNOWLEDGE:** All addresses and data words are serially transmitted to and from the EEPROM in 8-bit words. The EEPROM sends a "0" to acknowledge that it has received each word. This happens during the ninth clock cycle.

**STANDBY MODE:** The 24C02/04/08/16 features a low-power standby mode which is enabled: (a) upon power-up and (b) after the receipt of the STOP bit and the completion of any internal operations.

**MEMORY RESET:** After an interruption in protocol, power loss or system reset, any two-wire part can be reset by following these steps:



1. Clock up to 9 cycles.
2. Look for SDA high in each cycle while SCL is high.
3. Create a start condition.

Figure 2. Data Validity




Figure 3. Start and Stop Definition





Figure 4. Output Acknowledge





### 3. Device Addressing

The 2K/4K/8K/16K EEPROM devices all require an 8-bit device address word following a start condition to enable the chip for a read or write operation (see **Figure 5**)

The device address word consists of a mandatory "1", "0" sequence for the first four most significant bits as shown. This is common to all the Serial EEPROM devices.

The next 3 bits are the A2, A1 and A0 device address bits for the 2K EEPROM. These 3 bits must compare to their corresponding hardwired input pins.

The 4K EEPROM only uses the A2 and A1 device address bits with the third bit being a memory page address bit. The two device address bits must compare to their corresponding hardwired input pins. The A0 pin is no connect.

The 8K EEPROM only uses the A2 device address bit with the next 2 bits being for memory page addressing. The A2 bit must compare to its corresponding hard-wired input pin. The A1 and A0 pins are no connect.

The 16K does not use any device address bits but instead the 3 bits are used for memory page addressing. These page addressing bits on the 4K, 8K and 16K devices should be considered the most significant bits of the data word address which follows. The A0, A1 and A2 pins are no connect

The eighth bit of the device address is the read/write operation select bit. A read operation is initiated if this bit is high and a write operation is initiated if this bit is low.

Upon a compare of the device address, the EEPROM will output a "0". If a compare is not made, the chip will return to a standby state.

### 4. Write Operations

**BYTE WRITE:** A write operation requires an 8-bit data word address following the device address word and acknowledgment. Upon receipt of this address, the EEPROM will again respond with a "0" and then clock in the first 8-bit data word. Following receipt of the 8-bit data word, the EEPROM will output a "0" and the addressing device, such as a microcontroller, must terminate the write sequence with a stop condition. At this time the EEPROM enters an internally timed write cycle,  $t_{WR}$ , to the nonvolatile memory. All inputs are disabled during this write cycle and the EEPROM will not respond until the write is complete (see **Figure 6**).

**PAGE WRITE:** The 2K EEPROM is capable of an 8-byte page write, and the 4K, 8K and 16K devices are capable of 16-byte page writes.

A page write is initiated the same as a byte write, but the microcontroller does not send a stop condition after the first data word is clocked in. Instead, after the EEPROM acknowledges receipt of the first data word, the microcontroller can transmit up to seven (2K) or fifteen (4K, 8K, 16K) more data



words. The EEPROM will respond with a "0" after each data word received. The microcontroller must terminate the page write sequence with a stop condition (see **Figure 7**).

The data word address lower three (2K) or four (4K, 8K, 16K) bits are internally incremented following the receipt of each data word. The higher data word address bits are not incremented, retaining the memory page row location. When the word address, internally generated, reaches the page boundary, the following byte is placed at the beginning of the same page. If more than eight (2K) or sixteen (4K, 8K, 16K) data words are transmitted to the EEPROM, the data word address will "roll over" and previous data will be overwritten.

**ACKNOWLEDGE POLLING:** Once the internally timed write cycle has started and the EEPROM inputs are disabled, acknowledge polling can be initiated. This involves sending a start condition followed by the device address word. The read/write bit is representative of the operation desired. Only if the internal write cycle has completed will the EEPROM respond with a "0", allowing the read or write sequence to continue.

## 5. Read Operations

Read operations are initiated the same way as write operations with the exception that the read/write select bit in the device address word is set to "1". There are three read operations: current address read, random address read and sequential read.

### CURRENT ADDRESS READ:

The internal data word address counter maintains the last address accessed during the last read or write operation, incremented by one. This address stays valid between operations as long as the chip power is maintained. The address "roll over" during read is from the last byte of the last memory page to the first byte of the first page. The address "roll over" during write is from the last byte of the current page to the first byte of the same page. Once the device address with the read/write select bit set to "1" is clocked in and acknowledged by the EEPROM, the current address data word is serially clocked out. The microcontroller does not respond with an input "0" but does generate a following stop condition (see **Figure 8**).

### RANDOM READ:

A random read requires a "dummy" byte write sequence to load in the data word address. Once the device address word and data word address are clocked in and acknowledged by the EEPROM, the microcontroller must generate another start condition. The microcontroller now initiates a current address read by sending a device address with the read/write select bit high. The EEPROM acknowledges the device address and serially clocks out the data word. The microcontroller does not respond with a "0" but does generate a following stop condition (see **Figure 9**).

**SEQUENTIAL READ:** Sequential reads are initiated by either a current address read or a random address read. After the microcontroller receives a data word, it responds with an acknowledge. As long as the EEPROM receives an acknowledge, it will continue to increment the data word address and serially clock out sequential data words. When the memory address limit is reached, the data word address will "roll over" and the sequential read will continue. The sequential read operation is terminated when the




microcontroller does not respond with a "0" but does generate a following stop condition (see **Figure 10**).

**Figure 5. Device Address**

|     | MSB |   |   |   |    |    | LSB |     |
|-----|-----|---|---|---|----|----|-----|-----|
| 2K  | 1   | 0 | 1 | 0 | 0  | 0  | 0   | R/W |
| 4K  | 1   | 0 | 1 | 0 | 0  | 0  | P0  | R/W |
| 8K  | 1   | 0 | 1 | 0 | 0  | P1 | P0  | R/W |
| 16K | 1   | 0 | 1 | 0 | P2 | P1 | P0  | R/W |

**Figure 6. Byte Write**



**Figure 7. Page Write**






Figure 8. Current Address Read




Figure 9. Random Read





Figure 10. Sequential Read





## Electrical Characteristics

Absolute Maximum Stress Ratings :

- DC Supply Voltage . . . . . -0.3V to +6.5V
- Input / Output Voltage . . . . . GND-0.3V to VCC+0.3V
- Operating Ambient Temperature . . . . -40°C to +85°C
- Storage Temperature . . . . . -65°C to +150°C
- Electrostatic pulse (Human Body model) . . . . . 8000V

Comments :

Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to this device. These are stress ratings only. Functional operation of this device at these or any other conditions above those indicated in the operational sections of this specification is not implied or intended. Exposure to the absolute maximum rating conditions for extended periods may affect device reliability.

## DC Electrical Characteristics

Applicable over recommended operating range from: TA = -40°C to +85°C, VCC = +1.7V to +5.5V (unless otherwise noted)

| Parameter                 | Symbol           | Min                  | Typ  | Max                  | Unit | Condition                                            |
|---------------------------|------------------|----------------------|------|----------------------|------|------------------------------------------------------|
| Supply Voltage            | V <sub>CC1</sub> | 1.7                  | -    | 5.5                  | V    | -                                                    |
| Supply Voltage            | V <sub>CC2</sub> | 2.5                  | -    | 5.5                  | V    | -                                                    |
| Supply Current VCC=5.0V   | I <sub>CC1</sub> | -                    | 0.14 | 0.3                  | mA   | READ at 400KHZ                                       |
| Supply Current VCC=5.0V   | I <sub>CC2</sub> | -                    | 0.28 | 0.5                  | mA   | WRITE at 400KHZ                                      |
| Supply Current VCC=5.0V   | I <sub>SB1</sub> | -                    | 0.03 | 0.5                  | μA   | V <sub>IN</sub> =V <sub>CC</sub> or V <sub>SS</sub>  |
| Input Leakage Current     | I <sub>L1</sub>  | -                    | 0.10 | 1.0                  | μA   | V <sub>IN</sub> =V <sub>CC</sub> or V <sub>SS</sub>  |
| Output Leakage Current    | I <sub>LO</sub>  | -                    | 0.05 | 1.0                  | μA   | V <sub>OUT</sub> =V <sub>CC</sub> or V <sub>SS</sub> |
| Input Low Level           | V <sub>IL1</sub> | -0.3                 | -    | V <sub>CC</sub> ×0.3 | V    | V <sub>CC</sub> =1.7V to 5.5V                        |
| Input High Level          | V <sub>IH1</sub> | V <sub>CC</sub> ×0.7 | -    | V <sub>CC</sub> +0.3 | V    | V <sub>CC</sub> =1.7V to 5.5V                        |
| Output Low Level VCC=1.7V | V <sub>OL1</sub> | -                    | -    | 0.2                  | V    | I <sub>OL</sub> =0.15mA                              |
| Output Low Level VCC=5.0V | V <sub>OL2</sub> | -                    | -    | 0.4                  | V    | I <sub>OL</sub> =3.0mA                               |

Table 5

## Pin Capacitance

Applicable over recommended operating range from TA = 25°C, f = 1.0 MHz, VCC = +1.7V

| Parameter                       | Symbol           | Min | Typ | Max | Unit | Condition           |
|---------------------------------|------------------|-----|-----|-----|------|---------------------|
| Input/Output Capacitance(SDA)   | C <sub>I/O</sub> | -   | -   | 8   | pF   | V <sub>IO</sub> =0V |
| Input Capacitance(A0,A1,A2,SCL) | C <sub>IN</sub>  | -   | -   | 6   | pF   | V <sub>IN</sub> =0V |

Table 6



## AC Electrical Characteristics

Applicable over recommended operating range from  $T_A = -40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ ,  $V_{CC} = +1.7\text{V}$  to  $+5.5\text{V}$ ,  $C_L = 1$  TTL Gate and  $100\text{ pF}$  (unless otherwise noted)

| Parameter                                                     | Symbol              | $1.7\text{V} \leq V_{CC} < 2.5\text{V}$ |     |      | $2.5\text{V} \leq V_{CC} < 5.5\text{V}$ |     |      | Units         |
|---------------------------------------------------------------|---------------------|-----------------------------------------|-----|------|-----------------------------------------|-----|------|---------------|
|                                                               |                     | Min                                     | Typ | Max  | Min                                     | Typ | Max  |               |
| Clock Frequency, SCL                                          | $f_{\text{SCL}}$    | -                                       | -   | 400  | -                                       | -   | 1000 | KHZ           |
| Clock Pulse Width Low                                         | $t_{\text{LOW}}$    | 0.6                                     | -   | -    | 0.6                                     | -   | -    | $\mu\text{s}$ |
| Clock Pulse Width High                                        | $t_{\text{HIGH}}$   | 0.4                                     | -   | -    | 0.4                                     | -   | -    | $\mu\text{s}$ |
| Noise Suppression Time                                        | $t_{\text{I}}$      | -                                       | -   | 50   | -                                       | -   | 50   | ns            |
| Clock Low to Data Out Valid                                   | $t_{\text{AA}}$     | 0.1                                     | -   | 0.55 | 0.1                                     | -   | 0.55 | $\mu\text{s}$ |
| Time the bus must be free before a new transmission can start | $t_{\text{BUF}}$    | 0.5                                     | -   | -    | 0.5                                     | -   | -    | $\mu\text{s}$ |
| Start Hold Time                                               | $t_{\text{HD:STA}}$ | 0.25                                    | -   | -    | 0.25                                    | -   | -    | $\mu\text{s}$ |
| Start Setup Time                                              | $t_{\text{SU:DAT}}$ | 0.25                                    | -   | -    | 0.25                                    | -   | -    | $\mu\text{s}$ |
| Data In Hold Time                                             | $t_{\text{HD:DAT}}$ | 0                                       | -   | -    | 0                                       | -   | -    | $\mu\text{s}$ |
| Data in Setup Time                                            | $t_{\text{SU:DAT}}$ | 100                                     | -   | -    | 100                                     | -   | -    | ns            |
| Input Rise Time(1)                                            | $t_{\text{R}}$      | -                                       | -   | 0.3  | -                                       | -   | 0.3  | $\mu\text{s}$ |
| Input Fall Time(1)                                            | $t_{\text{F}}$      | -                                       | -   | 0.3  | -                                       | -   | 0.3  | $\mu\text{s}$ |
| Stop Setup Time                                               | $t_{\text{SU:STO}}$ | 0.25                                    | -   | -    | 0.25                                    | -   | -    | $\mu\text{s}$ |
| Data Out Hold Time                                            | $t_{\text{DH}}$     | 50                                      | -   | -    | 50                                      | -   | -    | ns            |
| Write Cycle Time                                              | $t_{\text{WR}}$     | -                                       | 1.9 | 3    | -                                       | 1.9 | 3    | ms            |
| 5.0V, $25^{\circ}\text{C}$ , Byte Mode(1)                     | Endurance           | 1M                                      | -   | -    | -                                       | -   | -    | Write Cycle   |

Table 7


### Notes:

1. This parameter is characterized and is not 100% tested.
2. AC measurement conditions:  
 $R_L$  (connects to  $V_{CC}$ ):  $1.3\text{ k}\Omega$   
 Input pulse voltages:  $0.3 V_{CC}$  to  $0.7 V_{CC}$   
 Input rise and fall time:  $50\text{ ns}$   
 Input and output timing reference voltages:  $0.5 V_{CC}$   
 The value of  $R_L$  should be concerned according to the actual loading on the user's system.




## Bus Timing

Figure 11. SCL: Serial Clock, SDA: Serial Data I/O



## Write Cycle Timing

Figure 12. SCL: Serial Clock, SDA: Serial Data I/O




### Notes:

The write cycle time  $t_{WR}$  is the time from a valid stop condition of a write sequence to the end of the internal clear/write cycle.




## Package Information

### PDIP Outline Dimensions




Top View



End View

COMMON DIMENSIONS  
(Unit of Measure=Inches)



Side View




| SYMBOL | MIN      | NOM   | MAX   | NOTE |
|--------|----------|-------|-------|------|
| A      |          |       | 0.210 | 2    |
| A2     | 0.115    | 0.130 | 0.195 |      |
| b      | 0.014    | 0.018 | 0.022 | 5    |
| b2     | 0.045    | 0.060 | 0.070 | 6    |
| b3     | 0.030    | 0.039 | 0.045 | 6    |
| c      | 0.008    | 0.010 | 0.014 |      |
| D      | 0.355    | 0.365 | 0.400 | 3    |
| D1     | 0.005    |       |       | 3    |
| E      | 0.300    | 0.310 | 0.325 | 4    |
| E1     | 0.240    | 0.250 | 0.280 | 3    |
| e      | 0.100BSC |       |       |      |
| eA     | 0.300BSC |       |       | 4    |
| L      | 0.115    | 0.130 | 0.150 | 2    |

#### Notes:

1. This drawing is for general information only; refer to JEDEC Drawing MS-001, Variation BA for additional information.
2. Dimensions A and L are measured with the package seated in JEDEC seating plane Gauge GS-3.
3. D, D1 and E1 dimensions do not include mold Flash or protrusions. Mold Flash or protrusions shall not exceed 0.010 inch.
4. E and eA measured with the leads constrained to be perpendicular to datum.
5. Pointed or rounded lead tips are preferred to ease insertion.
6. b2 and b3 maximum dimensions do not include Dambar protrusions. Dambar protrusions shall not exceed 0.010 (0.25 mm).



SOP



COMMON DIMENSIONS  
(Unit of Measure=mm)


| SYMBOL | MIN     | NOM | MAX  | NOTE |
|--------|---------|-----|------|------|
| A      | 1.35    | —   | 1.75 |      |
| A1     | 0.10    | —   | 0.25 |      |
| b      | 0.31    | —   | 0.51 |      |
| C      | 0.17    | —   | 0.25 |      |
| D      | 4.80    | —   | 5.00 |      |
| E1     | 3.81    | —   | 3.99 |      |
| E      | 5.79    | —   | 6.20 |      |
| e      | 1.27BSC |     |      |      |
| L      | 0.40    | —   | 1.27 |      |
| Φ      | 0"      | —   | 8"   |      |

Notes:

These drawings are for general information only. Refer to JEDEC Drawing MS-012, Variation AA for proper dimensions, tolerances, datums, etc.



TSSOP




Notes:


1. This drawing is for general information only. Refer to JEDEC Drawing MO-153, Variation AA, for proper dimensions, tolerances, datums, etc.
2. Dimension D does not include mold Flash, protrusions or gate burrs. Mold Flash, protrusions and gate burrs shall not exceed 0.15 mm (0.006 in) per side.
3. Dimension E1 does not include inter-lead Flash or protrusions. Inter-lead Flash and protrusions shall not exceed 0.25 mm (0.010 in) per side.
4. Dimension b does not include Dambar protrusion. Allowable Dambar protrusion shall be 0.08 mm total in excess of the b dimension at maximum material condition. Dambar cannot be located on the lower radius of the foot. Minimum space between protrusion and adjacent lead is 0.07 mm.
5. Dimension D and E1 to be determined at Datum Plane H.



UDFN




WLCSP






SOT23-5




TOP VIEW




SIDE VIEW

COMMON DIMENSIONS  
(UNITS OF MEASURE = MILLIMETER)



SIDE VIEW



SECTION B-B

| SYMBOL | MIN      | NOM  | MAX  |
|--------|----------|------|------|
| A      | —        | —    | 1.35 |
| A1     | 0.04     | —    | 0.15 |
| A2     | 1.00     | 1.10 | 1.20 |
| A3     | 0.55     | 0.65 | 0.75 |
| b      | 0.38     | —    | 0.48 |
| b1     | 0.37     | 0.40 | 0.43 |
| c      | 0.11     | —    | 0.21 |
| c1     | 0.10     | 0.13 | 0.16 |
| D      | 2.72     | 2.92 | 3.12 |
| E      | 2.60     | 2.80 | 3.00 |
| E1     | 1.40     | 1.60 | 1.80 |
| e      | 0.95BSC  |      |      |
| e1     | 1.90BSC  |      |      |
| L      | 0.30     | —    | 0.60 |
| L1     | 0.575REF |      |      |
| L2     | 0.258BSC |      |      |
| Θ      | 0°       | —    | 8°   |

Ordering information

| Order Number         | Package | Package Quantity | Marking<br>On The park |
|----------------------|---------|------------------|------------------------|
| CAT24C04YI-GT3A-TUDI | TSSOP8  | Tape,Reel,2500   | 24C04Y                 |



## Important statement:

- TUDI Semiconductor reserves the right to modify the product manual without prior notice! Before placing an order, customers need to confirm whether the obtained information is the latest version and verify the completeness of the relevant information.
- Any semi-guide product is subject to failure or malfunction under specified conditions. It is the buyer's responsibility to comply with safety standards when using TUDI Semiconductor products for system design and whole machine manufacturing. And take the appropriate safety measures to avoid the potential in the risk of loss of personal injury or loss of property situation!
- TUDI Semiconductor products have not been licensed for life support, military, and aerospace applications, and therefore TUDI Semiconductor is not responsible for any consequences arising from the use of this product in these areas.
- If any or all TUDI Semiconductor products (including technical data, services) described or contained in this document are subject to any applicable local export control laws and regulations, they may not be exported without an export license from the relevant authorities in accordance with such laws.
- The specifications of any and all TUDI Semiconductor products described or contained in this document specify the performance, characteristics, and functionality of said products in their standalone state, but do not guarantee the performance, characteristics, and functionality of said products installed in Customer's products or equipment. In order to verify symptoms and conditions that cannot be evaluated in a standalone device, the Customer should ultimately evaluate and test the device installed in the Customer's product device.
- TUDI Semiconductor documentation is only allowed to be copied without any alteration of the content and with the relevant authorization. TUDI Semiconductor assumes no responsibility or liability for altered documents.
- TUDI Semiconductor is committed to becoming the preferred semiconductor brand for customers, and TUDI Semiconductor will strive to provide customers with better performance and better quality products.