

- Quick Links**
- Cross reference
- RoHS/LF P/N Search
- Industry Standards
- Alphabetical List
- Documentation**
- 3D model search
- Customer drawing search
- Multi Selection Search
- Search by category

Start > Search=TJ04315300J0G* > TJ04315300J0G

TJ04315300J0G
TJ04315300J0G -
Terminal Blocks :
Pluggable plug, 3.81mm
pitch, horizontal wire-inlet,
4 position

ACTIVE

Distributor Stock

[Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)



Customer drawing

Environmental Compliance Report

Specifications

Download document

Dimensional	General	Mechanical	Electrical	Physical	Approvals / Certifications
Dimensional					
Strip length (Wire)	6 to 7 mm				
Solid wire size (AWG)	16 to 28				
Solid wire size (mm ²)	1.5				
Stranded wire size (AWG)	16 to 28				
Stranded wire size (mm ²)	1.5				
Pitch	3.81 mm				
Screw Size	M2				
General					
Gender	Female plug				
Packaging	Box				
Product Type	Screw Pluggable System				
Series	TJ				
Number of Positions	4				
Mechanical					
Number of mating cycles	200				
Electrical					
Withstanding Voltage	1.6 kV				
Current rating	10 A				
Voltage rating	300 V				
Physical					
Color (Housing)	Green				
Conductor entry angle	0°				
Material (Housing)	Thermoplastic UL94V-0				
Terminal material	Phosphor bronze				
Terminal plating	Tin				
Screw material	Steel				
Screw plating	Zinc				
Clamp material	Brass				
Clamp plating	Nickel				
Connection Type	Screw connection				
Temperature (Operating - range)	-40 to 115 Celcius				
Torque	3.0 Lb-in				
Approvals / Certifications					
Approvals / Certifications	cULus, VDE				