





1		2		3			4		
30.00 [1.181]				REVISIONS					
				REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
				A0	N/A		INITIAL RELEASE	2024.05.09	




规格 Specification:

- 1.额定值 Rating:3A 125/250VAC
- 2.接触电阻 Contact resistance:≤30 mΩ
- 3.绝缘电阻 Insulation resistance:≥100 MΩ(DC500V/Min)
- 4.电气寿命 Electronics life:>10000 cycles
- 5.操作力 Operation force:400±150gf
- 6.所有材料符合Rohs要求 All materials are Rohs compliant

PART NO.:

SS-X 03 25 P G-4 N 3 W W
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

- ① SS: XKB Vertical handle;
- ② Enclosure Material:
A-Metal case;
BLANK-Plastic case;
- ③ Current Rating: 03-03A;
- ④ Switch Circuit:25-2P5T;
- ⑤ P: Welding plates;
- ⑥ Handle Shape: G-Camber handle;
- ⑦ Handle Height: 3~15mm;
- ⑧ Enclosure Shape:N-Square enclosure;
- ⑨ Terminal specs:
1:TYPE-1; 2:TYPE-2;
3:TYPE-3; 4:TYPE-4; 5:TYPE-5;
- ⑩ Handle Colour:
B-Black; W-White; R-Red
- ⑪ Housing Colour:
B-Black; W-White; R-Red



产品字码标识

ANGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	桑 葚	VIEW:		MODEL TYPE:	SLIDE SWITCH	
CHECKED		UNIT:	mm/in	PART NO.:	SS-0325PG-4N3WW	
APPROVED		SIZE:	A4	DWG NO.:	X-SS-0325PG-4N3WW	
PRECISION CO.,LIMITED				SCALE	PAGE	REVISION
				N/A	1 / 1	A0