





	REVISIONS				
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A1	N/A		图框升级整理图面	2024.07.19	阿 树



- Specifications
- Voltage rating:250V AC/DC
- Current rating:5A AC/DC
- Withstanding voltage:1000V AC/minute
- Temperature range:-45° to+125°
- Insulation resistance:≥1000MΩ Min
- Contact resistance:≤10mΩ Max
- After environmental testing: ≤20mΩ

PART NO.:

X3025 H F-04 G-N2 XX
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No
- ② Category:H-HSG
- ③ Welding Board Angle: F-Female HSG
- ④ Pow No.-Pin No.: XX-02P~12P
- ⑤ Plug the Pin & special No:I-Without Ears
G-With Ears
- ⑥ Material: N2-PA66 94V-2;
- ⑦ Color: Blank-Natural Color; WH-White

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
02	3.00	6.90	08	21.00	24.90
03	6.00	9.90	09	24.00	27.90
04	9.00	12.90	10	27.00	30.90
05	12.00	15.90	11	30.00	33.90
06	15.00	18.90	12	33.00	36.90
07	18.00	21.90			


X3025HF-04G-N2	Nylon 66 94V-2	Natural Color	X3025TM	X3025HM	With Ears
X3025HF-04G-N2WH		White			Without Ears
X3025HF-04I-N2		Natural Color			
X3025HF-04I-N2WH		White			
PART NO	Material	Color	Suitable XKB Terminal	Mates With XKB Wafer	Note

ANGLAR	$\pm 5^\circ$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERANCES	



DESIGN
CHECKED
APPROVED

阿 桖



UNIT: mm/in

SIZE: A4

MODEL TYPE:	3.00mm Crimp Style Connectors
-------------	-------------------------------

PART NO.:	X3025HF-04G-N2
-----------	----------------

DWG NO.:	X-X3025HF-04G-N2
----------	------------------

SCALE	PAGE	REVISION
N/A	1/1	A1