

Search This Product Catalog


By Keyword

- Architecture & Construction
  - Product Catalog for Architecture & Construction
    - 3M™ Access Network Solutions
    - 3M™ Aerosols, Films, Hot Melt, Liquids, & Pastes Solutions
    - 3M™ Bonding Tapes
    - 3M™ Corrosion Protection Products
    - 3M™ Electrical Products**
    - 3M™ Glass Bubbles
    - 3M™ Heat Tracing Solutions
    - 3M™ Industrial Abrasives
    - 3M™ Industrial Tapes
    - 3M™ Novec™ Fire Protection Fluid
    - 3M™ Occupational Health & Environmental Safety Products
    - 3M™ Packaging Solutions
    - 3M™ Protection Products
    - 3M™ Reclosable Fasteners
    - Volition™ Networks

Product Catalog for Architecture & Construction > 3M™ Electrical Products . . . 3M™ Scotchlok™ Female Disconnects > 3M™ Scotchlok™ Female Disconnects Vinyl Insulated Butted Seam >

## 3M™ Scotchlok™ Female Disconnect, Vinyl Insulated Butted Seam MVU18-250DFX, 22-18 AWG

[Printer-friendly format](#)



This terminal has a wire range of 22-18 AWG and has case quantities of 500 per case.

[\[click to enlarge\]](#)

3M Id : 80-6100-6599-9  
GTIN(UPC/EAN) : 0 00 54007 11820 6

### Additional Information

The disconnects are attached to mating part by tongue of female part slipping over male tab. The use of dents and rolled edges on female part provides excellent holding force while allowing easy and quick disconnect.

### Learn More . . .

- [Email](#) [Female Disconnects - Vinyl Insulated Butted Seam - Product Selection Guide \(PDF 20.6 K\)](#)
- [Email](#) [Scotchlok Terminals MVU18-250DF, MVU14-250DF, MVU10-250 - Data Sheet \(PDF 34.7 K\)](#)
- [Email](#) [Terminal Stud Size Chart - Product Selection Guide \(PDF 14.9 K\)](#)

### Please Note:

Adobe® Acrobat® Reader is required to view PDF documents.



### Characteristics

Agency Approvals	UL and CSA
Barrel Inside Diameter	0.8 Inch
Barrel Length	0.25 Inch
Barrel Style	Butted
Conductor Sizes	22 - 18 AWG
CSA File Number	LR22190
Fastener Orientation	Female
Insulation Material	Vinyl
Length (L)	0.87 Inch
Mates with Male Tab Width (W)	0.25 Inch
Maximum Insulation Outer Diameter	0.145 Inch
Pad Width	0.250 Inch
Terminal Style	Standard
Terminal Type	Disconnect
Thickness	0.032 Inch
UL File Number	E70512