

1

2

3


4

REVISIONS

REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.06.27	阿树

Specification:

- Rating: DC 30V 0.5A.
- Contact resistance: $\leq 30\text{m}\Omega$
After test: $\leq 50\text{m}\Omega$.
- Insulation resistance: $\geq 100\text{m}\Omega$ (500VDC).
After test: $\geq 50\text{m}\Omega$.
- Withstanding voltage: 500vac.
- Insertion and extraction force: 3N~30N.
- Life test: 5000cycles min.
- Operation temperature range: $-20^{\circ}\text{C}+70^{\circ}\text{C}$.
- Preservative temperature range: $-40^{\circ}\text{C}+85^{\circ}\text{C}$.
- Sign" "is importance dimension.

Model No.	PJ-392W-X
Schematic	

RECOMMENDED P.C.B LAYOUT
UNSPECIFIED TOLERANCE: ± 0.05
(BOTTOM VIEW)

CODE	PLATING
—=B	Bushing&Nut (Ni Plated) Terminal (Ag Plated)
—=D	Bushing&Nut (Ni Plated) Terminal (Au Plated)
—=F	Bushing&Nut (Au Plated) Terminal (Au Plated)

Plastic	PBT	
Terminal 3	Phosphor Bronze	TIN
Terminal 2	Phosphor Bronze	TIN
Terminal 1	Phosphor Bronze	TIN
PAPT NAMF	MATERIAL	PLATING

AuGLAR	$\pm 5^{\circ}$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERANCE	

XKLB 星城
Connection

DESIGN	阿树	VIEW: 	MODEL TYPE: 3.5 PHONE JACK
CHECKED		UNIT: mm/in	PART NO.: PJ-392W-B
APPROVED		SIZE: A4	DWG NO.: X-PJ-392W-B
		SCALE	PAGE
		N/A	1/1
		REVISION	A1

1

2

3

4