



FEATURES

- Epitaxial Planar Die Construction
- Complementary PNP Type Available(MMDT5401)
- Ideal for Medium Power Amplification and Switching

SOT-363



MRKING:K4N









MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	parameter	Value	Units
V_{CBO}	Collector- Base Voltage	180	V
V_{CEO}	Collector-Emitter Voltage	160	V
V_{EBO}	Emitter-Base Voltage	6	V
I_c	Collector Current -Continuous	0.2	A
p_c	Collector Power Dissipation	0.2	W
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	$^{\circ}\text{C}$




ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown Voltage	$V_{(BR)CBO}$	$I_c=100\mu\text{A}, I_E=0$	180			V
Collector-emitter breakdown Voltage	$V_{(BR)CEO}$	$I_c=1\text{mA}, I_B=0$	160			V
Emitter-base breakdown Voltage	$V_{(BR)EBO}$	$I_E=10\mu\text{A}, I_c=0$	6			V
Collector cut-off current	I_{CBO}	$V_{CB}=120\text{V}, I_E=0$			0.05	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=4\text{V}, I_c=0$			0.05	μA
DC current gain	$h_{FE(1)}$	$V_{CE}=5\text{V}, I_c=1\text{mA}$	80			
	$h_{FE(2)}$	$V_{CE}=5\text{V}, I_c=10\text{mA}$	100		300	
	$h_{FE(3)}$	$V_{CE}=5\text{V}, I_c=50\text{mA}$	30			
Collector-emitter saturation Voltage	$V_{CE(sat)1}$	$I_c=10\text{mA}, I_B=1\text{mA}$			0.15	V
	$V_{CE(sat)2}$	$I_c=50\text{mA}, I_B=5\text{mA}$			0.2	V
Base-emitter saturation Voltage	$V_{BE(sat)1}$	$I_c=10\text{mA}, I_B=1\text{mA}$			1	V
	$V_{BE(sat)2}$	$I_c=50\text{mA}, I_B=5\text{mA}$			1	V
Transition frequency	f_T	$V_{CE}=10\text{V}, I_c=10\text{mA}, f=100\text{MHz}$	100		300	MHz
Output Capacitance	C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$			6	pF
Noise Figure	NF	$V_{CE}=5\text{V}, I_c=0.2\text{mA}, R_S=1\text{K}\Omega, f=1\text{kHz}$			8	dB

Typical Characteristics




SOT-363 package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.100	0.150	0.004	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.400	0.085	0.094
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
theta	0°	8°	0°	8°

SOT-363 Suggested pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.