



Memory module for the parameterization of SIMOCODE pro S/V without PC/PG,
Color: titanium gray

General technical data	
product designation	memory module
ambient temperature	
<ul style="list-style-type: none"> during storage during operation during transport 	-40 ... +80 °C -25 ... +60 °C -40 ... +80 °C

Certificates/ approvals	
General Product Approval	EMV



[Confirmation](#)



[KC](#)

Test Certificates	Marine / Shipping	other	Environment	Industrial Communication
Type Test Certificates/Test Report	 ABS RMRS	<p>Confirmation</p>	<p>Environmental Confirmations</p>	 Profibus

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7901-0AA01-0 Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7901-0AA01-0 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3UF7901-0AA01-0 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7901-0AA01-0&lang=en





