

# SWF634-VB Datasheet

## Power MOSFET

### PRODUCT SUMMARY

|                           |                        |     |
|---------------------------|------------------------|-----|
| $V_{DS}$ (V)              | 250                    |     |
| $R_{DS(on)}$ ( $\Omega$ ) | $V_{GS} = 10\text{ V}$ | 0.2 |
| $Q_g$ (Max.) (nC)         | 70                     |     |
| $Q_{gs}$ (nC)             | 13                     |     |
| $Q_{gd}$ (nC)             | 39                     |     |
| Configuration             | Single                 |     |



### FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- Surface Mount
- Low-Profile Through-Hole
- Available in Tape and Reel
- Dynamic  $dV/dt$  Rating
- 150 °C Operating Temperature
- Fast Switching
- Fully Avalanche Rated
- Compliant to RoHS Directive 2002/95/EC



**RoHS\***  
COMPLIANT  
HALOGEN  
**FREE**  
Available

TO-220 FULLPAK



N-Channel MOSFET

### ABSOLUTE MAXIMUM RATINGS ( $T_C = 25\text{ }^{\circ}\text{C}$ , unless otherwise noted)

| PARAMETER                                        |                         |                         | SYMBOL                            | LIMIT            | UNIT |
|--------------------------------------------------|-------------------------|-------------------------|-----------------------------------|------------------|------|
| Drain-Source Voltage                             |                         |                         | V <sub>DS</sub>                   | 250              | V    |
| Gate-Source Voltage                              |                         |                         | V <sub>GS</sub>                   | ± 20             |      |
| Continuous Drain Current                         | V <sub>GS</sub> at 10 V | T <sub>C</sub> = 25 °C  | I <sub>D</sub>                    | 16               | A    |
|                                                  |                         | T <sub>C</sub> = 100 °C |                                   | 12               |      |
| Pulsed Drain Current <sup>a, e</sup>             |                         |                         | I <sub>DM</sub>                   | 50               |      |
| Linear Derating Factor                           |                         |                         |                                   | 1.0              | W/°C |
| Single Pulse Avalanche Energy <sup>b, e</sup>    |                         |                         | E <sub>AS</sub>                   | 380              | mJ   |
| Avalanche Current <sup>a</sup>                   |                         |                         | I <sub>AR</sub>                   | 12               | A    |
| Repetitive Avalanche Energy <sup>a</sup>         |                         |                         | E <sub>AR</sub>                   | 13               | mJ   |
| Maximum Power Dissipation                        | T <sub>C</sub> = 25 °C  |                         | P <sub>D</sub>                    | 3.1              | W    |
|                                                  | T <sub>A</sub> = 25 °C  |                         |                                   | 110              |      |
| Peak Diode Recovery dV/dt <sup>c, e</sup>        |                         |                         | dV/dt                             | 5.0              | V/ns |
| Operating Junction and Storage Temperature Range |                         |                         | T <sub>J</sub> , T <sub>stg</sub> | - 55 to + 150    | °C   |
| Soldering Recommendations (Peak Temperature)     |                         | for 10 s                |                                   | 300 <sup>d</sup> |      |

#### Notes

- Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- $V_{DD} = 50\text{ V}$ , starting  $T_J = 25\text{ }^{\circ}\text{C}$ ,  $L = 2.7\text{ mH}$ ,  $R_g = 25\text{ }\Omega$ ,  $I_{AS} = 18\text{ A}$  (see fig. 12).
- $I_{SD} \leq 20\text{ A}$ ,  $dI/dt \leq 150\text{ A}/\mu\text{s}$ ,  $V_{DD} \leq V_{DS}$ ,  $T_J \leq 150\text{ }^{\circ}\text{C}$ .
- 1.6 mm from case.

\* Pb containing terminations are not RoHS compliant, exemptions may apply

**THERMAL RESISTANCE RATINGS**

| PARAMETER                                                               | SYMBOL     | TYP. | MAX. | UNIT |
|-------------------------------------------------------------------------|------------|------|------|------|
| Maximum Junction-to-Ambient<br>(PCB Mounted, Steady-State) <sup>a</sup> | $R_{thJA}$ | -    | 40   | °C/W |
| Maximum Junction-to-Case (Drain)                                        | $R_{thJC}$ | -    | 1.0  |      |

**Note**





a. When mounted on 1" square PCB (FR-4 or G-10 material).

**SPECIFICATIONS** ( $T_J = 25\text{ }^{\circ}\text{C}$ , unless otherwise noted)

| PARAMETER                                 | SYMBOL              | TEST CONDITIONS                                                                                                                                         |                                                                                      | MIN. | TYP.  | MAX.      | UNIT                  |
|-------------------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|------|-------|-----------|-----------------------|
| Static                                    |                     |                                                                                                                                                         |                                                                                      |      |       |           |                       |
| Drain-Source Breakdown Voltage            | $V_{DS}$            | $V_{GS} = 0\text{ V}$ , $I_D = 250\text{ }\mu\text{A}$                                                                                                  |                                                                                      | 250  | -     | -         | V                     |
| $V_{DS}$ Temperature Coefficient          | $\Delta V_{DS}/T_J$ | Reference to $25\text{ }^{\circ}\text{C}$ , $I_D = 1\text{ mA}^c$                                                                                       |                                                                                      | -    | 0.29  | -         | V/ $^{\circ}\text{C}$ |
| Gate-Source Threshold Voltage             | $V_{GS(th)}$        | $V_{DS} = V_{GS}$ , $I_D = 250\text{ }\mu\text{A}$                                                                                                      |                                                                                      | 2.0  | -     | 4.0       | V                     |
| Gate-Source Leakage                       | $I_{GSS}$           | $V_{GS} = \pm 20\text{ V}$                                                                                                                              |                                                                                      | -    | -     | $\pm 100$ | nA                    |
| Zero Gate Voltage Drain Current           | $I_{DSS}$           | $V_{DS} = 200\text{ V}$ , $V_{GS} = 0\text{ V}$                                                                                                         |                                                                                      | -    | -     | 25        | $\mu\text{A}$         |
|                                           |                     | $V_{DS} = 160\text{ V}$ , $V_{GS} = 0\text{ V}$ , $T_J = 125\text{ }^{\circ}\text{C}$                                                                   |                                                                                      | -    | -     | 250       |                       |
| Drain-Source On-State Resistance          | $R_{DS(on)}$        | $V_{GS} = 10\text{ V}$                                                                                                                                  | $I_D = 11\text{ A}^b$                                                                | -    | 0.200 | -         | $\Omega$              |
| Forward Transconductance                  | $g_{fs}$            | $V_{DS} = 50\text{ V}$ , $I_D = 11\text{ A}^d$                                                                                                          |                                                                                      | 6.7  | -     | -         | S                     |
| Dynamic                                   |                     |                                                                                                                                                         |                                                                                      |      |       |           |                       |
| Input Capacitance                         | $C_{iss}$           | $V_{GS} = 0\text{ V}$ ,<br>$V_{DS} = 25\text{ V}$ ,<br>$f = 1.0\text{ MHz}$ , see fig. 5 <sup>d</sup>                                                   |                                                                                      | -    | 1300  | -         | pF                    |
| Output Capacitance                        | $C_{oss}$           |                                                                                                                                                         |                                                                                      | -    | 430   | -         |                       |
| Reverse Transfer Capacitance              | $C_{rss}$           |                                                                                                                                                         |                                                                                      | -    | 130   | -         |                       |
| Total Gate Charge                         | $Q_g$               | $V_{GS} = 10\text{ V}$                                                                                                                                  | $I_D = 20\text{ A}$ , $V_{DS} = 160\text{ V}$ ,<br>see fig. 6 and 13 <sup>b, c</sup> | -    | -     | 70        | nC                    |
| Gate-Source Charge                        | $Q_{gs}$            |                                                                                                                                                         |                                                                                      | -    | -     | 13        |                       |
| Gate-Drain Charge                         | $Q_{gd}$            |                                                                                                                                                         |                                                                                      | -    | -     | 39        |                       |
| Turn-On Delay Time                        | $t_{d(on)}$         | $V_{DD} = 100\text{ V}$ , $I_D = 20\text{ A}$ ,<br>$R_g = 9.1\text{ }\Omega$ , $R_D = 5.4\text{ }\Omega$ , see fig. 10 <sup>b, c</sup>                  |                                                                                      | -    | 14    | -         | ns                    |
| Rise Time                                 | $t_r$               |                                                                                                                                                         |                                                                                      | -    | 51    | -         |                       |
| Turn-Off Delay Time                       | $t_{d(off)}$        |                                                                                                                                                         |                                                                                      | -    | 45    | -         |                       |
| Fall Time                                 | $t_f$               |                                                                                                                                                         |                                                                                      | -    | 36    | -         |                       |
| Drain-Source Body Diode Characteristics   |                     |                                                                                                                                                         |                                                                                      |      |       |           |                       |
| Continuous Source-Drain Diode Current     | $I_S$               | MOSFET symbol showing the integral reverse p - n junction diode<br> |                                                                                      | -    | -     | 1 5       | A                     |
| Pulsed Diode Forward Current <sup>a</sup> | $I_{SM}$            |                                                                                                                                                         |                                                                                      | -    | -     | 4 2       |                       |
| Body Diode Voltage                        | $V_{SD}$            | $T_J = 25\text{ }^{\circ}\text{C}$ , $I_S = 20\text{ A}$ , $V_{GS} = 0\text{ V}^b$                                                                      |                                                                                      | -    | -     | 2.0       | V                     |
| Body Diode Reverse Recovery Time          | $t_{rr}$            | $T_J = 25\text{ }^{\circ}\text{C}$ , $I_F = 20\text{ A}$ , $dI/dt = 100\text{ A}/\mu\text{s}^{b, c}$                                                    |                                                                                      | -    | 300   | 610       | ns                    |
| Body Diode Reverse Recovery Charge        | $Q_{rr}$            |                                                                                                                                                         |                                                                                      | -    | 3.4   | 7.1       | $\mu\text{C}$         |
| Forward Turn-On Time                      | $t_{on}$            | Intrinsic turn-on time is negligible (turn-on is dominated by $L_S$ and $L_D$ )                                                                         |                                                                                      |      |       |           |                       |

**Notes**

- a. Repetitive rating; pulse width limited by maximum junction temperature.  
 b. Pulse width  $\leq 300\text{ }\mu\text{s}$ ; duty cycle  $\leq 2\%$ .

**TYPICAL CHARACTERISTICS** (25 °C, unless otherwise noted)

**Fig. 1 - Typical Output Characteristics,  $T_J = 25\text{ °C}$** 

**Fig. 3 - Typical Transfer Characteristics**

**Fig. 2 - Typical Output Characteristics,  $T_J = 175\text{ °C}$** 

**Fig. 4 - Normalized On-Resistance vs. Temperature**




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage




Fig. 8 - Maximum Safe Operating Area




Fig. 9 - Maximum Drain Current vs. Case Temperature




Fig. 10a - Switching Time Test Circuit




Fig. 10b - Switching Time Waveforms




Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case




Fig. 12a - Unclamped Inductive Test Circuit




Fig. 12b - Unclamped Inductive Waveforms




Fig. 12c - Maximum Avalanche Energy vs. Drain Current




Fig. 13a - Basic Gate Charge Waveform







Fig. 13b - Gate Charge Test Circuit

**Note**a.  $V_{GS} = 5 V$  for logic level devices**Fig. 14 - For N-Channel**

**TO-220 FULLPAK (HIGH VOLTAGE)**

| DIM. | MILLIMETERS |        | INCHES    |       |
|------|-------------|--------|-----------|-------|
|      | MIN.        | MAX.   | MIN.      | MAX.  |
| A    | 4.570       | 4.830  | 0.180     | 0.190 |
| A1   | 2.570       | 2.830  | 0.101     | 0.111 |
| A2   | 2.510       | 2.850  | 0.099     | 0.112 |
| b    | 0.622       | 0.890  | 0.024     | 0.035 |
| b2   | 1.229       | 1.400  | 0.048     | 0.055 |
| b3   | 1.229       | 1.400  | 0.048     | 0.055 |
| c    | 0.440       | 0.629  | 0.017     | 0.025 |
| D    | 8.650       | 9.800  | 0.341     | 0.386 |
| d1   | 15.88       | 16.120 | 0.622     | 0.635 |
| d3   | 12.300      | 12.920 | 0.484     | 0.509 |
| E    | 10.360      | 10.630 | 0.408     | 0.419 |
| e    | 2.54 BSC    |        | 0.100 BSC |       |
| L    | 13.200      | 13.730 | 0.520     | 0.541 |
| L1   | 3.100       | 3.500  | 0.122     | 0.138 |
| n    | 6.050       | 6.150  | 0.238     | 0.242 |
| Ø P  | 3.050       | 3.450  | 0.120     | 0.136 |
| u    | 2.400       | 2.500  | 0.094     | 0.098 |
| v    | 0.400       | 0.500  | 0.016     | 0.020 |

ECN: X09-0126-Rev. B, 26-Oct-09  
DWG: 5972

**Notes**

1. To be used only for process drawing.
2. These dimensions apply to all TO-220, FULLPAK leadframe versions 3 leads.
3. All critical dimensions should C meet  $C_{pk} > 1.33$ .
4. All dimensions include burrs and plating thickness.
5. No chipping or package damage.

## Disclaimer

All products due to improve reliability, function or design or for other reasons, product specifications and data are subject to change without notice.

Shenzhen VBsemi Electronics Co., Ltd., branches, agents, employees, and all persons acting on its or their representatives (collectively, the "Shenzhen VBsemi"), assumes no responsibility for any errors, inaccuracies or incomplete data contained in the table or any other any disclosure of any information related to the product.(www.VBsemi.com)

Shenzhen VBsemi makes no guarantee, representation or warranty on the product for any particular purpose of any goods or continuous production. To the maximum extent permitted by applicable law on Shenzhen VBsemi relinquished: (1) any application and all liability arising out of or use of any products; (2) any and all liability, including but not limited to special, consequential damages or incidental ; (3) any and all implied warranties, including a particular purpose, non-infringement and merchantability guarantee.

Statement on certain types of applications are based on knowledge of the product is often used in a typical application of the general product VBsemi Shenzhen demand that the Shenzhen VBsemi of. Statement on whether the product is suitable for a particular application is non-binding. It is the customer's responsibility to verify specific product features in the products described in the specification is appropriate for use in a particular application. Parameter data sheets and technical specifications can be provided may vary depending on the application and performance over time. All operating parameters, including typical parameters must be made by customer's technical experts validated for each customer application. Product specifications do not expand or modify Shenzhen VBsemi purchasing terms and conditions, including but not limited to warranty herein.

Unless expressly stated in writing, Shenzhen VBsemi products are not intended for use in medical, life saving, or life sustaining applications or any other application. Wherein VBsemi product failure could lead to personal injury or death, use or sale of products used in Shenzhen VBsemi such applications using client did not express their own risk. Contact your authorized Shenzhen VBsemi people who are related to product design applications and other terms and conditions in writing.

The information provided in this document and the company's products without a license, express or implied, by estoppel or otherwise, to any intellectual property rights granted to the VBsemi act or document. Product names and trademarks referred to herein are trademarks of their respective representatives will be all.

## Material Category Policy

Shenzhen VBsemi Electronics Co., Ltd., hereby certify that all of the products are determined to be RoHS compliant and meets the definition of restrictions under Directive of the European Parliament 2011/65 / EU, 2011 Nian. 6. 8 Ri Yue restrict the use of certain hazardous substances in electrical and electronic equipment (EEE) - modification, unless otherwise specified as inconsistent.(www.VBsemi.com)

Please note that some documents may still refer to Shenzhen VBsemi RoHS Directive 2002/95 / EC. We confirm that all products identified as consistent with the Directive 2002/95 / EC European Directive 2011/65 /.

Shenzhen VBsemi Electronics Co., Ltd. hereby certify that all of its products comply identified as halogen-free halogen-free standards required by the JEDEC JS709A. Please note that some Shenzhenese VBsemi documents still refer to the definition of IEC 61249-2-21, and we are sure that all products conform to confirm compliance with IEC 61249-2-21 standard level JS709A.