

HBL47CM20C -- Twist-Lock Chem-Marine Plug



2P3W, 15A 125V, L5-15P, White & Yellow Nylon

Product Specifications

Product Type



Product Item

Plug

Wiring Scheme

2 Pole, 3 Wire Grounding

Amperage

15A

Voltage

125V AC

NEMA Configuration

L5-15P

Item Style

Chem/Marine

Device Color

Yellow

Horsepower

0.5

Cord Dia.

.230"-.720" (5.8-18.3)

Blade Holder Material

Natural White Nylon

Terminal Retainer Material

Clear polycarbonate

Housing Material

Yellow nylon

Cord Clamp Material

Natural (white) nylon

Blade Material

Brass

Terminal Clamp Material

Cold rolled steel-nickel-plated

Terminal Screw Material

#8-32 Brass (white finish on neutral screw when used)

Ground Screw Material

Brass (green finish)

Cord Clamp Screw Material

Steel-zinc-plated

Body Holding Screw Material

Steel-zinc-plated

Ratings


Molded into face

Catalog No.

Permanently ink marked on cord clamp.

Dielectric Voltage

Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	15A-#14AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20
Listings	UL/CSA
Certified	UL2306 OEM and replacement use on convention center flat cable cord sets.
Catalog Page	Click here for catalog page B11
Hubbellnet	Click here for Hubbellnet
Catalog Section	Click here for Section-B
UPC Number	78358516050
Weight in LBs	0.15



Hubbell Incorporated (Delaware)
185 Plains Road
Milford, CT 06460-2420
Ph: (203) 882-4800
Fax: (800) 255-1031

