





FEATURES

- High breakdown voltage
- Low collector-emitter saturation voltage
- Complementary to MMBTA92 (PNP)

SOT-23

1. BASE
2. EMITTER
3. COLLECTOR











MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)




Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	300	V
V_{CEO}	Collector-Emitter Voltage	300	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current -Continuous	0.3	A
I_{CM}	Collector Current-Peak	0.5	A
P_C	Collector Power dissipation	0.35	W
$R_{\theta JA}$	Thermal Resistance, junction to Ambient	357	$^{\circ}\text{C/W}$
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C = 100\mu\text{A}, I_E = 0$	300		V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}, I_B = 0$	300		V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = 100\mu\text{A}, I_C = 0$	5		V
Collector cut-off current	I_{CBO}	$V_{CB} = 200\text{V}, I_E = 0$		0.25	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = 5\text{V}, I_C = 0$		0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE} = 10\text{V}, I_C = 1\text{mA}$	60		
	$h_{FE(2)}$	$V_{CE} = 10\text{V}, I_C = 10\text{mA}$	100	200	
	$h_{FE(3)}$	$V_{CE} = 10\text{V}, I_C = 30\text{mA}$	60		
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 20\text{mA}, I_B = 2\text{mA}$		0.2	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = 20\text{mA}, I_B = 2\text{mA}$		0.9	V
Transition frequency	f_T	$V_{CE} = 20\text{V}, I_C = 10\text{mA}, f = 30\text{MHz}$	50		MHz



SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°