



Circuit breaker 10kA, 2-pole, D, 1.6 A according to UL 489-480Y/277V

Model	
product brand name	SENTRON
product designation	Miniature circuit breakers
design of the product	Miniature circuit-breaker 5SJ4
General technical data	
number of poles	2
number of poles / note	2P
tripping characteristic class	D
mechanical service life (switching cycles) / typical	20 000
installation environment regarding EMC	Suitable for environment B (immunity to interference not applicable)
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	F
overvoltage category	3
degree of pollution	3
Voltage	
insulation voltage / at AC / rated value	440 V
Supply voltage	
type of voltage	AC/DC
operational current / at AC / rated value	1.6 A
supply voltage / at AC / rated value	400 V
operating voltage	
<ul style="list-style-type: none"> at AC / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum 	277 V
<ul style="list-style-type: none"> at DC / rated value / maximum 	60 V
<ul style="list-style-type: none"> at DC / single channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum 	60 V
<ul style="list-style-type: none"> at DC / 2-channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum 	125 V
supply voltage frequency	
<ul style="list-style-type: none"> rated value 	50 Hz
Protection class	
protection class IP	IP20, with connected conductors, IP 40 in the handle range
Switching capacity	
switching capacity current	
<ul style="list-style-type: none"> acc. to EN 60898 / rated value 	10 kA
<ul style="list-style-type: none"> acc. to IEC 60947-2 / rated value 	15 kA
Dissipation	
power loss [W] / for rated value of the current / at AC / in	1.5 W

hot operating state / per pole	
Main circuit	
type of voltage supply / at AC / acc. to UL 489 and CSA C22.2 No. 5-02	480/277
suitability for operation	Mechanical engineering / industry
Product details	
product function / neutral conductor switching	No
product feature / touch protection	Yes
product component	
• tunnel terminals top	No
• tunnel terminals bottom	No
• combined terminal top	Yes
• combined terminal bottom	Yes
product feature	
• halogen-free	Yes
• sealable	Yes
• silicon-free	Yes
product extension / installable / supplementary devices	Yes
Product function	
product function / note	Terminal tightening torque for Cu, 60/75°C; 3.5Nm/31lb.in
Short circuit	
breaking capacity short-circuit current (I _{cn}) / at AC / acc. to UL 1077 and CSA C22.2 No.235	10 kA
Connections	
connectable conductor cross-section / finely stranded / with core end processing	
• minimum	1.5 mm ²
• maximum	25 mm ²
position / of power supply cord	Any
Mechanical Design	
height	121 mm
width	36 mm
depth	76 mm
installation depth	70 mm
number of modular width units	2
fastening method	on standard mounting rail
mounting position	any
net weight	335 g
Environmental conditions	
influence of the surrounding temperature	max. 95% humidity
vibration resistance	50 m/s ² at 25 to 150Hz and 60m/s ² at 35Hz (4sec)
vibration resistance / acc. to IEC 60068-2-6	50 m/s ² at 25 to 150Hz and 60m/s ² at 35Hz (4sec)
ambient temperature	
• minimum	-25 °C
• maximum	55 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	75 °C
Certificates	
reference code	
• acc. to DIN EN 61346-2	F
• acc. to IEC 81346-2	F
General Product Approval	Declaration of Conformity



Test Certificates

[Special Test Certificate](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SJ4215-8HG42>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SJ4215-8HG42>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SJ4215-8HG42

Tender specifications

<http://www.siemens.com/specifications>

