

1

2

3

4

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		独立各PIN数图纸, 增加开孔定位尺寸	2024.12.10	阿树

PART NO.:

X05 26 W I Z B 5
① ② ③ ④ ⑤ ⑥ ⑦

- ①Series No
②Row No-Pin No: 26Pin
③Welding Board Angle:W-Male
④T:Tradutlional C:Car-pin
⑤Planting Catogtry:
1:1u 2:2u 3:3u 4:5u 5:15u 6:30u 7:AuSn
⑥Color:B-Black W-White BL-Blue
⑦1:TYPE-1; 2:TYPE-2; 5:TYPE-5; 7:TYPE-7

Specifications:

规格:

- 1.Voltage rating:250VAC/DC
额定电压: 250V AC/DC
2.Current rating:3A AC/DC
额定电流: 3A AC/DC
3.Withstanding voltage:500V AC/minute
耐受电压: ≥500V AC/分钟
4.Temperature range: -55℃-+105℃
温度范围: -55℃-+105℃
5.Insulation resistance:1000MΩMIN
绝缘电阻: ≥1000MΩ
6.Contact resistance:30mΩMax
接触电阻: ≥30mΩ

Material:

材料:

- 7.Rubber core:PBT UL94V-0
胶芯: PBT UL94V-0
8.The iron shell:SPCC Nivkel Plating/Tin Plating/Gold Plating
铁壳: SPCC,镀镍/镀锡/镀金
B、成品不能有弯针, R角不一致等不良。

3.96 [0.156]

12.50 [0.492]±0.15
8.30 [0.327]±0.20

39.20 [1.543]±0.38

33.32 [1.312]±0.13

26.50 [1.043]±0.25

2.29 [0.090]±0.05

ø0.76 [ø0.030]

ø3.00 [ø0.118]

0.50 [0.020]±0.05

1.145 [0.045]±0.05

6.00 [0.236]±0.20

4.50 [0.177]±0.30

27.65 [1.089]±0.25

0.60 [0.024]

16.65 [0.656]

16.65 [0.656]

2.29 [0.090]

0.50 [0.020]

3.96 [0.156]

ø3.20 [ø0.126]

ø1.00 [ø0.039]

0.645 [0.025]

1.145 [0.045]

PCB LAYOUT

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:	MODEL TYPE: D-SUB
CHECKED		UNIT: mm/in	PART NO.: X0526WT7B5
APPROVED		SIZE: A4	DWG NO.: X-X0526WT7B5