


Kinghelm®



REV.	ECN NO.	DESCRIPTION	DATE	DESIGN
A0.		新版发行	20. 04. 06	Yang
A1.		重新核对图面	21. 01. 07	LiHui

PIN数	A±0.1	B±0.1	C±0.1
2P	7.60	4.50	1.25
3P	8.85	5.75	2.50
4P	10.10	7.00	3.75
5P	11.35	8.25	5.00
6P	12.60	9.50	6.25

Specifications:

Rated Voltage : 125V AC/DC

Rated Current : 1A AC,DC

Withstand Voltage : 200V AC/minute

Contact Resistance : 50mΩ(MAX.)

Insulation Resistance : 100MΩ(MIN.)

Storage Temperature Range:-40°C~+85°C;

Operation Temperature Range:-25°C~+70°C;

3	插片	黄铜H65	镀镍锡	
2	插针	黄铜H65	镀镍锡	
1	基座	LCP	本色	
序号	品名	材质	电镀/颜色	备注

深圳市金航标电子有限公司


UNLESS OTHERWISE,
GENERAL TOLERANCE:
X. xxx ±0.05
X. xx ±0.15
X. x ±0.25

ANGULAR:
X. xx ° ±1°
X. x ° ±3°
X. ° ±5°

KH-A1251LF-04A

0755-28190160

THIRD ANGLE PROJECTION



DRAWN:

UNIT:

MM

SCALE

1:1

SIZE:

A4

SHEET:

1/1

REV.

A1

CHECKED:

APPROVED: