




REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.07.01	阿树

Technolo Request:

1.Outlook:
NO burr,no hurt.

2.Electronic performance:

a:Insulation resistance:
Above DC500V/100MΩ;

b:Endure voltage:
AC500V at 1 minute;


c:Contact resistance:
Under 30MΩ;

3.Insertion fore & withdrawal force;0.3—3kgf.

4.Salt spray test :24H.

Waterproof tube	C3604	Ni
Spring	Phosphor Bronze	Ni
Shrapnel	Phosphor bronze	Ni
Terminal	Phosphor bronze	Ni
Plastic	PBT	Black
PAPT NAMF	MATERIAL	PLATING

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAuCES	



DESIGN	阿树	VIEW:	MODEL TYPE: DC POWER JACK
CHECKED		UNIT: mm/in	PART NO.: DC-F0765
APPROVED		SIZE: A4	DWG NO.: DC-F0765
		SCALE	PAGE
		N/A	1/1
		REVISION	A1