





REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.10.17	阿树



PCB Layout(Pattern side)



Circuit Diagram

NOTE:
Rating: DC 30V 0.1A
Operating Force: 40 ± 10gf
Lifetime: 100,000 Cycles

PART NO	H
TM-W07A-1	8.3
TM-W07A-2	8.5
TM-W07A-3	8.7
TM-W07A-4	9.3
TM-W07A-5	11.0
TM-W07A-6	12.3
TM-W07A-7	13.7

⑤	Contact Spring	1	Phosphor Bronze	Plating silver
④	Terminal	4	Phosphor Bronze	Plating silver
③	Base	1	Nylon	
②	Cover	1	Nylon	
①	Keystake	1	Nylon	

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:		MODEL TYPE:	DETECT SWITCH
CHECKED		UNIT:	mm/in	PART NO.:	TM-W07A-2
APPROVED		SIZE:	A4	DWG NO.:	