

Product data sheet

Miniature connectors




Product description	M16 Square male panel mount connector, Contacts: 12 (12-a), unshielded, solder, IP67, UL
Area	series 723
Part no.	09 0131 300 12


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	09 0131 300 12
Connector design	Square male panel mount connector
Type standard	DIN EN 61076-2-106
Version	Connector pin straight
Connector locking system	screw
Termination	solder
Degree of protection	IP67
Cross-sectional area	0.25 mm ² / AWG 24
Temperature range from/to	-40 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	13.07
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	500 V
Rated current	3,0 A
Insulation resistance	$\geq 10^{10} \Omega$
Pollution degree	1
Overvoltage category	I

Product data sheet

Miniature connectors



Product description	M16 Square male panel mount connector, Contacts: 12 (12-a), unshielded, solder, IP67, UL
Area	series 723
Part no.	09 0131 300 12

Insulating material group	III
EMC compliance	unshielded

Material

Housing material	Zinc die-cast nickel-plated
Contact body material	PBT (UL94 V-0)
Contact material	CuZn (brass)
Contact plating	Au (gold)
Locking material	Zinc die-cast nickel-plated
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	2d505d8b-9737-4a0d-9cd3-4db1ef037c65

Authorization/approvals


Approvals	UL
-----------	----

Classifications

ETIM 9.0	EC003569
----------	----------

Product description	M16 Square male panel mount connector, Contacts: 12 (12-a), unshielded, solder, IP67, UL
Area	series 723
Part no.	09 0131 300 12

Assembly instructions / Panel cut-out



Product description	M16 Square male panel mount connector, Contacts: 12 (12-a), unshielded, solder, IP67, UL
Area	series 723
Part no.	09 0131 300 12

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages. Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).