



接触电阻: $\leq 20\text{m}\Omega$

5.Plating Category: V01-All Gold Flash

NUMBER OF POSITIONS	DIMENSION	
	A	B
2x17	20.32	25.78
2x18	21.59	27.05
2x20	24.13	29.59
2x22	26.67	32.13
2x25	30.48	35.94
2x30	36.83	42.29
2x32	39.37	44.83
2x34	41.91	47.37
2x35	43.18	48.64
2x37	45.72	51.18
2x38	46.99	52.45
2x40	49.53	54.99

X1270H-2x03-PTV01	PBT UL 94V-0	Phosphor Bronze	Gold Flash	X1270WV-2x03B	XPD0.635-A30PXX-DC	X1270HI-2x03
				X1270WR-2x03B		
				X1270WVS-2x03B		
PART NO	Material	Material(Pin And Solder Tabs)	Finish(Pin And Solder Tabs)	Suitable XKB Wafer	Suitable XKB flat cable	Suitable XKB DIP

XKLE

DSND		SCALE: N/A	MODEL TYPE: 1.27mm two-piece IDC		
DWN		VIEW: 	PART NO.: X1270H-2x03-PTV01		
CHKD		UNIT: mm/in	DWG NO.: X-X1270H-2x03-PTV01		
APPD		SIZE: A4			
PRECISION CO., LIMITED			WEIGHT	SHEET	REVISION
				1/1	A0