

SEMICONDUCTOR GENERAL CATALOG

半導体製品総覧表2017年7月版

ASSPs 専用IC

Automotive ICs / 車載用

Communications ICs / 通信用

TV and Audio ICs / テレビ/ オーディオ用

Application Processors / アプリケーションプロセッサ

Interface Bridges / インタフェースブリッジ

Other Consumer Product ICs / その他機器用

Automotive ICs / 車載用

Image Recognition Processors / 画像認識プロセッサ

Part Number	Maximum Operating Frequency (MHz) MeP, MPE	Maximum Operating Frequency (MHz) ARM Cortex-A9 MPCore	Media Processing Engine [MPE]	Image Processing Accelerator										Video Input Interface (ch)	Video Output Interface (ch)	PCI Express® (lane)	UART (ch)	SPI (ch)	I ² C (ch)	CAN (ch)	CAN FD (ch)	PCM (ch)	Memory Controller	CPU Core		Package
				Affine Transformation	Pyramid	Filter	Histogram	Histogram of Oriented Gradients [HOG]	Enhanced CoHOG	Matching	SfM	Toshiba's Proprietary 32-bit RISC CPU MeP	ARM 32-bit RISC ARM® Cortex®-A9 MPCore													
TMPV7502XBG ☆	266.7	—	○	○	—	○	○	○	—	○	—	○	—	1	1	—	5	1	4	2	—	2	DDR2-SDRAM, SRAM, ROM, NOR Flash	○	—	PLFBGA324
TMPV7504XBG ☆	266.7	—	○	○	—	○	○	—	—	○	—	—	2	1	—	5	4	4	3	—	2	DDR2-SDRAM, SRAM, ROM, NOR Flash	○	—	PBGA516	
TMPV7506XBG ☆	266.7	—	○	○	—	○	○	○	—	○	—	—	4	1	1	5	4	4	3	—	2	DDR2-SDRAM, SRAM, ROM, NOR Flash	○	—	PBGA516	
TMPV7528XBG ☆	266.7	300	○	○	—	○	○	○	—	○	—	—	4	1	1	5	4	4	3	—	2	DDR2-SDRAM, SRAM, ROM, NOR Flash	○	○	PBGA516	
TMPV7602XBG **☆	266.7	—	○	○	○	○	○	○	○	○	—	—	2	1	—	5	4	4	2	2	2	LPDDR2-SDRAM, SRAM, ROM, NOR Flash	○	—	PLFBGA521	
TMPV7608XBG ☆	266.7	—	○	○	○	○	○	○	○	○	○	—	8	2	—	5	4	8	3	—	2	LPDDR2-SDRAM, SRAM, ROM, NOR Flash	○	—	PFBGA796	

☆: Dry-packed / 防湿梱包品

**: Under development / 開発中

- The video input interface of the TMPV7608XBG has a 4-of-8 video switch.
- The video input interface of the TMPV7602XBG has a 1-of-2 video switch.
- ARM and Cortex are registered trademarks of ARM Limited (or its subsidiaries) in the EU and/or elsewhere.
- PCI Express and PCIe are registered trademarks of PCI-SIG.
- TMPV7608XBGのビデオ入力インタフェースは、8入力4選択のビデオスイッチ付きです。
- TMPV7602XBGのビデオ入力インタフェースは、2入力1選択のビデオスイッチ付きです。
- ARMおよびCortexは、ARM Limited (またはその子会社)のEUまたはその他の国における登録商標です。
- PCI ExpressまたはPCIeは、PCI-SIG社の商標または登録商標です。

Automotive Display Controllers / 車載ディスプレイコントローラ

Part Number	Maximum Operating Frequency (MHz)	3D Graphic Accelerator	2D Graphic Accelerator	Display Controller (ch)	Video Capture (ch)	Stepper Motor Controller (ch)	DMAC (ch)	UART (ch)	SPI (ch)	I ² C (ch)	CAN (ch)	Timer (ch)	PWM (ch)	ADC (ch)	Memory Controller	Others	Package
TX4961XBG-240 ☆	240	—	○	1	1	—	8	3	2	1	3	8	6	8	NAND Flash, DDR-SDRAM, SRAM, ROM, NOR Flash	MLB, AC-link controller	PBGA456
TX4964FG-120 ☆	120	—	○	1	1	—	4	2	2	1	2	5	3	—	SRAM, ROM, NOR Flash	Embedded DRAM: 4 MBytes, I ² S: 2 ch	LQFP176
TX4966XBG-280 ☆	280	○	○	2	2	—	8	2	4	1	4	19	14	—	SDRAM, SRAM, ROM, NOR Flash	Embedded DRAM: 8 MBytes, APiX: 2 ch, MLB, I ² S: 2 ch	PBGA456
TMPR460XBG-300 ☆	300	—	○	1	1	4	8	2	2	1	2	10	10	8	Q-SPI Flash, LPDDR/SDRAM, SRAM, ROM, NAND/NOR Flash	I ² S: 2 ch, RTC, Voltage regulator	PBGA244
TMPR461XBG-300 ☆	300	—	○	2	1	5	8	2	2	1	3	10	24	14	Q-SPI Flash, LPDDR/SDRAM, SRAM, ROM, NAND/NOR Flash	I ² S: 2 ch, MLB, RTC, Voltage regulator	PBGA328

☆: Dry-packed / 防湿梱包品

Automotive Video Processors / 車載ディスプレイ用映像処理 IC (Dual/Single-Picture Video Processors) / (2画面/単画面映像処理 IC)

Part Number	Function	Package	ADC	Color Decoder	Overlay	Muteless Input Switch	New Picture Adjustment	LVDS Input I/F	Two Digital Video Output	Panel	Operating Temperature (°C)	Supply Voltage (V)
TC90195XBG ☆	Dual pictures processing	LFPGA293	1	1	○	○	○	○	○	WXGA+	-40 to +85	1.1 to 1.3 3.0 to 3.6
TC90175XBG ** ☆	Picture processing	LFPGA293	1	1	—	○	○	○	○	Full-HD		
TC90197XBG ☆	Dual pictures processing	LPGA 256	4	2	○	—	○	—	—	WVGA		1.4 to 1.6 2.3 to 2.7 3.0 to 3.6
TC90193SBG ☆	Quick display function for Rear view monitor	FBGA228	1	1	—	—	○	—	—			
TC90193ASBG ☆			1	1	—	○	○	—	—			
TC90202XBG ☆	LCD Timing control & Picture quality adjustment	FBGA121	—	—	—	—	○	—	—			
TC90205FG ☆		LQFP80	—	—	—	—	○	—	—			
TC90207FG ☆	LVDS to LVTTTL	LQFP64	—	—	—	—	—	○	—			1.4 to 1.6 3.0 to 3.6

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

(Video Decoder ICs) / (ビデオデコーダIC)

Part Number	Function	Package	ADC	Color Decoder	Component Input (D2)	New Picture Adjustment	ITU-R BT.601 Output	ITU-R BT.656 Output	8 bit Serial Output (D2)	Operating Temperature (°C)	Supply Voltage (V)
TC90104AFG ☆	Video Decoder	LQFP64	3	1	○	—	○	○	○	-40 to +85	1.4 to 1.6 2.3 to 2.7 3.0 to 3.6
TC90106FG ☆			3	1	○	—	—	○	○		
TC90105FG ☆	Video Decoder with 2.5 V regulator	LQFP80	2	2	—	○	○	○	—		
TC90107FG ☆		LQFP64	1	1	—	○	—	○	—		

☆: Dry-packed / 防湿梱包品

System Power Supplies / システム電源

Part Number	Package	Functions	Characteristics			Remarks	Supply Voltage (V)
			Output Voltage Typ. (V)	Input Voltage Max (V)	Power Dissipation Max (W)		
TB9004FNG	SSOP24 (0.65)	2 ch CPU voltage regulators Watchdog timer	3.4/2.5/1.5 5	45 (1 s)	0.85	Watchdog timer enable/disable All regulators enable/disable 5 V regulator enable/disable 2 reset outputs External transistor required	6 to 16
TB9005FNG ☆	SSOP20 (0.65)	CPU voltage regulator Watchdog timer	5	45 (60 s)	0.6	Low current consumption: 90 μA (typ.) Watchdog timer enable/disable Reset detection: 4.75 V or 4.25 V (selectable) External transistor required	6 to 18
TB9021FNG ☆	HTSSOP16	CPU voltage regulator Watchdog timer	5	50	2.8	Low current consumption: 30 μA (typ.) Output transistors included Window watchdog timer Reset detection: 4.7 V or 4.2 V (selectable)	6 to 18
TB9042FTG ** ☆	HQFN52	CPU voltage regulator Switching regulators Series regulators Watchdog timer SPI communications	1.5/1.2 5 5 5/3.3	40 (1 s)	5.5	2 switching regulators 1.2 V/1.5 V selectable 3 series regulators 2 watchdog timers SPI communications Diagnosis functions	7 to 20.1
TB9044FNG ** ☆	HTSSOP48	CPU voltage regulator Switching regulator Series regulator Trackers Watchdog timer SPI communications	5 5 5 5	40 (1 s)	3.84	Buck/Boost Switching regulator 1 series regulator 3 trackers 1 watchdog timer SPI communications Diagnosis functions	2.7 to 18

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

Blushed DC Motor Driver ICs / ブラシ付きモータドライバ

Part Number	Package	Functions	Remarks	Output Current Max (A)	Supply Voltage (V)
TB9051FTG ☆	PQFN28 (0.65)	1-ch H-bridge driver	PWM control, Small package, Built-in overcurrent detection, etc.	5	4.5 to 28
TB9052FNG ☆	HTSSOP48 (0.5)	H-bridge pre-driver	High speed pre-driver = 250 ns (typ.) High speed current monitor = 3 V/μs (min) Sequence control logic Diagnostic function	1	6 to 18
TB9056FNG ☆	SSOP24 (0.65)	LIN-compatible H-bridge driver	LIN Rev. 1.3 Motor driver: R _{DS(on)} (H bridge: P-ch + N-ch) = 2.2 Ω (typ.) Potentiometer support	0.3	7 to 18
TB9057FG ☆	LQFP48 (0.5)	H-bridge pre-driver	High speed pre-driver = 250 ns (typ.) High speed current monitor = 3 V/μs (min) Motor rotation detection Diagnostic function	1	5 to 21
TB9101FNG ☆	SSOP24 (0.65)	2-ch H-bridge driver	Diagnostic function, standby function, P-ch + N-ch = 1.2 Ω (typ.)	1	7 to 18
TB9102FNG ☆	SSOP24 (0.65)	6-ch Half-bridge driver / 3-ch H-bridge driver	SPI communications, Diagnosis function P-ch + N-ch = 1.0 Ω (typ.)	1	7 to 18
TB9110FNG ☆	SSOP24 (0.65)	N-ch MOS gate driver	Diagnosis function and standby function, Built-in charge pump, Ta = 105°C	0.02 ⁽¹⁾	7 to 18
TB9110AFNG ** ☆	SSOP24 (0.65)	N-ch MOS gate driver	Diagnosis function and standby function, Built-in charge pump, Ta = 125°C	0.02 ⁽¹⁾	7 to 18

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

Note (1): An external N-channel FET is required as a gate driver. / Gate Driver: 外付け Nch-FET 使用。

Stepping Motor Driver ICs / ステッピングモータドライバ

Part Number	Package	Functions	Remarks	Output Current Max (A)	Supply Voltage (V)
TB9120FTG ** ☆	QFN28 (Wettable half cut)	2-Phase Bipolar stepping motor driver (Clock-in controlled)	PWM controlled constant-current drive 1/32 microstep (maximum resolution), stall detect features and Mix DECAY mode	1	7.0 to 18

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

Brushless Motor Driver ICs / ブラシレスモータドライバ

Part Number	Package	Functions	Characteristics	Supply Voltage (V)
TB9061FNG ☆	SSOP24 (0.65)	Sensorless control with 120 degree commutation, Pre-driver	3-phase, full-wave sensorless drive PWM pulse input control/DC level input control (selectable) Comparator for induced voltage detection Thermal shutdown, overcurrent detection, overvoltage detection	5.5 to 18
TB9061AFNG ☆	SSOP24 (0.65)	Sensorless control with 120 degree commutation, Pre-driver	3-phase, full-wave sensorless drive PWM pulse input control/DC level input control (selectable) Comparator for induced voltage detection Thermal shutdown, overcurrent detection, overvoltage detection Output PWM Dynamic range expansion	5.5 to 18
TB9067FNG ☆	SSOP24 (0.65)	Hall IC, Pre-driver for 120 degree commutation	120-degree commutation logic Pre-drivers for a high-side P-ch FET and a low-side N-ch FET PWM pulse input control/DC level input control (selectable) Two options for setting the output duty cycle (pulse input, analog input) Overcurrent detection, thermal shutdown, supply voltage increase, supply voltage decrease Soft start	6 to 18
TB9068FG ☆	LQFP48 (0.5)	Motor driver with a LIN transceiver	Motor driver R _{DS(on)} : P-ch = 1 Ω (typ.), N-ch = 1 Ω (typ.) 120-degree commutation logic LIN 1.3-based transceiver 5-V supply for a microcontroller (external PNP transistor required) Watchdog timer, power-on reset timer Three analog comparators for Hall devices	7 to 18
TB9080FG ☆	LQFP64 (0.5)	Hall elements, Pre-driver for sine-wave control	Supports both PWM and DC inputs for sine-wave driver logic. Motor RPM feedback, auto lead angle correction Abnormal condition detection such as overcurrent, overvoltage, overtemperature and motor lock Sleep mode	7 to 18
TB9081FG ** ☆	LQFP64 (0.5)	3-Phase Brushless Motor Pre-driver	5-channel safety relay Selectable operation on fault detection Initial diagnosis of detection circuits	4.5 to 18

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

IGBT Gate-Pre Driver Control IC / IGBTゲートプリドライバコントロールIC

Part Number	Package	Functions	Characteristics	Supply Voltage (V)
TB9150FNG ** ☆	SSOP48 (0.5)	IGBT Gate-Pre driver control IC for in-vehicle inverters, Built-in isolation device (optical coupling) for primary-side and secondary-side	IGBT Gate-Pre driver control, IGBT temperature monitor, Short circuit detection (current sense, DESAT), UVLO, etc., Built-in fly-back controller	6 to 20 (GND1 Standard, Primary-side) 11 to 18 (VE Standard, Secondary-side)

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

Interface Bridges / インタフェースブリッジ

Part Number	Package	Applications	Functions and Features	Supply Voltage (V)
TC9560XBG ** ☆	PLFBGA170 (0.65)	Ethernet AVB Bridge Solution For Automotive Applications	Host (External application) I/F: PCIe I/F [Gen2.0 (5 GT/s), Endpoint, Single lane], Automotive I/F: Ethernet AVB [IEEE802.1AS, IEEE802.1Qav], MAC Audio I/F: I2S/TDM Peripheral I/F: I2C/SPI, Quad-SPI, UART, GPIO, INTC CPU Core: ARM Cortex-M3	1.8/3.3 for IO 1.8/2.5/3.3 for RGMII/RMII 1.1 for Core
TC9560AXBG ** ☆	PLFBGA170 (0.65)	Ethernet AVB Bridge Solution For Automotive Applications	Host (External application) I/F: PCIe I/F [Gen2.0 (5 GT/s), Endpoint, Single lane], Automotive I/F: Ethernet AVB [IEEE802.1AS, IEEE802.1Qav], MAC, 2ch CAN-FD Audio I/F: I2S/TDM Peripheral I/F: I2C/SPI, Quad-SPI, UART, GPIO, INTC CPU Core: ARM Cortex-M3	1.8/3.3 for IO 1.8/2.5/3.3 for RGMII/RMII 1.1 for Core
TC9560BxBG ** ☆	PLFBGA170 (0.65)	Ethernet AVB Bridge Solution For Automotive Applications	Host (External application) I/F: HSIC I/F (480 Mbps) Automotive I/F: Ethernet AVB [IEEE802.1AS, IEEE802.1Qav], MAC, 2ch CAN-FD Audio I/F: I2S/TDM Peripheral I/F: I2C/SPI, Quad-SPI, UART, GPIO, INTC CPU Core: ARM Cortex-M3	1.8/3.3 for IO 1.2 for HSIC 1.8/2.5/3.3 for RGMII/RMII 1.1 for Core

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

Communications ICs / 通信用

Wireless Communications ICs / 無線通信用 IC

Part Number	Package (Pin Pitch)	Functions	Applications	Functions and Features	Supply Voltage (V)	
TC32306FTG ☆	QFN36 (0.5 mm)	RF-IC	Remote keyless entry (remote door lock/unlock), TPMS (tire pressure monitoring system), Remote control (AM/FM), etc.	Single-chip RF transceiver; Supported modulation: ASK/FSK. Use for four RF Band: 315, 434, 868/915-MHz, Fractional-N ΔΣ PLL Receiver sensitivity: under -116 dBm (At IF BW = 320 kHz, data rate = 600 Hz, frequency deviation = +/-40 kHz) Transmitter power: +10 dBm (typ. by maximum coarse step control) Two IF Filter bandwidths: wide 320 kHz (typ.) at IF = 230 kHz/ middle 270 kHz (typ.) at IF = 280 kHz Signal Detection: RSSI detection, noise detection (only for FSK), preamble detection Serial control (4 wire SPI) /EEPROM control (This IC also can be used as a specialized for receiving.)	Current consumption TX: 12 mA (typ. /@Output level: +10 dBm) RX: 9.7 mA (typ.) Battery Saving: 0 μA (typ.) RX (ASK/QPSK): 62 mA/66 mA (typ.) TX (ASK/QPSK): 75 mA/75 mA (typ.) TX: 75 mA (typ. /@Output level: +14 dBm) Sleep: 5 μA RX: 30 mA (typ.) TX: 35 mA (typ.)	3V Use: 2.0 to 3.3 5V Use: 2.4 to 5.5
TC32163FG ☆	LQFP48 (0.5 mm)		DSRC (Dedicated Short Range Communication), ETC (Electronic Toll Collection System)	5.8-GHz transceiver; ASK/QPSK, transmit power = -15 dBm to -2 dBm Transmitter EVM = 6.5% (typ.) ACPR $\leq 5\text{ MHz}$ = -42 dBc (typ.), receiver EVM = 8% (typ.)		2.7 to 3.6
TC32166FNG ☆	SSOP10 (0.65 mm)		DSRC (Dedicated Short Range Communication), ETC (Electronic Toll Collection System)	5.8-GHz power amp; Power gain = 20 dB (typ.), ACPR (ASK/QPSK, $\leq 5\text{ MHz}$) = -44 dBc (@Output level: +14 dBm)		3.0 to 3.6
TC32168FTG ☆	QFN32 (0.5 mm)		ETC (Electronic Toll Collection System) for China	Single-Chip 5.8 GHz transceiver including Wakeup function and FM0 Modem Supported modulation: ASK/OOK Receiving sensitivity: -60 dBm (typ.) Wakeup sensitivity: -45 dBm (typ.) Transmit power: +3 dBm		1.8 to 3.6

☆: Dry-packed / 防湿梱包品

Proximity Wireless Compliant Products / 近接無線対応製品

Part Number	Package	Applications	Functions and Features	Supply Voltage (V)
TC35420AXLG ☆	WFLGA81	Proximity wireless transceiver	TransferJet™-compliant Wireless IC On-chip RF circuitry, digital signal processing SDIO UHS-I support	3.3 to 1.8
TJM35420XLQ ☆	LGA68	Proximity wireless transceiver	TransferJet™-compliant Wireless Module Built-in RF components SDIO UHS-I support	3.3 to 1.8

☆: Dry-packed / 防湿梱包品

Bluetooth® ICs / Bluetooth® IC

(Bluetooth® Classic / Bluetooth® Classic_low energy dual ICs for Consumer) /

(民生用Bluetooth® Classic / Bluetooth® Classic low energy dual IC)

CPU	Host-IF	Other Interfaces
ARM7TDMI-S™	UART	I ² C/SPI /GPIO

Part Number	Bluetooth Core Spec.	Profiles	Features	Operating temperature (°C)	Supply Voltage (V)	Package
TC35661SBG-203 ☆	Ver.4.2 Classic	SPP	<ul style="list-style-type: none"> · Receiver sensitivity -90 dBm · Transmit power 2 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA 	-40 to +85	1.7 to 1.9 or 2.7 to 3.6	BGA64 (0.5 mm Pitch) 5.0 mm x 5.0 mm
TC35661SBG-007 ☆		HCI	<ul style="list-style-type: none"> · Receiver sensitivity -91 dBm · Transmit power 2 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA · Wide band Speech 			
TC35661DBG-008 ☆			Ver.4.2 Classic/low energy dual			<ul style="list-style-type: none"> · Receiver sensitivity -90 dBm · Transmit power 2 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA
TC35661SBG-009 ☆ *	Ver.4.0 Classic/low energy dual					<ul style="list-style-type: none"> · Receiver sensitivity -90 dBm · Transmit power 2 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA
TC35661SBG-501 ☆		SPP, GATT, SMP	<ul style="list-style-type: none"> · Receiver sensitivity -91 dBm · Transmit power 2 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA 			BGA64 (0.5 mm Pitch) 5.0 mm x 5.0 mm
TC35661SBG-502 ☆			Ver.4.2 Classic/low energy dual			
TC35661DBG-501 ☆	<ul style="list-style-type: none"> · Receiver sensitivity -91 dBm · Transmit power 2 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA 					
TC35661SBG-503 ☆	Ver.4.2 Classic/low energy dual	SPP, GATT, SMP	<ul style="list-style-type: none"> · Receiver sensitivity -91 dBm · Transmit power 2 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA 			BGA64 (0.5 mm Pitch) 5.0 mm x 5.0 mm
TC35661SBG-551 ☆ *			<ul style="list-style-type: none"> · Receiver sensitivity -91 dBm · Transmit power 1 dBm · Current consumption in TX/RX (peak) 63 mA · Current consumption in deep sleep mode 30 μA · LE Secure Connections 			

☆: Dry-packed / 防湿梱包品

*: New product / 新製品

Bluetooth® ICs / Bluetooth® IC

(Bluetooth® low energy ICs for Consumer) / (民生用Bluetooth® low energy IC)

Host-IF	Other Interfaces	Other functions
UART	I ² C/SPI/GPIO	ADC/PWM/DC-DC

Part Number	Bluetooth Core Spec.	Profiles	NFC Tag	CPU	Features	Operating temperature (°C)	Supply Voltage (V)	Package	
TC35667FTG-005 ☆	Ver.4.0 low energy	HCI, GATT, SMP		ARM® ARM7TDMI-S™	<ul style="list-style-type: none"> Receiver sensitivity -92 dBm Transmit power 0 dBm Current consumption in TX/RX (peak) 5.9 mA (3.3 V, -4 dBm TX power)/ 5.7 mA Current consumption in deep sleep mode 0.05 μA 	-40 to +85	1.8 to 3.6	QFN40 (0.5 mm Pitch) 6.0 mm x 6.0 mm	
TC35670FTG-005 ☆			✓			-30 to +85			
TC35667FTG-006 ☆	Ver.4.1 low energy					<ul style="list-style-type: none"> Receiver sensitivity -92 dBm Transmit power 0 dBm Current consumption in TX/RX (peak) 5.9 mA (3.3 V, -4 dBm TX power)/ 5.7 mA Current consumption in deep sleep mode 0.05 μA Scatternet 		-40 to +85	QFN40 (0.5 mm Pitch) 6.0 mm x 6.0 mm
TC35670FTG-006 ☆			✓		-30 to +85			QFN40 (0.5 mm Pitch) 6.0 mm x 6.0 mm	
TC35676FSG-001 ☆					-40 to +85			QFN40 (0.4 mm Pitch) 5.0 mm x 5.0 mm	
TC35675XBG-001 ☆			✓		BGA52 (0.5 mm Pitch) 4.5 mm x 4.5 mm				
TC35678FSG-002 ☆ *	Ver.4.2 low energy			Cortex®-M0	<ul style="list-style-type: none"> Receiver sensitivity -93.5 dBm Transmit power 0 dBm Current consumption in TX/RX (peak) 3.3 mA (3.0 V, 0 dBm TX power)/ 3.3 mA Current consumption in deep sleep mode 0.05 μA Scatternet LE Data Length Extension LE Secure Connections 	-40 to +85	QFN40 (0.4 mm Pitch) 5.0 mm x 5.0 mm		
TC35678FXG-002 ☆ *			QFN60 (0.4 mm Pitch) 7.0 mm x 7.0 mm						
TC35679FSG-002 ☆ *			QFN40 (0.4 mm Pitch) 5.0 mm x 5.0 mm						
TC3567CFSG-001 ☆ **									
TC3567DFSG-001 ☆ **									

☆: Dry-packed / 防湿梱包品

*: New product / 新製品

** : Under development / 開発中

- ・ FeliCa is a registered trademark of Sony Corporation.
- ・ The Tag section of this product uses the FeliCa Lite-S technology licensed from Sony Corporation.
- ・ ARM is a registered trademark of ARM Limited (or its subsidiaries) in the EU and/or elsewhere. ARM7 is a trademark of ARM Limited (or its subsidiaries) in the EU and/or elsewhere.
- ・ FeliCaはソニー株式会社の登録商標です。
- ・ 本製品の Tag 部は、ソニー株式会社の FeliCa Lite-S 技術ライセンスに基づいて製品化されています。
- ・ ARMは、ARM Limited (またはその子会社) の EU またはその他の国における登録商標です。ARM7は、ARM Limited (またはその子会社) の EU またはその他の国における商標です。

(Bluetooth® Classic / Bluetooth® Classic_low energy dual / Bluetooth® low energy ICs for Automotive) /
 (車載用Bluetooth® Classic / Bluetooth® Classic_low energy dual / Bluetooth® low energy IC)

Part Number	Bluetooth Core Spec.	Profiles	Features	Operating temperature (°C)	Supply Voltage (V)	Package
TC35661IDBG-203 ☆	Ver.4.2 Classic	SPP	<ul style="list-style-type: none"> Receiver sensitivity -90 dBm Transmit power 2 dBm Current consumption in TX/RX (peak) 63 mA Current consumption in deep sleep mode 30 µA 	-40 to +85	2.7 to 3.6	BGA64 (0.8 mm Pitch) 7.0 mm x 7.0 mm
TC35661IDBG-007 ☆		HCI	<ul style="list-style-type: none"> Receiver sensitivity -90 dBm Transmit power 2 dBm Current consumption in TX/RX (peak) 63 mA Current consumption in deep sleep mode 30 µA Wide band Speech 			
TC35661IDBG-008 ☆			<ul style="list-style-type: none"> Receiver sensitivity -91 dBm Transmit power 2 dBm Current consumption in TX/RX (peak) 63 mA Current consumption in deep sleep mode 30 µA Wide band Speech 			
TC35661IDBG-009 ☆ **	Ver.4.2 Classic/low energy dual	SPP, GATT, SMP	<ul style="list-style-type: none"> Receiver sensitivity -91 dBm Transmit power 2 dBm Current consumption in TX/RX (peak) 63 mA Current consumption in deep sleep mode 30 µA Wide band Speech 			
TC35661IDBG-503 ☆ **		HFP, A2DP, AVRCP, PBAP, SPP	<ul style="list-style-type: none"> Receiver sensitivity -93 dBm Transmit power 1 dBm Current consumption in TX/RX (peak) 174 mA On-chip DSP Wide band Speech 			
TC35668IXBG ☆	Ver.4.0 Classic	HCI, GATT, SMP	<ul style="list-style-type: none"> Receiver sensitivity -92 dBm Transmit power 0 dBm Current consumption in TX/RX (peak) 5.9 mA (3.3 V, -4 dBm TX power)/ 5.7 mA Current consumption in deep sleep mode 0.05 µA 	-40 to +105	3.0 to 3.6	BGA97 (0.5 mm Pitch) 6.0 mm x 6.0 mm
TC35667IFTG-005 ☆	Ver.4.0 low energy		<ul style="list-style-type: none"> Receiver sensitivity -92 dBm Transmit power 0 dBm Current consumption in TX/RX (peak) 5.9 mA (3.3 V, -4 dBm TX power)/ 5.7 mA Current consumption in deep sleep mode 0.05 µA Scatternet 			
TC35667IFTG-006 ☆ **	Ver.4.1 low energy		<ul style="list-style-type: none"> Receiver sensitivity -93.5 dBm Transmit power 0 dBm Current consumption in TX/RX (peak) 3.3 mA (3.0 V, 0 dBm TX power)/ 3.3 mA Current consumption in deep sleep mode 0.05 µA Scatternet LE Data Length Extension LE Secure Connections 			
TC35679IFTG-002 ☆ **	Ver.4.2 low energy					

☆: Dry-packed / 防湿梱包品

** : Under development / 開発中

TV and Audio ICs / テレビ/オーディオ用

TV Tuning & Channel Decoder ICs / TVチューナ/伝送復調用IC

(Channel Decoder ICs) / (伝送復調用IC)

Part Number	Package	Use	Features	Supply Voltage (V)
TC90532XBG ☆	FBGA177	8PSK demodulator OFDM demodulator	Digital BS broadcasting, digital CS broadcasting (ISDB-S), 8PSK, QPSK demodulation, error correction, Digital terrestrial broadcasting (ISDB-T), OFDM demodulation, error correction, A/D converter, memory	3.0 to 3.6 1.1 to 1.3
TC90522XBG ☆	FBGA177	8PSK demodulator OFDM demodulator (Two channels each)	Digital BS broadcasting, digital CS broadcasting (ISDB-S), 8PSK, QPSK demodulation, error correction, Digital terrestrial broadcasting (ISDB-T), OFDM demodulation, error correction, A/D converter, memory	3.0 to 3.6 1.1 to 1.3
TC90527AFG ☆	LQFP48	OFDM demodulator	Digital terrestrial broadcasting (ISDB-T), OFDM demodulation, error correction, A/D converter, memory	3.0 to 3.6 1.1 to 1.3

☆: Dry-packed / 防湿梱包品

Audio ICs / オーディオ用IC

(Power Amp ICs) / (パワーアンプIC)

Part Number	Package	Intended Use		Output Power (P _{OUT})			Features	Supply Voltage (V)
		Car Stereos	Engine Sound	Recommended V _{CC}	R _L = 4 Ω THD = 10%	R _L = 8 Ω THD = 10%		
TB2909FNG	HTSSOP16		○	12 V		2 W x 1	MOS amplifier for 1 SEPP channel, Standby function, Mute function, Maximum power: 5 W x 1 ch, Output short detection, Thermal detection, Speaker open detection, Overvoltage detection	6 to 16
TB2931HQ	SPP25	○		13.2 V	24 W x 4		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 49 W x 4 ch, R _L = 2 Ω operation guaranteed, Output DC offset detection, Output short detection, +B overvoltage detection, Half short detection	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)
TB2938HQ	SPP25	○		13.2 V	24 W x 4		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 49 W x 4 ch, Output DC offset detection, Output short detection, +B overvoltage detection, Half short detection, Speaker burning prevention	6 to 18
TB2959HQ	SPP25	○		13.2 V	23 W x 4		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 47 W x 4 ch, AUX amp, +B overvoltage detection, Speaker burning prevention	6 to 18
TB2941HQ	SPP25	○		13.2 V	24 W x 4		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 49 W x 4 ch, R _L = 2 Ω operation guaranteed, High-side-switch, Output DC offset detection, 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)
TB2952AHQ	SPP25	○		13.2 V	24 W x 4		MOS amplifier for 4 BTL channels, Command-controlled standby and mute mode, Hardware-standby mode, Maximum power: 49 W x 4 ch, I ² C-bus controlled self-diagnosis, R _L = 2 Ω operation guaranteed, Selectable voltage gain (26/12 dB), 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)

Audio ICs / オーディオ用IC
(Power Amp ICs) / (パワーアンプIC)

Part Number	Package	Intended Use		Output Power (P _{OUT})			Features	Supply Voltage (V)
		Car Stereos	Engine Sound	Recommended V _{CC}	R _L = 4 Ω THD = 10%	R _L = 8 Ω THD = 10%		
TB2975HQ	SPP25	○		13.2 V	24 W x 4		MOS amplifier for 4 BTL channels, Command-controlled standby, and mute mode, Hardware-standby mode, Maximum power: 49 W x 4 ch, Class-KB efficiency, I ² C-bus controlled self-diagnosis, Cross-wiring detection, R _L = 2 Ω operation guaranteed, Selectable voltage gain (26/16 dB), 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)
TB2925HQ	SPP25	○		13.2 V	24 W x 4		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 49 W x 4 ch, Class-KB efficiency, R _L = 2 Ω operation guaranteed, Output DC offset detection, Output short detection, +B overvoltage detection, Cross-wiring detection, 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)
TB2996HQ	SPP25	○		13.2 V	24 W x 4		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 49 W x 4 ch, R _L = 2 Ω operation guaranteed, High quality sound, Output DC offset detection, Output short detection, +B overvoltage detection, 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)
TCB001HQ	SPP25	○		13.2 V	22 W x 4		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 45 W x 4 ch, Output DC offset detection, Output short detection, +B overvoltage detection, 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω)
TCB501HQ	SPP25	○		13.2 V	24 W		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 49 W x 4 ch, R _L = 2 Ω operation guaranteed, High-side-switch (include of back flow preventing circuit), Fulltime Output DC offset detection, 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)
TCB502HQ	SPP25	○		13.2 V	24 W		MOS amplifier for 4 BTL channels, Standby function, Mute function, Maximum power: 49 W x 4 ch, R _L = 2 Ω operation guaranteed, Full time Output DC offset detection, 6 V operations (Engine idling reduction capability), Proof against from GSM	6 to 18 (R _L = 4 Ω) 6 to 16 (R _L = 2 Ω)

(Compact Disc Player IC) / (コンパクトディスクプレーヤ用IC)

Part Number	Package	Classification	Features	Supply Voltage (V)
TC94B16FG ☆	LQFP80	Single-chip processor	Sync separation, EFM demodulation, error detection/correction, error-corrected output, microcontroller interface, search control, digital equalizer, text data decoding, variable-speed playback, x8 oversampling digital filter, multi-bit D/A converter, head amp On-chip 3.3-to-1.5-V regulator, x4 playback mode for CD-DA/R	3.3/1.5

☆: Dry-packed / 防湿梱包品

(CD/MP3 Player ICs) / (CDMP3 プレーヤ用IC)

Part Number	Package	Classification	Features	Supply Voltage (V)
TC94A92FG ☆	LQFP80	Single-chip processor	CD-DA/R/RW: x2 playback, low power consumption, 1-Mbit SRAM (128 Kwords x 8 bits), standby mode, Supports various compressed audio formats: MP3, WMA, AAC RF amp, CD digital servo, 8fs digital filter, Multi-bit D/A converter	3.3/1.5
TC94A93MFG ☆	LQFP80	Single-chip processor	CD-DA/R/RW: x2 playback, low power consumption, 1-Mbit SRAM (128 Kwords x 8 bits), standby mode, Supports various compressed audio formats: MP3, WMA, AAC RF amp, CD digital servo, 8fs digital filter Multi-bit D/A converter, shock-proof feature	3.3/1.5

☆: Dry-packed / 防湿梱包品

Application Processors / アプリケーションプロセッサ

TZ1000 Series / TZ1000 シリーズ

Part Number	Package (package size) (ball pitch)	CPU	CPU Frequency (MHz)	SRAM (KB)	NOR Flash (MB)	Accelerometer	Gyroscope	Magnetometer	Bluetooth® core specification version	Bluetooth® Low Energy Controller	Quad SPI for Flash Connection	GPIO (ch)	I ² C (Master/Slave) (ch)	UART (ch)	DMA (ch)	AES	True Random Number Generator	SPI (ch)	PWM (ch)	32-bit Timer	Watchdog Timer	12-bit ADC	24-bit ADC	USB	Operating Temperature (°C)
TZ1011MBG	PLFBGA153 (8.50 mm x 9.80 mm) (0.5 mm)	ARM Cortex-M4F	48	288	(1) 1	●	●	●	4.0	●	●	(2) 24 [32]	(2) 2 [3]	(2) 2 [3]	8	128/192/256-bits key length	1	(2) 3 [4]	4	2	1	4	3	USB 2.0 Device	Ta = -20 to 70
TZ1021MBG	PVFBGA110 (6.70 mm x 4.00 mm) (0.4 mm)					-	-	-	-	32		3	3	4											
TZ1031MBG	PLFBGA153 (8.50 mm x 9.80 mm) (0.5 mm)					●	●	-	4.0	●		(2) 24 [32]	(2) 2 [3]	(2) 2 [3]				(2) 3 [4]							
TZ1041MBG	PLFBGA136 (6.70 mm x 8.00 mm) (0.5 mm)					-	-	-	4.1	●		(2) 24 [32]	(2) 2 [3]	(2) 2 [3]				(2) 3 [4]							

Note (1): NOR Flash is connected internally via SPI. / Nor FlashはSPI経由で内部接続。

(2): Number inside the bracket means the channel counts of internal MCU. / []内の数字は内蔵のMCUのチャネル数を含めた数です。

TZ1200 Series / TZ1200 シリーズ

Part Number	Package (package size) (ball pitch)	CPU	CPU Frequency (MHz)	SRAM (MB)	e-MMC (ch)	External bus	2D Graphics Accelerator	MIPI® DBI Type B	MIPI® DBI Type C	MIPI® DSI	Quad SPI for Flash Connection	GPIO (ch)	I ² C (Master/Slave) (ch)	UART (ch)	DMA (ch)	True Random Number Generator	Compressor & Decompressor	SPI (ch)	PWM (ch)	32-bit Timer	Watchdog Timer	12-bit ADC	24-bit ADC	DAC	USB	LED driver	Operating Temperature (°C)
TZ1201XBG	PUFBGA210 (8.0 mm x 8.0 mm) (0.4 mm)	ARM Cortex-M4F	96 (up to 120)	2.2	2	1	●	●	●	●	●	120	2	4	16	1	1	4	8	2	1	16	4	1	USB 2.0 Device	4	Ta = -20 to 70

- ARM and Cortex are trademarks or registered trademarks of ARM Limited in the EU and other countries.
- eMMC™ is a registered trademark of the MultiMediaCard Association (MMCA).
- Bluetooth is a registered trademark owned by Bluetooth SIG, Inc. and any use of such mark by Toshiba is under license.
- MIPI is a licensed trademark of MIPI Alliance, Inc. in the U.S. and other jurisdictions.
- ApP Lite is a trademark of Toshiba Corporation.
- All other trademarks and trade names are properties of their respective owners.
- ARM、およびCortexはARM LimitedのEUおよびその他の国における商標もしくは登録商標です。
- eMMCは、JEDEC Solid State Technology Associationの商標です。
- Bluetoothは、Bluetooth SIG, Inc.の登録商標であり、東芝はライセンスに基づき使用しています。
- MIPIは、米国およびその他の管轄区域におけるMIPI Alliance, Inc.のライセンス商標です。
- ApP Liteは、株式会社東芝の商標です。
- その他本文中に記載されている会社名および製品名は、それぞれ各社が商標または登録商標として使用している場合があります。

TZ2000 Series / TZ2000 シリーズ

Part Number	Package (package size) (ball pitch)	CPU	CPU Frequency	SRAM (MByte)	L1 I Cache (Kbyte)	L1 D Cache (Kbyte)	L2 Cache (Kbyte)	DRAM Controller	External Extended Bus Interface	2D Graphic Engine	LCD Controller	USB	UART	I ² C	I ² S	SPIB	SPIM	PWM	12bit ADC	SDIO/e-MMC	GPIO	DMA controller	Timer/Counter	RTC	Secure Boot System & Encrypt Data Function	FPU	Camera I/F	Operating Temperature (°C)		
TZ2002XBG	PLFBGA280 (15 mm x 15 mm) (0.8 mm pitch)	ARM® Cortex®-A9 MPCore	200	1	16	16	—	DDR3/DDR3L x 8 bit	—	Toshiba original graphics accelerator	WVGA (800 x 480 pixel) 60 fps, 24 bit Parallel I/F	USB2.0 host/device	4	5	2	2	2	5	4	2	64	●	9	1	—	—	—	Ta = -20 to 70 Ta = -40 to 85 (1)		
TZ2003XBG	PLFBGA280 (15 mm x 15 mm) (0.8 mm pitch)		300	1 MB + 32 KB	32	32	128	DDR3/DDR3L x 16 bit	Address: 27 bit, Data: 32 bit	Toshiba original graphics accelerator	WVGA (800 x 480 pixel) 60 fps, 24 bit Parallel I/F	USB2.0 host /device	4	4	2	2	7	6	4	3	128	●	9	1	●	●	●	Ta = -20 to 80 Ta = -40 to 85 (1)		
TZ2100XBG	PLFBGA310 (16 mm x 16 mm) (0.8 mm pitch)		600	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
TZ2101XBG			—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
TZ2102XBG			—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Note(1): Extended temperature range / 温度拡張品

- ARM and Cortex are trademarks or registered trademarks of ARM Limited in the EU and other countries.
- ApP Lite is a trademark of Toshiba Corporation.
- All other trademarks and trade names are properties of their respective owners.
- ARM、およびCortexはARM LimitedのEUおよびその他の国における商標もしくは登録商標です。
- ApP Liteは、株式会社東芝の商標です。
- その他本文中に記載されている会社名および製品名は、それぞれ各社が商標または登録商標として使用している場合があります。

TZA300 Series / TZA300 シリーズ

Part Number	Package (package size)	Video I/O Interface	Video Input Port	Video Output Port	Feature	Applications	Supply Voltage (V)
TZA300XBG	PFBGA448 (19 mm x 19 mm) (0.8 mm pitch)	<ul style="list-style-type: none"> LVCOS Parallel I/O - YUV/RGB 444 (24 bit) - YUV 422 (16 bit) - YUV 422 (8 bit) (1) 	1	2	<ul style="list-style-type: none"> Up to 1080p @ 60 fps (2) Video Dynamic Range Enhancing Ultra-low latency processing (100 pixel clock cycles or less) 3D Noise Reduction Control Interface: I²C BUS 	Surveillance camera system Surveillance monitor system	Core, PLL: 1.2 DDR3 I/F: 1.5/2.5 I/O: 1.8/3.3

Note(1): YC multiplex for only 480p/576p

(2): Special license file is required for performing dynamic range enhancer processing of input videos other than VGA, 480p and 576p. For more information kindly contact the sales division. / VGA、480P及び576P以外の入力映像に対する鮮明化には特別なライセンスファイルが必要です。詳細については、営業部門にお問い合わせください。

Interface Bridges / インタフェースブリッジ

MPD: Mobile Peripheral Devices

Part Number	Package (Package Size) (Ball Pitch)	Functions		Feature/Supported Resolution	Applications	Supply Voltage (V)
		Rx (input)	Tx (output)			
TC358743XBG ☆	P-TFPGA64 (6 mm x 6 mm) (0.65 mm)	HDMI® 1.4	MIPI® CSI-2 1.01	HDMI® to MIPI® CSI-2 Camera Serial Interface Bridge HDMI® Video format: Up to FHD (1920 x 1080, 60 fps, 24 bpp (bits per pixel))	Smart TV, smart monitor, smart set-top box, Digital Media Adapter (DMA)	1.2 (MIPI®/Core) 3.3 (HDMI®) 1.8 to 3.3 (I/O) 2.5 (APLL)
TC358749XBG ☆	P-VFBGA80 (7 mm x 7 mm) (0.65 mm)	HDMI® 1.4b	MIPI® CSI-2 1.01	HDMI® to MIPI® CSI-2 Camera Serial Interface Bridge Video de-interlacing, Video scaling HDMI® Video format: Up to FHD (1920 x 1080, 60 fps, 24 bpp)	Smart TV, smart monitor, smart set-top box, DMA	1.2 (MIPI®/Core/PLL) 3.3 (HDMI®) 1.8 to 3.3 (I/O)
TC358840XBG ☆	P-VFBGA80 (7 mm x 7 mm) (0.65 mm)	HDMI® 1.4b	MIPI® CSI-2 1.01	HDMI® to MIPI® CSI-2 Camera Serial Interface Bridge HDMI® Video format: Up to 4K Ultra HD (3840 x 2160, 30 fps, 24 bpp)	Smart set top box, smart TV, smart monitor, DMA	1.2 MIPI® 1.1 CORE/PLL 3.3 (HDMI®) 1.8 to 3.3 (I/O)
TC358779XBG ☆	P-VFBGA80 (7 mm x 7 mm) (0.65 mm)	HDMI® 1.4b	MIPI® DSI 1.1	HDMI® to MIPI® DSI Display Serial Interface Bridge Video de-interlacing, Video scaling HDMI® Video format: Up to FHD (1920 x 1080, 60 fps, 24 bpp)	Tablet, digital still camera (DSC), LCD displays, video projector, head mounted display (HMD), game accessory, other integrated display panel application with MIPI® DSI interface	1.2 (MIPI®/CORE/PLL) 3.3 (HDMI®) 1.8 to 3.3 (I/O)
TC358870XBG ☆	P-VFBGA80 (7mm x 7mm) (0.65 mm)	HDMI® 1.4b	MIPI® DSI 1.1	HDMI® to MIPI® DSI Display Serial Interface Bridge HDMI® Video format: Up to 4K Ultra HD (3840 x 2160, 30 fps, 24 bpp)	HMD, mobile devices, gaming accessories, wearable computers display	1.2 MIPI® 1.1 CORE/PLL 3.3 (HDMI®) 1.8 to 3.3 (I/O)
TC358746XBG ☆	P-VFBGA72 (4.5 mm x 4.5 mm) (0.40 mm)	(1) MIPI® CSI-2 1.01 (2) Parallel	(1) Parallel (2) MIPI® CSI-2 1.01	MIPI® CSI-2 to Parallel Camera Interface Bridge Parallel to MIPI® CSI-2 Camera Interface Bridge Up to 100 MHz PCLK frequency for Output mode, and 166 MHz for Input mode.	Smartphone, tablet, VOIP phone, industrial device	1.2 (MIPI®/Core) 1.8 to 3.3 (I/O)
TC358748XBG ☆	P-VFBGA80 (7 mm x 7 mm) (0.65 mm)					
TC358762XBG ☆	P-VFBGA64 (5 mm x 5 mm) (0.50 mm)	(1) MIPI® DSI 1.01 (2) MIPI® DSI 1.01	(1) MIPI® DPI 2.0 (2) MIPI® DBI-2 2.0	MIPI® DSI to MIPI® DPI/DBI Display Interface Bridge Up to WXGA (1366 x 768, 60 fps, 24 bpp)	Tablet, smartphone, smart watch, HMD, portable navigation device (PND)	1.2 (MIPI®/Core) 1.8 to 3.3 (I/O)
TC358763XBG ☆	P-VFBGA72 (4.5 mm x 4.5 mm) (0.40 mm)	(1) MIPI® DPI 2.0 (2) MIPI® DBI-2 2.0	(1) MIPI® DSI 1.01 (2) MIPI® DSI 1.01	MIPI® DPI/DBI to MIPI® DSI Display Interface Bridge Up to XGA (1024 x 768, 60 fps, 24 bpp)	Smartphone, DSC, digital video camera (DVC), smart watch, HMD, PND	1.2 (MIPI®/Core) 1.8 to 3.3 (I/O)
TC358764XBG ☆	P-TFPGA49 (5 mm x 5 mm) (0.65 mm)	MIPI® DSI 1.01	LVDS	MIPI® DSI to LVDS Display Interface Bridge (single link) Up to WXGA (1366 x 768, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 3.3 (LVDS) 1.8 to 3.3 (I/O)
TC358765XBG ☆	P-TFPGA64 (6 mm x 6 mm) (0.65 mm)	MIPI® DSI 1.01	LVDS	MIPI® DSI to LVDS Display Interface Bridge (dual link) Up to UXGA (1600 x 1200, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 3.3 (LVDS) 1.8 to 3.3 (I/O)
TC358766XBG ☆	P-VFBGA120 (6 mm x 6 mm) (0.50 mm)	(1) MIPI® DSI 1.01 (2) MIPI® DPI 2.0 (3) MIPI® DSI 1.01	(1) VESA DisplayPort™ 1.1a (2) VESA DisplayPort™ 1.1a (3) MIPI® DPI 2.0	MIPI® DSI to DisplayPort® Display Interface Bridge MIPI® DPI to DisplayPort® Display Interface Bridge MIPI® DSI to MIPI® DPI Display Interface Bridge Up to WUXGA (1920 x 1200, 60 fps, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 1.2 & 1.8 (DisplayPort®) 1.8 (I/O)
TC358767AXBG ☆	P-VFBGA81 (5 mm x 5 mm) (0.50 mm)	(1) MIPI® DSI 1.01 (2) MIPI® DPI 2.0	(1) VESA DisplayPort™ 1.1a (2) VESA DisplayPort™ 1.1a	MIPI® DSI to DisplayPort® Display Interface Bridge MIPI® DPI to DisplayPort® Display Interface Bridge Up to WUXGA (1920 x 1200, 60 fps, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 1.2 & 1.8 (DisplayPort®) 1.8 (I/O)
TC358768AXBG ☆	P-VFBGA72 (4.5 mm x 4.5 mm) (0.40 mm)	RGB	MIPI® DSI 1.02	RGB to MIPI® DSI Display Interface Bridge Up to WUXGA (1920 x 1200, 60 fps, 24-bit/pixel)	Smartphone, tablet, Ultrabook™	1.2 (MIPI®/Core) 1.8 to 3.3 (I/O)
TC358778XBG ☆	P-VFBGA80 (7 mm x 7 mm) (0.65 mm)					
TC358770AXBG ☆	P-VFBGA100 (5 mm x 5 mm) (0.40 mm)	MIPI® DSI 1.02	VESA DisplayPort™ 1.1a	MIPI® DSI to DisplayPort® Display Interface Bridge Up to (QSXGA 2560 x 2048, 60 fps, 24 bit per pixel)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 1.2 & 1.8 (DisplayPort®) 1.8 (I/O)
TC358777XBG ☆	P-VFBGA80 (7 mm x 7 mm) (0.65 mm)					

☆: Dry-packed / 防湿梱包品

MPD: Mobile Peripheral Devices

Part Number	Package (Package Size) (Ball Pitch)	Functions		Feature/Supported Resolution	Applications	Supply Voltage (V)
		Rx (input)	Tx (output)			
TC358771XBG ☆	P-VFBGA49 (5 mm x 5 mm) (0.65 mm)	MIPI® DSI 1.01	LVDS	MIPI® DSI to LVDS Display Interface Bridge with Back Light Control (single link) Up to UXGA (1600 x 1200, 60 fps, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 1.8 (LVDS) 1.8 to 3.3 (I/O)
TC358772XBG ☆	P-VFBGA 64 (6 mm x 6 mm) (0.65 mm)	MIPI® DSI 1.01	LVDS	MIPI® DSI to LVDS Display Interface Bridge with Back Light Control (dual link) Up to WUXGA (1920 x 1200, 60 fps, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 1.8 (LVDS) 1.8 to 3.3 (I/O)
TC358774XBG ☆	P-VFBGA49 (5 mm x 5 mm) (0.65 mm)	MIPI® DSI 1.01	LVDS	MIPI® DSI to LVDS Display Interface Bridge (single link) Up to UXGA (1600 x 1200, 60 fps, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 1.8 (LVDS) 1.8 to 3.3 (I/O)
TC358775XBG ☆	P-VFBGA64 (6 mm x 6 mm) (0.65 mm)	MIPI® DSI 1.01	LVDS	MIPI® DSI to LVDS Display Interface Bridge (dual link) Up to WUXGA (1920 x 1200, 60 fps, 24 bpp)	Tablet, Ultrabook™	1.2 (MIPI®/Core) 1.8 (LVDS) 1.8 to 3.3 (I/O)
TC358860XBG ☆	P-VFBGA65 (5 mm x 5 mm) (0.5 mm)	VESA Embedded DisplayPort (eDP™) ver1.4	MIPI® DSI 1.02	4K2K VESA's Embedded Display Port (eDP™) to MIPI® DSI Display Serial Interface Bridge Up to 4K Ultra HD (4096 x 2048, 60 fps, 3840 x 2160@, 24 bpp)	Phablet, tablet, portable game and PC, HMD	1.2 (MIPI®) 1.1 (Core, MIPI® D-PHY, eDP-PHY) 1.8 (eDP™-PHY) 1.8 or 3.3 (I/O, HPD)

☆: Dry-packed / 防湿梱包品

I/O Expander

Part Number	Package (Pin Pitch)	Functions	Applications	Functions and Features	Supply Voltage (V)
TC35894XBG ☆	P-TFBGA36 (0.5 mm)	I/O expander	I/O port expansion	Up to 24 GPIO ports. GPIO ports can be used for key matrix (up to 96 keys) or PWM/timer (up to 3 channels). Chattering reduction, internal clock oscillator, internal pull-up/pull-down resistors Up to 26-port direct key functionality (when GPIOs are not used).	1.62 to 3.60
TC35894FG ☆	P-LQFP44 (0.8 mm)			Up to 24 GPIO ports. GPIO ports can be used for key matrix (up to 96 keys) or PWM/timer (up to 3 channels). Chattering reduction, internal clock oscillator, internal pull-up/pull-down resistors Up to 26-port direct key functionality (when GPIOs are not used)	1.62 to 3.60

☆: Dry-packed / 防湿梱包品

- MIPI: MIPI is a trademark of MIPI Alliance, Inc.
- HDMI: HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries.
- DisplayPort, eDP: VESA, DisplayPort and eDP are trademarks, service marks, registered trademarks, and/or registered service marks owned by VESA.
- Ultrabook: *Ultrabook is a trademark of Intel Corporation* in the U.S. and/or other countries
- MIPI: MIPIはMIPI Alliance, Inc.の登録商標です。
- HDMI: HDMI、HDMIロゴ、High-Definition Multimedia Interfaceは、米国およびその他の国々における、HDMIライセンスの商標または登録商標です。
- DisplayPort、eDP: VESA、Displayport、eDPはVESA (Video Electronics Standards Association)の商標または登録商標です。
- Ultrabook: Ultrabookは、アメリカ合衆国および/またはその他の国におけるIntel Corporationの商標です。

Other Product ICs / その他機器用

Shock Sensor ICs / ショックセンサIC

Part Number	Package	Device Type	Output Source Current Min (μ A)	Output Sink Current Min (μ A)	Window-Comparator Detection Voltage Levels Typ. (V)	Supply Current ($T_a = 25^\circ\text{C}$) Max (mA)	Supply Voltage (V)	Remarks
TB6082FNG	VSOP10	Shock sensor amp (low-noise charge amp)	80 (OP-AMP2) (@ $V_{CC} - 0.3$ V)	500 (OP-AMP2) (@ 0.3 V)	—	5.0 ($V_{CC} = 2.5$ V, $V_{ref} = 1.0$ V)	2.3 to 5.5	1 channel, Built-in amplifier for notch filter, low-noise
TB6082FTG	QFN16	Shock sensor amp (low-noise charge amp)	80 (OP-AMP2) (@ $V_{CC} - 0.3$ V)	500 (OP-AMP2) (@ 0.3 V)	—	5.0 ($V_{CC} = 2.5$ V, $V_{ref} = 1.0$ V)	2.3 to 5.5	1 channel, Built-in amplifier for notch filter, low-noise
TB6086FTG	QFN16	Shock sensor amp (Sensor signal Amplifier)	100 (OP-AMP) (@ $V_{CC} - 0.3$ V)	100 (OP-AMP) (@ 0.3 V)	2.05 (High) 1.25 (Low)	4.0 ($V_{CC} = 3.3$ V, $V_{ref} = 1.65$ V)	3.0 to 5.5	1 channel, Built-in amplifier for notch filter, Window Comparator
TC93A33FTG	QFN16	Shock sensor amp (low-noise charge amp)	80 (OP-AMP2) (@ $V_{CC} - 0.3$ V)	80 (OP-AMP2) (@ 0.3 V)	—	4.5 ($V_{CC} = 1.8$ V, EN = H)	1.6 to 2.3	1 channel, Built-in amplifier for notch filter, low-noise

High-Frequency Modulator ICs / 高周波重畳IC

Part Number	Package	Device Type	Frequency (MHz)	Amplitude (mApp)	Operating Current Consumption ($V_{DD} = 5.0$ V, $T_a = 25^\circ\text{C}$) Max (mA)	Supply Voltage (V)	Remarks
TC93A14AFUG	SSOP6	High-frequency modulator for optical disk (2-ch)	250 to 450	25 to 80	21.5	4.5 to 5.5	Spread spectrum type

Interface ICs for Hot Water Dispensers / 給湯器用インタフェースIC

Part Number	Package	Features	Applications	Supply Voltage (V)
T6B70BFG	SOP16	Carrier receiver, carrier identification, carrier pseudo-sine wave generator	Communication for hot water dispensers	4.5 to 5.5
T6B70BFNG	SSOP16	Carrier receiver, carrier identification, carrier pseudo-sine wave generator Smaller package version of T6B70BFG	Communication for hot water dispensers	4.5 to 5.5

SEMICONDUCTOR GENERAL CATALOG

半導体製品総覧表

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as "TOSHIBA". Hardware, software and systems described in this document are collectively referred to as "Product".

- ▶ TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- ▶ This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- ▶ Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- ▶ **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT. For details, please contact your TOSHIBA sales representative.**
- ▶ Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- ▶ Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- ▶ The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- ▶ **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NON-INFRINGEMENT.**
- ▶ Product may include products using GaAs (Gallium Arsenide). GaAs is harmful to humans if consumed or absorbed, whether in the form of dust or vapor. Handle with care and do not break, cut, crush, grind, dissolve chemically or otherwise expose GaAs in Product.
- ▶ Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- ▶ Product may include products subject to foreign exchange and foreign trade control laws.
- ▶ Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

In addition to the above, the following are applicable only to development tools.

- ▶ Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Use the Product in a way which minimizes risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. For using the Product, customers must also refer to and comply with the latest versions of all relevant TOSHIBA information, including without limitation, this document, the instruction manual, the specifications, the data sheets for Product.
- ▶ Product is provided solely for the purpose of performing the functional evaluation of a semiconductor product. Please do not use Product for any other purpose, including without limitation, evaluation in high or low temperature or humidity, and verification of reliability.
- ▶ Do not incorporate Product into your products or system. Products are for your own use and not for sale, lease or other transfer.

製品取り扱い上のお願い

株式会社東芝およびその子会社ならびに関係会社を以下「当社」といいます。本資料に掲載されているハードウェア、ソフトウェアおよびシステムを以下「本製品」といいます。

- ▶ 本製品に関する情報等、本資料の掲載内容は、技術の進歩などにより予告なしに変更されることがあります。
- ▶ 文書による当社の事前の承諾なしに本資料の転載複製を禁じます。また、文書による当社の事前の承諾を得て本資料を転載複製する場合でも、記載内容に一切変更を加えたり、削除したりしないでください。
- ▶ 当社は品質、信頼性の向上に努めていますが、半導体・ストレージ製品は一般に誤作動または故障する場合があります。本製品をご使用頂く場合は、本製品の誤作動や故障により生命・身体・財産が侵害されることのないように、お客様の責任において、お客様のハードウェア・ソフトウェア・システムに必要な安全設計を行うことをお願いします。なお、設計および使用に際しては、本製品に関する最新の情報（本資料、仕様書、データシート、アプリケーションノート、半導体信頼性ハンドブックなど）および本製品が使用される機器の取扱説明書、操作説明書などをご確認の上、これに従ってください。また、上記資料などに記載の製品データ、図、表などに示す技術的な内容、プログラム、アルゴリズムその他応用回路例などの情報を使用する場合は、お客様の製品単独およびシステム全体で十分に評価し、お客様の責任において適用可否を判断してください。
- ▶ 本製品は、特別に高い品質・信頼性が要求され、またはその故障や誤作動が生命・身体に危害を及ぼす恐れ、膨大な財産損害を引き起こす恐れ、もしくは社会に深刻な影響を及ぼす恐れのある機器（以下「特定用途」という）に使用されることは意図されていませんし、保証もされていません。特定用途には原子力関連機器、航空・宇宙機器、医療機器、車載・輸送機器、列車・船舶機器、交通信号機器、燃焼・爆発制御機器、各種安全関連機器、昇降機器、電力機器、金融関連機器などが含まれますが、本資料に個別に記載する用途は除きます。特定用途に使用された場合には、当社は一切の責任を負いません。なお、詳細は当社営業窓口までお問い合わせください。
- ▶ 本製品を分解、解析、リパースエンジニアリング、改造、改変、翻案、複製等しないでください。
- ▶ 本製品を、国内外の法令、規則及び命令により、製造、使用、販売を禁止されている製品に使用することはできません。
- ▶ 本資料に掲載してある技術情報は、製品の代表的動作・応用を説明するためのもので、その使用に際して当社及び第三者の知的財産権その他の権利に対する保証または実施権の許諾を行うものではありません。
- ▶ 別途、書面による契約またはお客様と当社が合意した仕様書がない限り、当社は、本製品および技術情報に関して、明示的にも黙示的にも一切の保証（機能動作の保証、商品性の保証、特定目的への合致の保証、情報の正確性の保証、第三者の権利の非侵害保証を含むがこれに限らない。）をしておりません。
- ▶ 本製品にはGaAs（ガリウムヒ素）が使われているものがあります。その粉末や蒸気等は人体に対し有害ですので、破壊、切断、粉砕や化学的な分解はしないでください。
- ▶ 本製品、または本資料に掲載されている技術情報を、大量破壊兵器の開発等の目的、軍事利用の目的、あるいはその他軍事用途の目的で使用しないでください。また、輸出に際しては、「外国為替及び外国貿易法」、「米国輸出管理規則」等、適用ある輸出関連法令を遵守し、それらの定めるところにより必要な手続を行ってください。
- ▶ 本製品には、外国為替及び外国貿易法により、輸出または海外への提供が規制されているものがあります。
- ▶ 本製品のRoHS適合性など、詳細につきましては製品個別に必ず当社営業窓口までお問い合わせください。本製品のご使用に際しては、特定の物質の含有・使用を規制するRoHS指令等、適用ある環境関連法令を十分調査の上、かかる法令に適合するようご使用ください。お客様がかかる法令を遵守しないことにより生じた損害に関して、当社は一切の責任を負いかねます。

上記に加えて、以下は開発ツールのみ適用されます。

- ▶ 当社は品質、信頼性の向上に努めていますが、本製品は誤作動または故障する場合があります。本製品をご使用頂く場合は、本製品の誤作動や故障により生命・身体・財産が侵害されることのないようにご使用ください。本製品をご使用頂く場合は、本製品に関する最新の情報（本資料、取扱説明書、仕様書、データシートなど）をご確認の上、これに従ってください。
- ▶ 本製品は、半導体製品の機能評価に使用されることを意図しています。機能評価以外の目的（温度・湿度特性評価、信頼性評価など）には使用しないでください。
- ▶ 本製品をお客様の製品に組み込まないでください。また、本製品を販売、譲渡、貸与等しないでください。

【お問い合わせ先】

TOSHIBA

TOSHIBA ELECTRONIC DEVICES & STORAGE CORPORATION

東芝デバイス&ストレージ株式会社

https://toshiba.semicon-storage.com/

©2017 TOSHIBA ELECTRONIC DEVICES & STORAGE CORPORATION