



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (Cd/m ²)	*RATED LIFE (HRS)
CF20325-24B	8400 Kelvin x = .290 REF. y = .305 REF.	**1830 MAX.	735 @ 5mA	5.0 TYP. 7.0 MAX.	46,000 TYP.	20,000 MIN. 40,000 AVG.

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

**MAY BE HIGHER WHEN MOUNTED IN METAL RAIL AND USING INPUT HARNESS, REF. 2250 Vrms Max. @ 0 C.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP								
			DRAWN BY		APPV'D BY		DATE	SIZE	FSCM NO.	DRAWING NO.					
A			CHANGE BRIGHTNESS TO 46,000 TYP.		5/3/05		L. WENGSTROM	J.K.	5/3/05	A	55335	CF20325-24B			
			RELEASED		4/15/04										
REV. NO.	DESCRIPTION/ECO NUMBER				APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE		RELEASED DATE	REVISION DATE	REV. NO.	SHEET
										NONE		4/15/04	5/3/05	A	1 OF 1