



## Specifications:

Approval category	: UL224
Standard	: CSA, LR54949
Approval bodies	: UL
Shrink ratio	: 2:1
Shrink temperature	: 100°C
Minimum operating temperature	: -55°C
Maximum operating temperature	: 135°C

## Specification Table

Material	Colour	Dielectric Strength (kV/mm)	Unshrunk Diameter	Fully Shrunk Diameter	Flammability Rating	External Length / Height (m)	Reel Length (m)	Part Number					
Irradiated polyolefin	Black	20	1.6	0.8	VW-1	150	150	SP16/RL/BLACK					
			3.2	1.6				SP32/RL/BLACK					
			4.8	2.4				SP48/RL/BLACK					
			6.4	3.2		75	75	SP64/RL/BLACK					
			9.5	4.7				SP95/RL/BLACK					
			12.7	6.3				SP127/RL/BLACK					
			19	9.5		60	60	SP190/RL/BLACK					
Polyolefin			Black	20		1.6	0.8	VW-1	1.2	-	SP16/1.2/BLACK		
						2.4	1.2				SP24/1.2/BLACK		
						3.2	1.6				SP32/1.2/BLACK		
4.8						2.4	SP48/1.2BLACK						
6.4						3.2	SP64/1.2BLACK						
9.5						4.7	SP95/1.2/BLACK						
12.7						6.3	SP127/1.2/BLACK						
19	9.5	SP190/1.2/BLACK											
38.1	19	SP381/1.2/BLACK											
50.8	25.4	SP508/1.2/BLACK											
Irradiated polyolefin	Black	20			9.5	4.7	VW-1				5	-	SP95/5/BLACK
					12.7	6.3							SP127/5/BLACK

Dimensions : Millimetres (Unless Specified)

## Specification Table

Material	Colour	Dielectric Strength (kV/mm)	Unshrunk Diameter	Fully Shrunk Diameter	Flammability Rating	External Length / Height (m)	Reel Length (m)	Part Number	
Irradiated polyolefin	Black	20	25.4	12.7	VW-1	5	-	SP254/5/BLACK	
Polyolefin	Clear		2.4	1.2	-	1.2		SP24/1.2/CLEAR	
Irradiated polyolefin			6.4	3.2				SP64/1.2/CLEAR	
Polyolefin			19	9.5				SP190/1.2/CLEAR	
Irradiated polyolefin			6.4	3.2				5	SP64/5/CLEAR
			38.1	19		SP381/5/CLEAR			
			2.4	1.2		150		SP24/RL/CLEAR	
			3.2	1.6				SP32/RL/CLEAR	
			4.8	2.4				SP48/RL/CLEAR	
			Irradiated polyolefin	Yellow		9.5		4.7	75
12.7						6.3		SP127/RL/CLEAR	
19	9.5				60	60		SP190/RL/CLEAR	
38.1	19				30	30		SP381/RL/CLEAR	
Polyolefin	1.6		0.8		VW-1	1.2		-	SP16/1.2/YELLOW
	2.4		1.2						SP24/1.2/YELLOW
	3.2		1.6						SP32/1.2/YELLOW
	4.8		2.4						SP48/1.2/YELLOW
Irradiated polyolefin	6.4		3.2						SP64/1.2/YELLOW
	9.5		4.7						SP95/1.2/YELLOW
	12.7		6.3	SP127/1.2/YELLOW					
	19	9.5	SP190/1.2/YELLOW						
	25.4	12.7	SP254/1.2/YELLOW						
	38.1	19	SP381/1.2/YELLOW						
Polyolefin	50.8	25.4	SP508/1.2/YELLOW						
Irradiated polyolefin	1.6	0.8	5	SP16/5/YELLOW					

Dimensions : Millimetres (Unless Specified)