


**features**

- Excellent for high frequency applications
- Low DC resistance and high Q
- Operating temperature: -40°C ~ +125°C
- Low tolerance ±2% available
- Small size allows for high density mounting (1E, 1J, 2A, 2B)
- Marking: Yellow marking on blue protective coating (1E, 1J, 2A, 2B)
- Products with lead-free terminations meet EU RoHS and China RoHS requirements
- AEC-Q200 Qualified

**dimensions and construction**



Type (Inch Size Code)	Dimensions inches (mm)				
	L	W	c	d	t
<b>1E</b> (0402)	.039±.004 (1.0±0.1)	.02±.002 (0.5±0.05)	.006±.004 (0.15±0.1)	.01±.004 (0.25±0.1)	.014±.002 (0.35±0.05)
<b>1J</b> (0603)	.063±.008 (1.6±0.2)	.031±.004 (0.8±0.1)	.012±.004 (0.3±0.1)	.012±.004 (0.3±0.1)	.02±.004 (0.5±0.1)
<b>2A</b> (0805)	.079±.008 (2.0±0.2)	.049±.008 (1.25±0.2)	.016±.008 (0.4±0.2)	.012±.004 (0.3±0.2)	.02±.004 (0.5±0.1)
<b>2B</b> (1206)	.126±.008 (3.2±0.2)	.063±.008 (1.6±0.2)	.02±.008 (0.5±0.2)	.016 <sup>+0.008</sup> <sub>-.004</sub> (0.4 <sup>+0.2</sup> <sub>-.1</sub> )	.024±.004 (0.6±0.1)

**Inductance Marking**

Part 1J (nH)	Marking
1.0	L1
1.2	L2
1.5	L3
1.8	L4
2.2	22
2.7	27
3.3	33
3.9	39
4.7	47
5.6	56
6.8	68
8.2	82

Part 1J (nH)	Marking
10	10
12	12
15	15
18	H1
22	H2
27	H3
33	H4
39	H5
47	H6
56	H7
68	H8
82	H9

Part Marking	Value (nH) 2.2 - 8.2	Value (nH) 10 and higher
2A	Ex. = 2.2 = 2.2nH	Ex. = 15 = 15nH
2B	Ex. = 2N2 = 2.2nH	Ex. = 15N = 15nH

No marking on 1E (0402)

**ordering information**

New Part #	KL73	2A	T	TE	4N7	G
Type						
Size Code		1E: 0402 1J: 0603 2A: 0805 2B: 1206				
Termination Material			T: Sn			
Packaging				TP: 7" paper 2mm pitch (1E only - 10,000 pieces/reel) TE: 7" embossed plastic 4mm pitch (1J, 2A, 2B - 4,000 pieces/reel)		
Nominal Inductance					4N7: 4.7nH 47N: 47nH	
Tolerance						B: ±0.1nH C: ±0.2nH G: ±2% J: ±5%

For further information on packaging, please refer to Appendix A.

## applications and ratings

Part Designation	Nominal Inductance (nH)	Inductance Tolerance	Quality Factor Minimum	Self Resonant Frequency Minimum (MHz)	DC Resistance Maximum ( $\Omega$ )	Allowable DC Current Maximum (mA)	Measured Frequency (MHz)**						
KL731ETTPN56B	0.56	B: $\pm 0.1$ nH	7	14000	0.10	700	500						
KL731ETTPN68B	0.68												
KL731ETTPN82B	0.82												
KL731ETTP1N0*	1.0	B: $\pm 0.1$ nH C: $\pm 0.2$ nH	10	12000	0.15	500	500						
KL731ETTP1N2*	1.2			10000	0.20								
KL731ETTP1N5*	1.5			8000	0.25			650					
KL731ETTP1N8*	1.8			6000	0.30			600					
KL731ETTP2N2*	2.2			5000	0.50			550					
KL731ETTP2N7*	2.7			4000	1.00			500					
KL731ETTP3N3*	3.3			3000	1.50			450					
KL731ETTP3N9*	3.9			2500	2.00			350					
KL731ETTP4N7*	4.7			2000	3.00			300					
KL731ETTP5N6*	5.6			G: $\pm 2\%$ J: $\pm 5\%$	7			1500	5.00	150	200		
KL731ETTP6N8*	6.8	1000	200										
KL731ETTP8N2*	8.2	500											
KL731ETTP10N*	10					0.10							
KL731ETTP12N*	12						650						
KL731ETTP15N*	15							450					
KL731ETTP18N*	18								350				
KL731ETTP22N*	22											250	
KL731ETTP27N*	27												200
KL731ETTP33N*	33												
KL731JTTE1N0*	1.0			10	100								
KL731JTTE1N2*	1.2		15										
KL731JTTE1N5*	1.5	20	13000										
KL731JTTE1N8*	1.8		10000										
KL731JTTE2N2*	2.2		8000	0.15									
KL731JTTE2N7*	2.7		6000	0.25									
KL731JTTE3N3*	3.3		5000	0.50									
KL731JTTE3N9*	3.9		4000										
KL731JTTE4N7*	4.7		3000										
KL731JTTE5N6*	5.6		2500										
KL731JTTE6N8*	6.8		2000										
KL731JTTE8N2*	8.2		25		1500	1.0							
KL731JTTE10N*	10	1000											
KL731JTTE12N*	12	10			600	2.50							
KL731JTTE15N*	15				200								
KL731JTTE18N*	18					150							
KL731JTTE22N*	22			120									
KL731JTTE27N*	27						100						
KL731JTTE33N*	33												
KL731JTTE39N*	39												
KL731JTTE47N*	47												
KL731JTTE56N*	56												
KL731JTTE68N*	68												

\* Add tolerance character (B, C, G, J)

\*\* The operating temperature range of the coil (ambient temperature + self heating) must remain at +125°C or less

For complete environmental specifications, please refer to [www.koaspeer.com](http://www.koaspeer.com)

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

12/01/14

applications and ratings (continued)

Part Designation	Nominal Inductance (nH)	Inductance Tolerance	Quality Factor Minimum	Self Resonant Frequency Minimum (MHz)	DC Resistance Maximum ( $\Omega$ )	Allowable DC Current Maximum (mA)	Measured Frequency (MHz)**				
KL732ATTE1N0*	1.0	C: $\pm 0.2\text{nH}$	20	13000	0.25	900	500				
KL732ATTE1N2*	1.2			10000							
KL732ATTE1N5*	1.5			9000							
KL732ATTE1N8*	1.8		25	8000		0.50		800			
KL732ATTE2N2*	2.2			6000							
KL732ATTE2N7*	2.7			5000							
KL732ATTE3N3*	3.3			4500				700			
KL732ATTE3N9*	3.9			4000							
KL732ATTE4N7*	4.7			3000							
KL732ATTE5N6*	5.6			G: $\pm 2\%$ J: $\pm 5\%$				20	2500	1.00	400
KL732ATTE6N8*	6.8	2000									
KL732ATTE8N2*	8.2	1500									
KL732ATTE10N*	10	15	1000		1.50	250					
KL732ATTE12N*	12		800								
KL732ATTE15N*	15		700			150					
KL732ATTE18N*	18		600								
KL732ATTE22N*	22	C: $\pm 0.2\text{nH}$	25		9000	0.25	1000	500			
KL732ATTE27N*	27				7000						
KL732ATTE33N*	33				6000						
KL732ATTE39N*	39		35	5000	0.50		900				
KL732ATTE47N*	47			4500							
KL732ATTE56N*	56			4000			800				
KL732ATTE68N*	68			3500							
KL732ATTE82N*	82			3000							
KL732ATTE100*	100			G: $\pm 2\%$ J: $\pm 5\%$			40		2500	1.00	500
KL732BTTE2N2*	2.2								2000		
KL732BTTE2N7*	2.7	1500									
KL732BTTE3N3*	3.3	25	1000		2.00	400					
KL732BTTE3N9*	3.9		500								
KL732BTTE4N7*	4.7		400			200					
KL732BTTE5N6*	5.6		400								

\* Add tolerance character (B, C, G, J)

\*\* The operating temperature range of the coil (ambient temperature + self heating) must remain at +125°C or less

For L-Frequency and Q-Frequency Characteristics, see Environmental Applications at [www.koaspeer.com](http://www.koaspeer.com)





## environmental applications

### Performance Characteristics





Parameter	Requirements Maximum Limit	$\Delta$ L/L $\Delta$ Q/Q Typical	Test Method
Resistance to Soldering Heat	Without distinct damage in appearance and construction $\Delta$ L/L: $\pm 2\%$ , $\Delta$ Q/Q: $\pm 20\%$	$\Delta$ L/L: $\pm 0.5\%$ $\Delta$ Q/Q: $\pm 1.5\%$	260°C $\pm$ 5°C, 10s $\pm$ 1s
Rapid Change of Temperature	Without distinct damage in appearance and construction $\Delta$ L/L: $\pm 2\%$ , $\Delta$ Q/Q: $\pm 20\%$	$\Delta$ L/L: $\pm 0.5\%$ $\Delta$ Q/Q: $\pm 1.6\%$	-40°C (30min.)/ +125°C (30min.) 100 cycles
Low Temperature Exposure	Without distinct damage in appearance and construction $\Delta$ L/L: $\pm 2\%$ , $\Delta$ Q/Q: $\pm 20\%$	$\Delta$ L/L: $\pm 0.7\%$ $\Delta$ Q/Q: $\pm 1.2\%$	-40°C $\pm$ 3°C, 1000h
High Temperature Exposure	Without distinct damage in appearance and construction $\Delta$ L/L: $\pm 2\%$ , $\Delta$ Q/Q: $\pm 20\%$	$\Delta$ L/L: $\pm 0.4\%$ $\Delta$ Q/Q: $\pm 1.3\%$	125°C $\pm$ 2°C, 1000h
Moisture Exposure	Without distinct damage in appearance and construction Insulation resistance: 50M $\Omega$ or more $\Delta$ L/L: $\pm 2\%$ , $\Delta$ Q/Q: $\pm 20\%$	$\Delta$ L/L: $\pm 0.4\%$ $\Delta$ Q/Q: $\pm 1.4\%$	40°C $\pm$ 2°C, 90%~95%RH, 1000h
Resistance to Solvent	Without distinct damage in appearance, construction and marking $\Delta$ L/L: $\pm 2\%$ , $\Delta$ Q/Q: $\pm 20\%$	$\Delta$ L/L: $\pm 0.6\%$ $\Delta$ Q/Q: $\pm 1.2\%$	Immerse the inductors for 30s $\pm$ 5s in the reagent (20°C ~ 25°C) of JIS K8839 (1995)

### Frequency Characteristics Test equipment: HP4291B impedance analyzer (1E, 1J, 2A, 2B)

#### L - Frequency Characteristics



#### Q - Frequency Characteristics



Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/21/14