


## 1.View and size(视图及尺寸)

| Main technical indicators(主要技术指标) |                                                                                |
|-----------------------------------|--------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                   | 5000                                                                           |
| 2.Working Temperature (温度)        | -55~+150 ℃                                                                     |
| 3.IP Rating (防护级别)                | IP 50                                                                          |
| 4.Diameter of socket end(插合端直径)   | φ1.3                                                                           |
| 5.Testing Voltage (测试电压)          | 1350V                                                                          |
| 6.Working Voltage (工作电压)          | 1450V                                                                          |
| 7.Rated Current (额定电流)            | 12A                                                                            |
| 8.Shell material(壳体材质)            | Brass (chromium plating)/(nickel plating) fixation ring/<br>黄铜 (镀铬) / (镍镀) 固定圈 |
| 9.Pin Material(插针材料)              | Copper alloy gold plating(铜合金镀金)                                               |
| 10.Insulator material(绝缘体材质)      | PPS                                                                            |


| Sum up(总结)                  |                                                        |
|-----------------------------|--------------------------------------------------------|
| Series(系列)                  | B                                                      |
| Shell style/model (外壳样式/型号) | ZCG-VWith two nuts (fixed back and forth)带有两个螺母 (前后固定) |
| Button (按键)                 | A button(一个按键)                                         |
| Termination type (终止类型)     | Mother solder tin(母焊锡)                                 |
| Line diameter awg(线材直径)     | 28-20AWG                                               |
| Cable diameterφ (电缆直径)      | 0-0                                                    |
| Match plug(匹配插头)            | TGG.2B.P06.CLAD52H                                     |

| Location pin combination (定位销组合) |                                          |               |                         |
|----------------------------------|------------------------------------------|---------------|-------------------------|
| (编号)<br>Number                   | Number of<br>positioning pins(定<br>位销数量) | Angle(角<br>度) | Series(系列)~2B           |
| G                                | One(1)                                   |               | (Zero degrees)0°        |
| A                                | Two(2)                                   | A             | Thirty degrees(30°)     |
| B                                | Two(2)                                   |               | Forty-five degrees(45°) |
| C                                | Two(2)                                   |               | Sixty degrees(60°)      |
| D                                | Two(2)                                   | Y             | 95 degrees (95°)        |
| E                                | Two(2)                                   | β             | 120 degrees(120°)       |
| F                                | Two(2)                                   |               | 145 degrees(145°)       |
| J                                | Two(2)                                   | A             | 37.5degrees(37.5°)      |
| K                                | Two(2)                                   |               | 52.5degrees(52.5°)      |
| L                                | Two(2)                                   | Y             | Seventy degrees(70°)    |


|        | A      | B      | C√     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |



|    | A    | L    | E     | M    | S1   | S2   |
|----|------|------|-------|------|------|------|
| MM | φ20  | 18.5 | M15*1 | 3.5  | 13.5 | 17   |
| in | 0.79 | 0.73 |       | 0.14 | 0.53 | 0.67 |




Welded surface  
(焊接面)



Panel hole size  
(面板开孔尺寸)



(Welded mother  
adhesive core)  
焊接型母胶芯



Positive view of the socket  
(插座正视图)

|                                 |                  |
|---------------------------------|------------------|
| Model(型号)                       | ZCG.2B.P06.C.L.L |
| Positioning pin(定位销)            |                  |
| Series(系列)                      |                  |
| Needle core configuration(针芯配置) |                  |
| Outer casing(外壳)                |                  |
| Insulator(绝缘体)                  |                  |
| Needle core(针芯)                 |                  |

|                                  |  |          |  |                                      |          |                                        |
|----------------------------------|--|----------|--|--------------------------------------|----------|----------------------------------------|
| DESIGNED (设计)                    |  | DATE(日期) |  | SCALE(比例)                            | N/A(不适用) | MODEL TYPE<br>型号类型: ZCG.2B.P06.CLL     |
| CHECKED (校对)                     |  | DATE(日期) |  | VIEW(视图)                             |          | PART NO. 2B6 core socket<br>名称: 2B6芯插座 |
| APPROVED (审核)                    |  | DATE(日期) |  | UNIT(单位)                             | MM       | DWG NO.:                               |
| REVISIONS                        |  |          |  | MATERIAL (材料)                        |          | WEIGHT(重量) SHEET(页) REVISION(修订)       |
| www.helloxkb.com www.helloxkb.cn |  |          |  | XKB INDUSTRIAL PRECISION CO.,LIMITED |          | 1/1 A0                                 |