

Search within category

GO

BUY NOW

DESIGN / INSTALL



BSV18X-E

Butt Splice, 22 – 18 AWG, vinyl insulated, convenience package.

Specs	Packaging Details	Tools	Documents	★ Add to Favorites	🛒 Add to BOM
Style	Butt Splice				
Wire Range In. (mm²)	22 - 18 AWG (0.5 - 1.5)				
Barrel Configuration	Expanded				
Barrel Type	Brazed Seam				
Base Material	Copper				
Insulation	Vinyl				
Panduit Color Code	Red				
Plating Type	Tinned				
Part Number Series	BSV				
Length In (mm)	1.03 (26.2)				
Max. Insulation Diameter In. (mm)	0.17 (4.3)				
Wire Strip Length In. (mm)	5/16" (7.9)				
Flammability Rating	V0				
Max. Voltage Rating	600V				
CA-800/EZ Series Crimp Die	—				
CA9 Series Crimp Die	—				
Tool	CT-100A, CT-600-A, CT-1550, CT-1551, CT-2500				
CSA Certified	C22.2 No 65				
UL Listed	UL 486C				
Packaging Type	Bag				
Pieces Per Reel	—				
Material	Vinyl				
Part Features	• Expanded wire entry designed to accommodate wire with a larger insulation thickness • Designed to splice two solid or stranded wires together to repair or lengthen wires • Internal wire stop assures proper length of insertion into terminal barrel				
RoHS Compliancy Status	Compliant				
Min. Order Qty.	20				