

[illegible]

接触电阻: 80mΩ Max

Poles	A	B
20	8.20	4.50
22	8.70	5.00
30	10.70	7.00
34	11.70	8.00
40	13.20	9.50
50	15.70	12.00
60	18.20	14.50
70	20.30	17.00
80	23.20	19.50
100	28.20	24.50
120	33.20	29.50

[illegible][illegible][illegible]

	REVISIONS						
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN		
A0	N/A		INITIAL RELEASE	/	/		
A1	N/A		图面升级整理图面	2025.2.14	阿树		

Specifications:

规格:

Voltage rating:60V AC/DC
额定电压: 60V AC/DC

Current rating:0.5A AC/DC
额定电流: 0.5A AC/DC

Withstanding voltage:1500V AC/minute
耐受电压: 1500V AC/分钟

Temperature range:-55℃~+105℃
温度范围: -55℃~+105℃

Insulation resistance:500MΩ min
绝缘电阻: 500MΩ Min

Contact resistance:80mΩ Max
接触电阻: 80mΩ Max

PART NO.:

X0528 W V S-80 A S-LP V01

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

①Series No
②Category:W-Wafer
③Welding Board Angle:V-Stright 180°
④Welding Way: S-SMT
⑤Row No.Pin No:XX-20-120P
⑥Total Height:A=2.40mm;B=2.90mm;C=3.40mm
⑦Special No:S-With positioning Columm
⑧Material:LP-LCP UL 94V-O
⑨Plating:V01-Gold Flash

Total Height (H)	Male Height(C)	D
3.0mm	2.40	0.85
3.5mm	2.90	1.35
4.0mm	3.40	1.85

Poles	A	B
20	8.20	4.50
22	8.70	5.00
30	10.70	7.00
34	11.70	8.00
40	13.20	9.50
50	15.70	12.00
60	18.20	14.50
70	20.30	17.00
80	23.20	19.50
100	28.20	24.50
120	33.20	29.50

X0582WS-80AS-LPV01	LCP	Phosphor copper	X0582WS
PART NO	Material	Material(Pin)	Suitable XKB Wafer

AUGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	

DESIGN

CHECKED

APPROVED

阿树

UNIT: mm/in

SIZE: A4

MODEL TYPE:
0.5mm BTB Style Connector

PART NO.:
X0582WS-80AS-LPV01

DWG NO.:

SCALE	PAGE	REVISION
N/A	1/1	A1

KXB INDUSTRIAL PRECISION CO.,LIMITED

[illegible]