







RoHS
Compliant

ZONE		EC N.O.	DESCRIPTION	DRAWING	DATE
A			INITIAL	林生财	2020.02.18

NOTES:
1.MECHANICAL PERFORMANCE,
1-1.INSERTION FORCE: 5N~20N.
1-2.REMOVAL FORCE: 5N~20N.
1-3.DURABILITY: 10000 CYCLES.
2.ELECTRICAL PERFORMANCE,
2-1. CURRENT RATING:5.0A
2-2. LLCR:VBUS & GND PINS AND OTHER
PINS: 40mΩ/PIN MAX.SHIELD: 50mΩ/MAX.
2-3.INSULATION RESISTANCE: 100MΩ MIN
2-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V
FOR 1 MINUTE.
3.ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -25°C~+85°C.



3D VIEW



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

PIN ASSIGNMENTS:

PIN No.	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
SIGNAL NAME	GND	TX1+	TX1-	Vbus	CC1	D+	D-	SBU1	Vbus	RX2-	RX2+	GND
PIN No.	B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
SIGNAL NAME	GND	RX1+	RX1-	Vbus	SUB2	D-	D+	CC2	Vbus	TX2-	TX2+	GND

6	EMI PLATE	STAINLESS STEEL T=0.10		1
5	MID PLATE	STAINLESS STEEL T=0.15	Tin Plating Overall	1
4	SHELL	STAINLESS STEEL T=0.3	Nickel Plating Overall	1
3	TERMINAL 2	COPPER ALLOY T=0.15	Under Plating: Ni; Contact Plating: Au Soldering Plating: Au	12
2	TERMINAL 1	COPPER ALLOY T=0.15	Under Plating: Ni; Contact Plating: Au Soldering Plating: Au	12
1	HOUSING	HIGH TEMP.THERMOPLASTIC	COLOR BLACK UL94V-0	1
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

LZG




LZG INDUSTRIAL CO. LTD

DRAWING:	林生财	DATE:	2020.02.18	SCALE:	1:1
CHECK:	李宏鑫	DATE:	2020.02.18	MATERIAL:	*
APPROVAL:	杨进宝	DATE:	2020.02.18	DWG. NO.	
DRAWING NO.	ZB48044-24SBAP-A			SHEET	1/1

PART NAME	USB TYPE C 24PIN	TOLERANCE UNLESS	0.0±0.20	0.1±0.2	UNIT:	mm
PART NO.	ZB48044-24SBAP-A	OTHERWISE SPECIFIED:	0.00±0.15	0.0±0.1		


RoHS
Compliant

ZONE	E C N . N O .	DESCRIPTION	DRAWING	DATE
A		INITIAL	林生财	2020.02.18




② 卷盘贴标签示意图

③ 10盘产品叠层示意图



④ 产品入外箱示意图



⑤ 外箱封箱示意图

NOTE:

1. QUANTITY/REEL: 900 PCS
数量/卷: 900 PCS
QUANTITY/INNER CARTON: 900 X 10 = 9000 PCS
数量/箱: 900 X 10 = 9000 PCS
2. FREE 28 CAVE IN THE FRONT CARRIER AND FREE 28 CAVE IN THE END CARRIER.
包装带内圈空28格, 外圈空28格.

LZG®

LZG INDUSTRIAL CO. LTD

PART NAME	USB TYPE C 24PIN	TOLERANCE UNLESS	0.0±0.20	0.1±0.2	UNIT:	mm
PART NO.	ZB48044-24SBAP-A	OTHERWISE SPECIFIED:	0.00±0.15	0.0±0.1		

DRAWING:	林生财	DATE:	2020.02.18	SCALE	1:1
CHECK:	李宏鑫	DATE:	2020.02.18	MATERIAL	*
APPROVAL:	杨进宝	DATE:	2020.02.18	DWG. NO.	
DRAWING NO.	ZB48044 PACKING DRAWING	SHEET	1/1		