



Fuse combination switches FUSERBLOC



References

► NFC and DIN - External front or right side operation



Rating (A) / Fuse size / Frame size	No. of poles	Switch I-O-TEST	CHANGEOVER switch I-O-II	Integrated solid neutral link	Door interlocked external front handle	Door interlocked TEST external front handle	Door interlocked external right-side handle	Door interlocked CHANGEOVER external front handle	Shaft extensions for external handle	Terminal shrouds ⁽¹⁾	Additional contact holder for U type AC ⁽²⁾
25 / 10x38 / 0	3 P	3631 3002	3670 3002	-	Padlockable I-O	Padlockable I-O-TEST					
	3 P + switch neutral	3631 4002	3670 4002		S1 type	S1 type					
	3 P + solid neutral	3631 5002	-								
CD 32 / 10x38 / 0	3 P	3631 3003	3670 3003		Black IP55 1411 2111	Black IP65 1413 2115	Padlockable I-O	Padlockable I-O-II	320 mm 1401 0532	-	3999 0710
	3 P + switch neutral	3631 4003	3670 4003				S1 type	S1 type			
	3 P + solid neutral	3631 5003	-								
32 / 14x51 / 0	3 P	3631 3004	3670 3004		Red/Yellow IP65 1414 2111	Red/Yellow IP65 1414 2115	Black IP55 1415 2111	Black IP55 1411 2113			
	3 P + switch neutral	3631 4004	3670 4004								
	3 P + solid neutral	3631 5004	-								
50 / 14x51 / 11	2 P	3831 2005	-		Padlockable I-O	Padlockable I-O-TEST	Red/Yellow IP65 1418 2111	Red/Yellow IP65 1414 2113			
	3 P	3831 3005	3870 3005		S1 type	S1 type					
	4 P	3831 6005	3870 6005		Black IP65 1413 2111	Black IP55 1411 2115				standard	
63 / 00C / 12	2 P	3831 2006	-	3829 9310							
	3 P	3831 3006	3870 3006		Red/Yellow IP65 1414 2111	Red/Yellow IP65 1414 2115					
	4 P	3831 6006	3870 6006								
100 / 22x58 / 13	2 P	3831 2010	-		Padlockable I-O	Padlockable I-O-TEST	Padlockable I-O	Padlockable I-O-II	320 mm 1400 1032		
	3 P	3831 3010	3870 3010		S2 type	S2 type	S2 type	S2 type		2 P 3998 2016	
	4 P	3831 6010	3870 6010		Black IP65 1423 2111	Black IP55 1421 2115	Black IP55 1425 2111	Black IP55 1421 2113		3 P 3998 3016	
125 / 22x58 / 13	2 P	3831 2011	-								
	3 P	3831 3011	3870 3011		Red/Yellow IP65 1424 2111	Red/Yellow IP65 1424 2115	Red/Yellow IP65 1428 2111	Red/Yellow IP65 1424 2113		4 P 3998 4016	
	4 P	3831 6011	3870 6011								

Auxiliary contacts pre-break and signalisation I-O-TEST (see "Accessories" pages)

Auxiliary contacts for fuse blown indication (see "Accessories" pages)

S type auxiliary contacts for signalisation I-O: as standard operation (see "Accessories" pages)

ST type auxiliary contacts for signalisation I-O-TEST: TEST operation (see "Accessories" pages)

Drive shaft kit for S and ST type auxiliary contacts for signalisation (see "Accessories" pages)

Handle key interlocking accessories (see "Accessories" pages)

Label holder (see "Accessories" pages)

(1) Top/bottom.

(2) 4 auxiliary contacts as standard, without additional holder, the additional holder is for extra 4 auxiliary contacts.