

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-40V	3.7mΩ@-10V	-120A



合肥矽普半导体

Siliup Semiconductor Technology Co., Ltd

技术 品质 服务

www.siliup.com


Feature

- Fast Switching
- Low Gate Charge and Rdson
- Advanced Split Gate Trench Technology
- 100% Single Pulse avalanche energy Test

Applications


- PWM Application
- Hard switched and high frequency circuits
- Power Management

Package



PDFN5×6-8L

Circuit diagram



Marking



40P04AGH :Device Code
** :Week Code

Order Information

Device	Package	Unit/Tape
SP40P04AGHNK	PDFN5X6-8L	5000

Absolute maximum ratings (Ta=25°C, unless otherwise noted)

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	-40	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current (Tc=25°C)	I_D	-120	A
Continuous Drain Current (Tc=100°C)	I_D	-80	A
Pulsed Drain Current	I_{DM}	-480	A
Single Pulse Avalanche Energy ¹	E_{AS}	950	mJ
Power Dissipation (Tc=25°C)	P_D	150	W
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	0.83	°C/W
Storage Temperature Range	T_{STG}	-55 to 150	°C
Operating Junction Temperature Range	T_J	-55 to 150	°C


Electrical characteristics (Ta=25°C, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	VGS=0V , ID= -250uA	-40	-	-	V
Drain-Source Leakage Current	IDSS	VDS=-32V , VGS=0V , TJ=25℃	-	-	-1	uA
Gate-Source Leakage Current	IGSS	VGS=±20V , VDS=0V	-	-	±100	nA
Gate Threshold Voltage	VGS(th)	VGS=VDS , ID = -250uA	-2	-3	-4	V
Static Drain-Source On-Resistance	RDS(ON)	VGS=-10V , ID= -20A	-	3.7	4.7	mΩ
Dynamic characteristics						
Input Capacitance	Ciss	VDS=-20V , VGS=0V , f=1MHz	-	4539	-	pF
Output Capacitance	Coss		-	1236	-	
Reverse Transfer Capacitance	Crss		-	74	-	
Total Gate Charge	Qg	VDS=-20V , VGS=10V , ID=-85A	-	62	-	nC
Gate-Source Charge	Qgs		-	12.5	-	
Gate-Drain Charge	Qgd		-	8	-	
Switching Characteristics						
Turn-On Delay Time	Td(on)	VDD=-20V , VGS=10V , RG=1.6Ω,ID=-85A	-	20.8	-	nS
Rise Time	Tr		-	31	-	
Turn-Off Delay Time	Td(off)		-	80	-	
Fall Time	Tf		-	27	-	
Diode Characteristics						
Diode Forward Voltage	VSD	VGS=0V , IS=-1A , TJ=25℃	-	-	-1.2	V
Maximum Body-Diode Continuous Current	IS		-	-	-120	A
Reverse Recovery Time	Trr	IS=-20A, di/dt=100A/us, TJ=25℃	-	55	-	nS
Reverse Recovery Charge	Qrr		-	96	-	nC


Note :

1. The test condition is $V_{DD}=-20V, V_{GS}=-10V, L=0.5mH, R_G=25\Omega$


Typical Characteristics




Output Characteristics




Rdson-Junction Temperature




Transfer Characteristics




Gate Charge




Rdson- Drain Current




Source- Drain Diode Forward




Capacitance vs Vds




Power De-rating



Safe Operation Area




Current De-rating




Normalized Maximum Transient Thermal Impedance


PDFN5X6-8L Package Information



Top View
[顶视图]



Bottom View
[背视图]



Side View
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	3.910	4.110	0.154	0.162
E1	3.375	3.575	0.133	0.141
D2	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°