

**PRODUCTS**

- Rocker switches
- Pushbutton switches
- Toggle switches
- Slide switches
- Rotary switches
- Foot switches
- Tact and key switches**
- Snap-action switches
- Micro-signal switches
- ECO switches
- Sensors
- Systems and modules
- Accessories
- General information
- Catalog request / download

PRODUCTS ▶ TACT AND KEY SWITCHES

## Tact and key switches

### SERIES 6425 - KEY SWITCHES - TO 100 MA 28 V

[◀ Show previous product](#)
[Show next product ▶](#)

6425.5111

[Drawing](#)
[Accessories](#)


Similar to original product

[→ Print data sheet](#)

Product number	6425.5111
Miscellaneous	LED lower for button 834 900 ... and 835 900 ...
Pitch	16 + 19 mm
Switching function	Normally open contact (SPNO)
Number of poles	1-pole
connections	PCB terminal
Mechanical life endurance	1E6
Rating IEC	100 mA 28 V
Contact resistance (new condition)	< 250 mOhm
Insulation resistance (new condition)	> 100 MOhm
Ambient temperature	-20 °C ... +70 °C
Actuators and additional actuators	POM
Housing description	PBTP
Connection surface	external connection tinned
Contact material	Au
Contact distance	< 3 mm
Lighting	red
Miscellaneous	The key base of the standard key can be snapped into a 1.2 mm thick frame with a cut-out of 13.55 x 13.55 mm.
Operating force	0.7 N
Bounce time	< 5 ms
Total travel / stroke	1.4 ± 0.2 mm
Shop / Stock version	